



Trench Schottky Rectifier

FEATURES

- Patented Trench Schottky technology
- Excellent high temperature stability
- Low forward voltage
- Low power loss/ high efficiency
- High forward surge capability
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition


ITO-220AB


TYPICAL APPLICATIONS

Trench Schottky barrier rectifier are designed for high frequency miniature switched mode power supplies such as adapters, lighting and on-board DC/DC converters.

MECHANICAL DATA

Case: ITO-220AB

Molding compound meets UL 94 V-0 flammability rating

Packing code with suffix "G" means green compound (halogen-free)

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 2 whisker test

Polarity: As marked

Mounting torque: 0.56 Nm max.

Weight: 1.7 g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)											
PARAMETER				SYMBOL	TSF10H45C			TSF10H60C			UNIT
Maximum repetitive peak reverse voltage				V _{RRM}	45			60			V
Maximum average forward rectified current		per device		I _{F(AV)}	10						A
		per diode			5						
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load per diode				I _{FSM}	100						A
Voltage rate of change (Rated V _R)				dV/dt	10000						V/μs
					Min.	Typ.	Max.	Min.	Typ.	Max.	
Instantaneous forward voltage per diode (Note1)		I _F = 2.5A	T _J = 25°C	V _F	-	0.44	-	-	0.46	-	V
		I _F = 5A			-	0.48	0.58	-	0.54	0.62	
		I _F = 2.5A	T _J = 125°C		-	0.33	-	-	0.38	-	
		I _F = 5A			-	0.40	0.50	-	0.48	0.56	
Instantaneous reverse current per diode at rated reverse voltage			T _J = 25°C	I _R	-	-	500	-	-	500	μA
			T _J = 125°C		-	5	15	-	6	25	mA
Typical thermal resistance per diode				R _{θJC}	5.5						°C/W
Operating junction temperature range				T _J	- 55 to +150						°C
Storage temperature range				T _{STG}	- 55 to +150						°C

Note 1: Pulse Test with Pulse Width=300μs, 1% Duty Cycle

ORDERING INFORMATION

PART NO.	PACKING CODE	PACKING CODE SUFFIX	PACKAGE	PACKING
TSH10HxxC (Note 1)	C0	G	ITO-220AB	50 / Tube

Note 1: "xx" defines voltage from 45V (TSF10H45C) to 60V (TSF10H60C)

EXAMPLE

PREFERRED PART NO.	PART NO.	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
TSF10H45C C0G	TSF10H45C	C0	G	Green compound

RATINGS AND CHARACTERISTICS CURVES

($T_A=25^\circ\text{C}$ unless otherwise noted)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG. 2- TYPICAL FORWARD CHARACTERISTICS




FIG. 3- TYPICAL FORWARD CHARACTERISTICS




FIG. 4- TYPICAL REVERSE CHARACTERISTICS




FIG. 5- TYPICAL REVERSE CHARACTERISTICS






FIG. 6- TYPICAL JUNCTION CAPACITANCE




PACKAGE OUTLINE DIMENSIONS
ITO-220AB



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	4.30	4.70	0.17	0.19
B	2.50	3.16	0.10	0.12
C	2.30	2.96	0.09	0.12
D	0.46	0.76	0.02	0.03
E	6.30	6.90	0.25	0.27
F	9.60	10.30	0.38	0.41
G	3.00	3.40	0.12	0.13
H	0.95	1.45	0.04	0.06
I	0.50	0.90	0.02	0.04
J	2.40	3.20	0.09	0.13
K	14.80	15.50	0.58	0.61
L	-	4.10	-	0.16
M	12.60	13.80	0.50	0.54
N	-	1.80	-	0.07
O	2.41	2.67	0.09	0.11

MARKING DIAGRAM



P/N = Specific Device Code
G = Green Compound
YWW = Date Code
F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[TSF10H60C C0G](#) [TSF10H45C C0G](#)