

## Surface Mount Ultrafast Power Rectifiers

### FEATURES

- Glass passivated chip junction
- Ideal for automated placement
- Built-in strain relief
- Ultrafast recovery time for high efficiency
- Moisture sensitivity level: level 1, per J-STD-020
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



### MECHANICAL DATA

**Case:** DO-214AB (SMC)

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - green compound (halogen-free)

Base P/N with prefix "H" on packing code - AEC-Q101 qualified

**Terminal:** Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

with prefix "H" on packing code meet JESD 201 class 2 whisker test

**Polarity:** Indicated by cathode band

**Weight:** 0.21 g (approximately)

**DO-214AB (SMC)**

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted)								
PARAMETER	SYMBOL	MUR 305S	MUR 310S	MUR 315S	MUR 320S	MUR 340S	MUR 360S	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	150	200	400	600	V
Maximum RMS voltage	V <sub>RMS</sub>	35	70	105	140	280	420	V
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	150	200	400	600	V
Maximum average forward rectified current	I <sub>F(AV)</sub>	3						A
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I <sub>FSM</sub>	75						A
Maximum instantaneous forward voltage (Note 1) I <sub>F</sub> = 3 A, 25°C I <sub>F</sub> = 3 A, 150°C	V <sub>F</sub>	0.875 0.710				1.25 1.05		V
Maximum reverse current @ rated VR T <sub>J</sub> =25 °C T <sub>J</sub> =150 °C	I <sub>R</sub>	5 150				10 250		μA
Maximum reverse recovery time (Note 2)	T <sub>rr</sub>	25				50		ns
Typical thermal resistance	R <sub>θJL</sub>	11						°C/W
Operating junction temperature range	T <sub>J</sub>	- 55 to +175						°C
Storage temperature range	T <sub>STG</sub>	- 55 to +175						°C

Note 1: Pulse test with PW=300μs, 1% duty cycle

Note 2: Reverse Recovery Test Conditions: I<sub>F</sub>=0.5A, I<sub>R</sub>=1.0A, I<sub>RR</sub>=0.25A

ORDERING INFORMATION					
PART NO.	AEC-Q101 QUALIFIED	PACKING CODE	GREEN COMPOUND CODE	PACKAGE	PACKING
MUR3xxS (Note 1)	Prefix "H"	R7	Suffix "G"	SMC	850 / 7" Plastic reel
		R6		SMC	3,000 / 13" Paper reel
		M6		SMC	3,000 / 13" Plastic reel

Note 1: "xx" defines voltage from 50V (MUR305S) to 600V (MUR360S)

EXAMPLE					
PREFERRED P/N	PART NO.	AEC-Q101 QUALIFIED	PACKING CODE	GREEN COMPOUND CODE	DESCRIPTION
MUR360S R7	MUR360S		R7		
MUR360S R7G	MUR360S		R7	G	Green compound
MUR360SHR7	MUR360S	H	R7		AEC-Q101 qualified

## RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG.1 MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 TYPICAL FORWARD CHARACTERISTICS




FIG. 4 TYPICAL FORWARD CHARACTERISTICS




FIG. 5 TYPICAL REVERSE CHARACTERISTICS




FIG. 6 TYPICAL REVERSE CHARACTERISTICS






FIG. 7 TYPICAL JUNCTION CAPACITANCE




## PACKAGE OUTLINE DIMENSIONS




DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	2.90	3.20	0.114	0.126
B	6.60	7.11	0.260	0.280
C	5.59	6.22	0.220	0.245
D	2.00	2.62	0.079	0.103
E	1.00	1.60	0.039	0.063
F	7.75	8.13	0.305	0.320
G	0.10	0.20	0.004	0.008
H	0.15	0.31	0.006	0.012

SUGGESTED PAD LAYOUT



MARKING DIAGRAM



### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Taiwan Semiconductor:

[MUR305S R7](#) [MUR310S R7](#) [MUR315S R7](#) [MUR340S R7](#) [MUR310S R7G](#) [MUR320S R6](#) [MUR310S R6G](#)  
[MUR320S R7G](#) [MUR360SHR6](#) [MUR310S R6](#) [MUR315S R6G](#) [MUR305S R6G](#) [MUR360S R6](#) [MUR360SHR7](#)  
[MUR320SHR6](#) [MUR305S R7G](#) [MUR340S R6G](#) [MUR360S R7G](#) [MUR360S R6G](#) [MUR340S R6](#) [MUR340SHR6](#)  
[MUR320S R6G](#) [MUR315S R7G](#) [MUR340S R7G](#)