REV. Status ISSUE 2 REVISED AND REDRAWN ON CAD/CAM 01/08/92 HA

ISSUE 3 **TEMECULA** WAS CARSON 01/26/93 TS

ISSUE 4 ADDED DCM21-PC MICROTRAN AND SAFETY 01/20/96 TS

TELECOMMUNICATION DRY COUPLING TRANSFORMER DESIGNED TO OPERATE AT A MAX LEVEL OF +7dBm AND TO REFLECT A PRIMARY SOURCE IMPEDANCE OF APPROXIMATELY 600ΩCT WITH 600ΩCT LOAD ON SECONDARY

A. Electrical Specifications (@ 25°C)

1. Pri Source Impedance; 600Ω CT

2. Sec Load Impedance;  $600\Omega$  CT

3. Operating Level; -45 dBm to +7 dBm

4. Insertion Loss;

1.4 dB MAX @ 1 KHz, 0 dBm

Frequency Response;

±0.5 dB 300 Hz to 3.5 KHz @ 0 dBm

6. Primary Impedance;

600  $\Omega$  +15%, -5% @ 300 Hz to 3.5 KHz, OdBm 600  $\Omega$  +10%, -5% @ 500 Hz to 2.5 KHz, 0dBm

7. Longitudinal Balance;

60 dB MIN @ 200 Hz to 1 KHz

40 dBm MIN @ 4 KHz

8. DC Resistance;

44 Ω ±20% (1-3) =

 $(4-6) = 56 \Omega \pm 20\%$ 9. Turns Ratio;  $(1-3) : (4-6) = 1 : 1.00 \pm 2\%$ 

10. Dielectric Strength;

1500 Vrms 1 minute @ Pri to Sec, and Pri to Core 1000 Vrms 1 minute @ Sec to Core


11. Total Harmonic Distortion;

0.5% MAX @ 300 Hz to 3.5 KHz, 0 dBm

12. Induced Voltage; (1-3) 250 Vrms 5 KHz 1 minute B. Marking; TTC-108, TAMURA, DCM21-PC, MICROTRAN, safety agency logos, 196-date code and country of origin


C. Safety; CSA-22.2 No. 66-M1988 File No. LR81383

UL 1863 File No. E142035



E. Mechanical Specifications

**-** 19.8(0.781)



3.81(0.150) MIN →  $1.02 \pm 0.25(0.04 \pm 0.01)$ 

4 + 0.2 $4 \le 20 \pm 0.3$ 

 $20 \le 50 \pm 0.4$ PREPARED BY:

Brennan ENGINEER:

T. Shiozawa QUALITY CONTROL:

SUBJECT TO C PRIOR NOTICE V. Casey

DWG CONTROL NO. REV P-A1-10017 ACAD\TTC\A1100171.DWG

TELECOMMUNICATION COUPLING **TRANSFORMER** 

CONTENTS OF THIS DRAWING ARE TANKRA CORPORATION OF AMERICA SUBJECT TO CHANGE WITHOUT 43359 BUSINESS PARK DRIVE TEMECULA CA 02500\_6694 43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624 (909) 699-1270 FAX 9096769482

APPROVED: V. Casey

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tamura: