REV. Status REVISION -12/24/94 TS

REVISION A DCR (4-6)1300Ω WAS 13000Ω 9/5/95 TS

REVISION B ADDED PM17-M MICROTRAN 10/03/95 TS

REVISION C ADDED RoHS 12/02/05 MP


REVISION D ADDED TEMP **RATING** 4/29/15 MP TELECOMMUNICATION COUPLING MINIATURE ENCAPSULATED TRANSFORMER DESIGNED TO OPERATE 40mW MAX IN PRIMARY AND REFLECT A PRIMARY SOURCE IMPEDANCE OF APPROXIMATELY 10KΩCT WITH 10KΩCT LOAD ON SECONDARY.


- A. Electrical Specifications (@ 20 ° C)
 - 1. Pri Source Impedance; $10K\Omega$ CT
 - 2. Sec Load Impedance; $10K\Omega$ CT
 - 3. Pri DC Current; 1 mA MAX
 - 4. Operating Level; 40 mW MAX @ 300 Hz
 - 5. Frequency Response (relative to 1 KHz); ±2.0 dB, @ 300 Hz to 100 KHz
 - 6. Longitudinal Balance; 60 dB MIN @ 1 KHz
 - 7. DC Resistance;

(1-3) 1000Ω ±20% (4-6) 1300Ω ±20%

- 8. Turns Ratio; (1-3): (4-6) = 1 : 1.00 ±2%
- 9. Dielectric Strength;

500 Vrms 0.5 minute @ Pri - Sec





TOLERANCES (mm) 4 ± 0.2 $4 \le 20 \pm 0.3$ $20 \le 50 \pm 0.4$

PREPARED BY: C. POPPE

ENGINEER:	DF
MATHI P.	
SAFETY ENGINEER	C

RAWING CONTROL NO. REV P-A1-11225

 $2.50\pm0.25(0.10\pm0.01)$ TYP

MODEL DESCRIPTION AUDIO COUPLING MINIATURE ENCAPSULATED XFMR

CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT 1040 SOUTH ANDREASEN DRIVE, \$100 ESCONDIDO, CA. 92029 1040 SOUTH ANDREASEN DRIVE, #100 ESCONDIDO, CA. 92029 (951) 699-1270 FAX 7607400536

-10.4(0.41)MAX

MODEL SPECIFICATION MET-09 DIM: mm[In] SCL: 2/1

APPROVED:

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING. M. PITCHAI

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tamura: