

REV. Status

REVISION –
06/15/92 YSREVISION A
FLIPPED RADII
& CLARIFIED
MARKING
06/24/05 YSREVISION B
RoHS COMPLIANT
11/03/05 MPREVISION C
NOTE 5: 400 μ H
WAS 500 μ H
05/16/07 MP


A. Electrical specification (@ 25°C)

1. Power rating;
500 mW
2. Dielectric strength;
500 VDC 1 minute
3. Insulation resistance;
10,000 M Ω MIN @ 500 VDC
4. Turns ratio;
(1–2) : (3–4) : (5–6) = 2 : 1 : 1 \pm 5%
5. Primary open circuit inductance;
400 μ H MIN @ 1 KHz, 40 mV (1–2)
6. Primary ET–constant
8.5V– μ s MIN
7. Rise time;
5.6 ns MAX
8. Interwinding capacitance between primary and secondary;
11.0 PF MAX @ 100 KHz
9. Primary leakage inductance with shorted secondary;
1.1 μ H MAX @ 100 KHz
10. DC Resistance;
Primary (1–2) 1.3 Ω MAX
Secondary (3–4) 0.7 Ω MAX
Tertiary (5–6) 0.7 Ω MAX

B. Marking;

G507, TAM, date code and country of origin

C. Schematic diagram




PIN 1 Designation



"TAM" and country of origin (molded)

D. Mechanical Specification



PREPARED BY:

K. BRENNAN

ENGINEER:

M. PITCHAI

SAFETY ENGINEER

B. OCONNELL

APPROVED:

Y. SEKIGUCHI

DRAWING CONTROL NO.	REV	MODEL DESCRIPTION	MODEL SPECIFICATION
P-A1-10633	C	PULSE TRANSFORMER	G507
CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE		TAMURA CORPORATION OF AMERICA	
1040 SOUTH ANDREASEN DRIVE, #100 ESCONDIDO, CA. 92029		DIM: mm[In] SCL: 2/1 SH: 1 OF 1	
(951) 699-1270 FAX 7607400536		PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.	

RoHS
COMPLIANT

MODEL NUMBER

G507

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tamura:

G507