

# **Specification**

### **Patent Pending**

Part No : **GGBSFTP.45.9.A.08** 

Product Name : 45\*45\*9mm Terrablast Stacked Patch Antenna

Feature : GPS L1, GPS L2 and GPS L5 band, GLONASS, Galileo

and BeiDou Operation

Right-Hand Circularly Polarized Terrablast Patch

Single Feed Patch Assembly

Ultra-Impact Resistant

Tuned for Centre Positioning on a 50\*50mm

Ground-plane

Patent Pending Design

**RoHS Compliant** 





### 1. Introduction

The Taoglas GGBSFTP.45.9.A.08 is a 45\*45mm Terrablast GPS L1, GPS L2 and GPS L5, embedded stacked passive patch antenna with 9mm thickness. This patch is made from a revolutionary new material developed to meet the unique needs of the UAV and automotive industries. It uses a patent pending antenna technology which results in much lighter weight and withstands greater impacts.

Typical applicable industries are:

- Transportation
- Defense
- Marine
- Agriculture
- UAV navigation

The antenna has been tuned and tested on a 50\*50mm ground plane, working at GPS 1575.42MHz, 1227.6MHz and 1176.45MHz. This Terrablast patch also operates at other worldwide Navigation systems such as GLONASS, Galileo and BeiDou.

The GGBSFTP.45.9.A.08 is mounted via a pin and double sided adhesive. This antenna works well without modifications in most environment but can be tuned and further optimized to different ground planes and enclosures if this is required. Custom antenna modifications are subject to possible NRE and minimum order quantity.

Terrablast antennas are not suitable for SMD reflow. The correct method is manual soldering at a soldering temperature of 380°C +/- 20°C for a duration of 3 to 5 seconds. All Terrablast antennas undergo rigorous temperature, vibration and impact tests and exceed the highest ISO16750 standards.

For further information, or support to test and integrate Taoglas Terrablast technology please contact your regional Taoglas facility.



# 2. Specification

| ELECTRICAL               |                            |              |               |
|--------------------------|----------------------------|--------------|---------------|
|                          | GPS L1                     | GPS L2       | GPS L5        |
| Frequency                | 1575.42 MHz                | 1227.6 MHz   | 1176.45 MHz   |
| Return Loss              | ≤-10dB                     | ≤-10dB       | ≤-6dB         |
| Efficiency               | 63 %                       | 50 %         | 31 %          |
| Average<br>Gain          | -2 dB                      | -2.9 dB      | -4.9 dB       |
| Peak Gain                | 2.5 dBi typ.               | 1.1 dBi typ. | -0.8 dBi typ. |
| Polarization             | RHCP                       | RHCP         | RHCP          |
| Impedance                | 50 Ω                       | 50 Ω         | 50 Ω          |
| MECHANICAL               |                            |              |               |
| Dimensions               | 45 x 45 x 9 mm             |              |               |
| Material                 | Terrablast                 |              |               |
| Pin Diameter             | 0.9 mm                     |              |               |
| Pin Length               | 1.7 mm                     |              |               |
| Weight                   | 41.8g                      |              |               |
| ENVIRONMENTAL            |                            |              |               |
| Operation<br>Temperature | -30°C to 85°C              |              |               |
| Storage<br>Temperature   | -40°C to 95°C              |              |               |
| Humidity                 | Non-condensing 65°C 95% RH |              |               |


<sup>\*</sup> Antenna properties were measured with the antenna mounted on 50\*50mm Ground Plane.






## 3. Antenna Characteristics

#### 3.1 Return Loss




### 3.2 Efficiency






### 3.3 Peak Gain




# 3.4 Average Gain






# 4. 2D Antenna Radiation

### **4.1 Test Setup**







### 4.2 X-Y Plane



### **X-Z Plane**




### **Y-Z Plane**






# 5. 3D radiation pattern






# 6. Mechanical Drawing-Patch






### **6.1 Adhesive Thickness**



Red Line shows the adhesive without Liner – thickness 0.08~0.1mm

# 7. PCB Footprint Recommendation






# 8. Packaging

8 pcs GGBSFTP.45.9.A.08 per Tray Tray Dimensions - 255\*144\*12mm Weight - 350g

24 pcs GGBSFTP.45.9.A.08 per S Carton Carton Dimensions - 263\*154\*96mm Weight - 1kg

96 pcs GGBSFTP.45.9.A.08 per Large Carton Large Carton Dimensions - 327\*280\*218mm Weight - 4kg

Pallet Dimensions: 1200mm\*1000mm\*1280mm 36 Cartons per Pallet 9 Cartons per Layer, 4 Layers





Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taoglas:

GGBSFTP.45.9.A.08