APPROVED: DATE:															
										Rev	AWO #		Description	Date	Appr
						_						יטטע	RELEASED ED 5P, 8P OPTION	1/9/19	AY/RC
DATE		111LE:				_				A B			JPDATE SPEC.	9/23/20 3/3/21	LH/RC
CUSTOM CAB	_E ASSEME	BLIES AF	RE NON-	CANCEL	LABLE/N	ION-RET	URNABLE	-		D			JPDATE SPEC.	<u> ୬</u> ୲୬୮୮	
(Number of Conductors)	4P	5P	8P	12P	16P	24P	30P	36P	40P						
N (Pitch)	1.00±0.08	1.00 ±0.08	1.00 ±0.08	1.00 ±0.08	1.00±0.08	1.00 ±0.08	1.00 ±0.08	1.00 ±0.08	1.00±0.08	٥l	S1		AWM 2743 1005C 9	0V VW-1	52
P (Total Pitch)	3.00±0.10		7.00 ±0.10	11.0 ±0.10		23.00±0.10	29.00±0.10	35.00 ±0.10	39.00±0.10						
(Total Length)	101.6 ±2.00		101.6 ±2.00						101.6 ±2.00					i	
(Film Length)	93.60±2.00		93.60±2.00						93.60±2.00		⊗→	(printed))		@,
IL (Margin Width)	1.00±0.10	1.00±0.10					1.00 ±0.10		1.00±0.10	103			/ [_	
M (Total Width) W	5.00±0.12	6.00±0.12	9.00±0.12	13.00 ±0.12	17.00±0.12	25.00 ±0.12	31.00±0.12	37.00 ±0.12	41.00 ±0.12	5±0.03 M					
" (Strip Length) S1	4.00±1.00	4.00 ±1.00	4.00 ±1.00	4.00 ±1.00	4 .00 ±1.00	4.00 ±1.00	4.00 ±1.00	4 .00 ±1.00	4 .00 ±1.00	0.65	-		IL		
(Strip Length) S2	4.00±1.00	4.00 ±1.00	4.00 ±1.00	4.00 ±1.00	4.00 ±1.00	4.00 ±1.00	4.00 ±1.00	4 .00 ±1.00	4 .00 ±1.00	الاق		Тор	o insula tidr(te /printed)	+	
(Stiffener) B1	8.00±2.00	8.00 ±2.00	8.00±2.00	8.00 ±2.00	8.00±2.00	8.00±2.00	8.00±2.00	8.00±2.00	8.00±2.00	-					
(Stiffener) B2	8.00±2.00	8.00 ±2.00	8.00±2.00	8.00 ±2.00	8.00±2.00	8.00±2.00	8.00±2.00	8.00±2.00	8.00±2.00	t	B1		Under insula kbi() ⊢	B2	
(Slanting) A1	≤0.30	≤0.30	≤0.30	≪0.30	≪0.30	≤0.30	≤0.30	≪0.30	≤0.30	.005	_		L		_
(Slanting) A2	≤0.30	≤0.30	≤0.30	≤0.30	≤0.30	≤0.30	≤0.30	≪0.30	≤0.30	ct_0.035±0.005					
(Terminal thickness) t	0.30±0.03	0.30 ±0.03	0.30±0.03	0.30 ±0.03	0.30±0.03	0.30 ±0.03	0.30±0.03	0.30±0.03	$0.30\pm\!\!0.03$	0.03					
(Thickness) T	0.12 ±0.03	0.12 ±0.03	0.12±0.03	0.12±0.03	0.12±0.03	0.12 ±0.03	0.12±0.03	0.12±0.03	0.12±0.03	t t	A1				
(Number of Con CA-DK10-XX-10 T 04 05 08 12 16 24 30 36 40											A1	<u>0–0.3MA</u> X	Α <u>2</u>	<u>2 0-0.3ΜΑ</u> Σ	<u>_</u>
SPECIFICATIONS Material: Insulator: PET, Support Tape: UL Style: AWM Plating: Conductor: Tin Environmental: Lead free, RoH	color White PET, color 2743, 105 plated Cop	Blue. *C, 90V oper Flat			Rohs]			ALL TOLE	DIMENSIONS RANCES: EXC SEE C ROVALS AY AC	SE SPECIFIED ARE MILLIMETE CEPT AS NOTE HART DATE 1/9/1 1/9/1	D TITLE FI SAME SIZE X		AL LENGTH	5000 10 PITCH 101.6MM

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Adam Tech:

CA-DK10-12-101.6-A-44-88