>	σ	n	Ū
Electrical: Voltage rating: 150 VAC rms Current rating: 1.5 Amp Contact Resistance: 20 mohms max Insulation resistance: 1000 Mohms min @ 500 VDC Dielectric withstanding voltage: Contact to Contact: 1,000 VDC or AC Peak for 1 minute Contact to Screen and Test panel: 1,500 VDC or AC Peal Temperature Rating: Operating temperature: -40°C to +85°C Environmental: Lead free, RoHS compliant. 6 5	SPECIFICATIONS: Material: Insulator: PBT, glass reinforced, rated UL 94V-0 Insulator color: Black Contacts: Phosphor Bronze Cantacts Plating: Round contact Gold over Nickel underplate overall Flat contact Gold over Nickel underplate on contact area, Tin over Nickel underplate on solder tails (See chart for thickness)		APPROVED:
for 1 minute	.106 [2.70]	$\begin{array}{c} .498\\ .498\\ .132\\ .510\\ .3.35\\ .3.51\\ .3.45\\ .070\\ .136\\ .070\\ .170\\ .170\\ .170\\ .203\\ .170\\ .360\\ .3$	
SS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES [MM] RANCES: EXCEPT AS NOTED HES + .020 ØXX ± .015 ± .015 ØXXX ± .010 ROVALS DATE SS 5/2/05	RECOMMENDEDPCBLAYOUTPart NumberLED 1 (GreeMTJ-88ARX1-LDGreeMTJ-88ARX1-LHGreeMTJ-88ARX1-LPYellow/(GreeMTJ-88ARX1-LVGreeMTJ-88ARX1-LVGreeMTJ-88ARX1-L16Green/Y	$ \begin{array}{c} 0.25 \\ 0.51 \\ 0.51 \\ 12 \\ 12 \\ 12 \\ 12 \\ 12 \\ 12 \\ 12 \\ $	Rev AWO # C 540 [13.72]
ADAM TE(909 Rahway Avenue, Union, Phone: 908-687-5000 Fax: 90 TITLE MODULAR TELEPHONE JA(RIGHT ANGLE, WITH LED'S SIZE PART NO. MTJ-88ARX1-I X PART NO. MTJ-88ARX1-I X S0005C Iscale: NTS 2 I	LED 1 Color Green Yellow/Green Green Green/Yellow		
SHEET 1 OF	LED 2 Color Green Yellow Yellow/Green Yellow/Green Green/Yellow	$\begin{array}{c} 335 \\ 90] \\ \hline \\ 170 \\ [2.54] \\ [2.54] \\ [4.32] \\ 14.32 \\ 28 \\ 28 \\ 5 \\ 5 \\ 5 \\ 5 \\ 5 \\ 5 \\ 5 \\ 5 \\ 5 \\ $	Date Appr 8/3/16 AY/NP
		ი ი	ې م

6

S

4

ω

N

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Adam Tech:

MTJ-88ARX1-LP