

EPCOS Sample Kit 2012


NTC Inrush Current Limiters



NTC inrush current limiters

	S 153	S 235	S 236	S 237	S 238	S 364	S 464
T_A °C	-55 up to 170	-55 up to 170	-55 up to 170	-55 up to 170	-55 up to 170	-55 up to 170	-55 up to 170
R_{25} Ω	4.7 ... 33.0	4.7 ... 10.0	2.2 ... 120.0	1.0 ... 60.0	2.5 ... 16.0	1.0 ... 10.0	1.0 ... 10.0
P_{max} W	1.4	1.8	2.1	3.1	3.9	5.1	6.7
I_{max} A	1.3 ... 3.0	3.0 ... 4.4	1.5 ... 6.0	1.6 ... 9.0	4.0 ... 8.4	7.5 ... 16.0	8.0 ... 20.0
$B_{25/100}$ K	2800; 2900; 3000	2800; 2900	2700 ... 3450	2700 ... 4000	2800 ... 3165	2800 ... 3300	2800 ... 3300

Dimensional drawing in mm



Type	l	w_{max}	h_{max}	th_{max}	ϕd	Lead spacing [e]
S153	25 min.	8.5	13	6	0.6	5
S235	25 min.	9.5	14	6	0.6	5
S236	25 min.	11.5	16	6	0.6	5
S237	25 min.	15	22	7	0.8	7.5
S238	25 min.	16	23	7	1.0	7.5
S364	25 min.	21	28	7	1.0	7.5
S464	25 min.	26	31	7	1.0	7.5

Applications

- For every area of electrical engineering and electronics, e.g. SMPS, lighting control, telecom, power supply, entertainment electronics and automotive

Important information: It is incumbent on the customer to check and decide whether a product is suitable for use in a particular application. Our products are described in detail in our data sheets. Our *Important Notes* and the product-specific *Cautions and Warnings* must be observed. All relevant information is available through our sales offices.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[EPCOS / TDK:](#)

[B57321V2103J60](#) [B57888S0888M888](#)