


# TA58LT00F

## 150 mA Output Current and Tracking Regulator with ON/OFF Control Switch

The TA58LT00F consists of small-surface mount type tracking regulators with an output current of 150 mA (maximum) and an ON/OFF control switch. Control by an EN (ON/OFF) terminal enables the regulator to be operated only when required (output ON). The output voltage can be controlled to an arbitrary voltage between 2.5V and 13.4V by applying a necessary voltage to ADJ through a microcontroller, etc. It is also possible to enable or disable the regulator via the enable (ON/OFF) terminal. Enabling the regulator only when necessary contributes to the energy saving of equipment.


### Features

- Built-in ON/OFF control function (active high)
- Maximum output current : 150 mA
- Output voltage : 2.5 V to 13.4 V
- Tracking voltage accuracy :  $\pm 10$  mV (@ $T_j = 25^\circ\text{C}$ )
- Low standby current (output OFF mode) : 1  $\mu\text{A}$  (Typ.)
- Protection function : Overcurrent protection / overheating protection / Reverse connection of power supply / 60 V load dump
- Package type : Surface-mount 5-pin New PW-Mold




Weight : 0.36 g (Typ.)

### Pin Assignment



### Marking



Note 1: A line under a Lot No. identifies the indication of product Labels.

Not underlined: [[Pb]]/INCLUDES > MCV

Underlined: [[G]]/RoHS COMPATIBLE or [[G]]/RoHS [[Pb]]

Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. The RoHS is the Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

The product(s) in this document ("Product") contain functions intended to protect the Product from temporary small overloads such as minor short-term overcurrent, overvoltage, or overheating. The protective functions do not necessarily protect Product under all circumstances. When incorporating Product into your system, please design the system (1) to avoid such overloads upon the Product, and (2) to shut down or otherwise relieve the Product of such overload conditions immediately upon occurrence. For details, please refer to the notes appearing below in this document and other documents referenced in this document.

Start of commercial production  
2005-06


## Pin Description

Pin No.	Symbol	Description
1	IN	Input terminal. Connected by capacitor ( $C_{IN}$ ) to GND.
2	EN	Output ON/OFF control terminal. Output is ON when this pin is set to "High", OFF when this pin is open or set to "Low".
3	GND	Ground terminal
4	ADJ	Adjustment terminal
5	OUT	Output terminal. Connected by capacitor ( $C_{OUT}$ ) to GND.

## How to Order

Product No.	Package	Package Type and Capacity
TA58LT00F(T6L1,Q)	5-pin New PW-Mold : Surface-mount	Tape (2000 pcs/reel)

## Block Diagram



**Absolute Maximum Rating (Ta = 25°C)**

Characteristic		Symbol	Rating	Unit
Input voltage		V <sub>IN</sub>	-38 to 38	V
EN Input voltage		V <sub>EN</sub>	-0.3 to 38	V
ADJ Input voltage		V <sub>ADJ</sub>	-0.3 to 38	V
Output current		I <sub>OUT</sub>	150	mA
Junction temperature		T <sub>j</sub>	150	°C
Operating Junction temperature		T <sub>jopr</sub>	-40 to 150	°C
Storage temperature		T <sub>stg</sub>	-55 to 150	°C
Power dissipation	Ta = 25°C	P <sub>D</sub>	1	W
	Tc = 25°C		10	

Note 2: Do not apply current and voltage (including reverse polarity) to any pin that is not specified.

Note 3: If it is connected EN terminal to IN terminal, be careful so that the negative voltage is not impressed on EN terminal.

Note 4: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc.).

**Thermal Characteristics**

Characteristic	Symbol	Max	Unit
Thermal resistance, junction to ambient	R <sub>th(j-a)</sub>	125	°C/W
Thermal resistance, junction to case	R <sub>th(j-c)</sub>	12.5	°C/W

**Operating conditions**

Characteristic	Symbol	Min	Typ.	Max	Unit
Input voltage	V <sub>IN</sub>	6	—	26	V
ADJ Input voltage	V <sub>ADJ</sub>	2.5	—	13.4	V

**Protection Function (Reference)**

Characteristic	Symbol	Test Condition	Min	Typ.	Max	Unit
Thermal shutdown	T <sub>SD</sub>	V <sub>IN</sub> = 14 V	150	175	—	°C
Thermal shutdown hysteresis width	T <sub>SD(hys)</sub>		—	15	—	°C
Peak circuit current	I <sub>PEAK</sub>	V <sub>IN</sub> = 14 V, T <sub>j</sub> = 25°C	—	210	—	mA
Short circuit current	I <sub>SC</sub>	V <sub>IN</sub> = 14 V, T <sub>j</sub> = 25°C	—	210	—	mA
Overvoltage protection	V <sub>OV</sub>	—	38	—	—	V

Note 5: Ensure that the devices operate within the limits of the maximum rating when in actual use.

Note 6: The output voltage shuts down when the overvoltage protection circuit operates.

## Electrical Characteristics


(Unless otherwise specified,  $2.5\text{ V} \leq V_{\text{ADJ}} \leq 13.4\text{ V}$ ,  $V_{\text{EN}} = \text{H}$ ,  $C_{\text{IN}} = 0.33\text{ }\mu\text{F}$ ,  $C_{\text{OUT}} = 10\text{ }\mu\text{F}$ ,  $\text{ESR} = 1\text{ }\Omega$ ,  $T_j = -40\text{ to }125^\circ\text{C}$ )

Characteristic	Symbol	Test Condition	Min	Typ.	Max	Unit
Tracking accuracy	$\Delta V_{\text{OUT}}$	$V_{\text{IN}} = 14\text{ V}$ , $I_{\text{OUT}} = 50\text{ mA}$	-10	—	+10	mV
		$6\text{ V} \leq V_{\text{IN}} \leq 26\text{ V}$ , $5\text{ mA} \leq I_{\text{OUT}} \leq 100\text{ mA}$ , $-40^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$	-20	—	+20	
Line regulation	Reg·line	$6\text{ V} \leq V_{\text{IN}} \leq 26\text{ V}$ , $I_{\text{OUT}} = 50\text{ mA}$	—	—	25	mV
Load regulation	Reg·load	$V_{\text{IN}} = 14\text{ V}$ , $5\text{ mA} \leq I_{\text{OUT}} \leq 100\text{ mA}$	—	—	35	mV
Quiescent current	$I_{\text{B}}$	$6\text{ V} \leq V_{\text{IN}} \leq 26\text{ V}$ , $I_{\text{OUT}} = 0\text{ A}$	—	—	0.8	mA
		$6\text{ V} \leq V_{\text{IN}} \leq 26\text{ V}$ , $I_{\text{OUT}} = 100\text{ mA}$	—	—	15	
Quiescent current (OFF mode)	$I_{\text{B(ON)}}$	$6\text{ V} \leq V_{\text{IN}} \leq 26\text{ V}$ , $V_{\text{EN}} = 0\text{ V}$	—	—	20	$\mu\text{A}$
Dropout voltage	$V_{\text{D}}$	$I_{\text{OUT}} = 50\text{ mA}$	—	—	0.3	V
		$I_{\text{OUT}} = 100\text{ mA}$	—	—	0.6	
Output control voltage (ON)	$V_{\text{EN(ON)}}$	$I_{\text{OUT}} = 50\text{ mA}$	3	—	—	V
Output control voltage (OFF)	$V_{\text{EN(OFF)}}$	—	—	—	0.5	V
Output control current (ON)	$I_{\text{EN(ON)}}$	$V_{\text{IN}} = 14\text{ V}$ , $V_{\text{EN}} = 5\text{ V}$ , $I_{\text{OUT}} = 1\text{ mA}$	—	—	120	$\mu\text{A}$

## Electrical Characteristics Common to All Products

- $T_j = 25^\circ\text{C}$  in the measurement conditions of each item is a regulation for where the standard condition when a pulse test is carried out, and any drift in the electrical characteristic due to a rise in the junction temperature of the chip may be disregarded.

## Standard Application Circuit















- Place  $C_{IN}$  as close as possible to the input terminal and GND. Place  $C_{OUT}$  as close as possible to the output terminal and GND. Although capacitor  $C_{OUT}$  acts to smooth the dc output voltage during suspension of output oscillation or load change, it might cause output oscillation in a cold environment due to increased capacitor ESR. It is therefore recommended to use a capacitor with small temperature sensitivity. Please connect the resistance of 0.5 to  $2\Omega$  with the series when the ceramic capacitor is used.







The IC may oscillate due to external conditions (output current, temperature, or the type of the capacitor used). The type of capacitor required must be determined by the actual application circuit in which the IC is used.

## Usage Precautions

- Note that, depending on the load conditions, a steep increase in the input voltage ( $V_{IN}$ ) may cause a momentary rise in output voltage ( $V_{OUT}$ ) even if the EN (enable) pin is Low.
- Low voltage  
Do not apply voltage to the Product that is lower than the minimum operating voltage, or the Product's protective functions will not operate properly and the Product may be permanently damaged.
- Overcurrent Protection  
The overcurrent protection circuits in the Product are designed to temporarily protect Product from minor overcurrent of brief duration. When the overcurrent protective function in the Product activates, immediately cease application of overcurrent to Product. Improper usage of Product, such as application of current to Product exceeding the absolute maximum ratings, could cause the overcurrent protection circuit not to operate properly and/or damage Product permanently even before the protection circuit starts to operate.
- Overheating Protection  
The thermal shutdown circuits in the Product are designed to temporarily protect Product from minor overheating of brief duration. When the overheating protective function in the Product activates, immediately correct the overheating situation. Improper usage of Product, such as the application of heat to Product exceeding the absolute maximum ratings, could cause the overheating protection circuit not to operate properly and/or damage Product permanently even before the protection circuit starts to operate.
- Overvoltage Protection  
The overvoltage protection circuits in the Product are designed to temporarily protect Product from minor overvoltage of brief duration. When the overvoltage protective function in the Product activates, immediately cease application of overvoltage to Product. Improper usage of Product, such as application of voltage to Product exceeding the absolute maximum ratings, could cause the overvoltage protection circuit not to operate properly and/or damage Product permanently even before the protection circuit starts to operate.










## Package Dimensions

HSIP5-P-1.27B

Unit: mm



Weight: 0.36 g (Typ.)

## RESTRICTIONS ON PRODUCT USE

- Toshiba Corporation, and its subsidiaries and affiliates (collectively "TOSHIBA"), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively "Product") without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Toshiba:

[TA58LT00F\(T6L1,Q\)](#)