

N-250MG

Electrical Specifications (@25°C)

1. Maximum Power: 250 VA
2. Input Voltage: 115 V, 50 / 60 Hz
3. Output Voltage: 230V \pm 5%
4. Full Secondary Load: 1.10 Amps RMS

Description:

The N-250MG is part of the line of Auto-Transformers that are single winding transformers in which the primary coil is a fraction of the entire winding for voltage step-up. This causes part of the power to be transferred conductively through the windings, rather than all of the power being transferred by induction.

Safety:

These units are designed with 1500V isolation between the winding and the core. Materials and construction are rated for Class B insulation system.

Dimensions:

Unit: In inches




A	B	C	D	E
3.875	3.250	3.687	2.50	2.437

Weight: 6.60 lbs

Mounting Holes: .203 x .375

Connection: 6 ft. long cord with NEMA 5-15P Plug, 1 ft. long cord with NEMA 6-15P socket.

Schematic:



RoHS Compliance: As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetix's website for the most current version.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Triad Magnetics:](#)

[N-250MG](#)