

VPL28-2000

Electrical Specifications (@25C)

1. Maximum Power: 56.0VA
2. Input Voltage – Series: 230VAC @ 50/60Hz, Parallel: 115VAC @ 50/60Hz
3. Output Voltage – Series: 28.0V CT @ 2.00A, Parallel: 14.0V @ 4.00A
4. Voltage Regulation: 20% TYP @ full load to no load
5. Hipot: 3500VAC between primary to secondary and windings to core.

Construction:

Dual winding construction with an insulated shroud, both made of a high temperature material that exceeds UL flammability requirements. Shrouds are provided over the connections of the leads to the windings on both primary and secondary coils. Devices are designed with a minimum of 6mm creepage distance between the primary and secondary and are manufactured with a Class B (130°C) insulation system

Agency Files:

TUV: File R72182067, EN 61558-1:2005+A1, EN61558-2-6:2009. Double Insulated.
Non-inherently Short-Circuit-Proof.




Dimensions: Units: In inches

A	B	C	D	E
3.062	2.562	2.625	2.00	2.250

Weight: 2.7 lbs.
Lead Length: 7"

Connections¹:



Input: Series – BLK to BLU, Jumper WHT to BRN
Parallel – BLK to BLU, Jumper BLK to BRN and WHT to BLU
Output: Series – VIO to YEL, Jumper GRY to RED
Parallel – VIO to YEL, Jumper VIO to RED and GRY to YEL



RoHS Compliance: As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetix' website for the most current version.

¹ Primary and secondary windings are designed to be connected in series or parallel. Windings are not intended to be used independently.



Picture for illustration Purposes only



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Triad Magnetics:](#)

[VPL28-2000](#)