

### WDU24-300

#### Electrical Specifications (@25C)

1. Primary Rating: 120V 60Hz (11.8W @ Full Load)
2. Primary Excitation Current: 85mA Max
3. Secondary Rating: 24VDC  $\pm$  5%, 300mADC
4. Secondary No-Load Rating: 31.45VDC Ref.
5. Output Ripple Voltage: 1150mV Max
6. Operating Temperature Range: -10 Deg C to +40 Deg C
7. Temperature Rise: 75 Deg C Max at rated load  
50 Deg C Max on enclosure surface

#### Mechanical Parameters:

Case Type: Thermoplastic molded enclosure.  
Output Cord: 24 AWG, 6 Ft. Long Min.

Agency File:


UL/CUL: File E245587, UL 1310

#### A. Dimensions:

| H  | W  | D  |
|----|----|----|
| 70 | 50 | 41 |

\*Units: In Millimeter

#### B. Schematic:






Technical Note: 1. Inside (tip)-positive (+), outside-negative (-)

**DOE Compliance:** Effective December 30, 2017, the DOE will now not consider an external power supply with specific characteristics to meet the definition of a device that is subject to EPCA regulation, as long as the power supply is not distributed for use with consumer products.

**RoHS Compliance:** As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

\* Upon printing, this document is considered “uncontrolled”. Please contact Triad Magnetix’ website for the most current version.



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Triad Magnetics:](#)

[WDU24-300](#)