

Waber-by-Tripp Lite 6-Outlet Industrial Surge Protector, 6-ft. Cord, 1050 Joules

MODEL NUMBER: DG206







Highlights

- 6 outlets/6 ft. cord
- 1050 joule rating

Package Includes

- DG206 Power Strip
- Warranty information
- Instruction manual

Description

The Waber-by-Tripp Lite DG206 Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 1050 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme.PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15RELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)FORMAT - Corded metal power distribution strip with lighted power switchSUPPRESSION - 1050 joules AC suppression

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- · Keyhole mounting tabs for installation in a wide variety of applications
- UL1449 (USA/400V rating), UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

Specifications



OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(6) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15	
Right-Angle Outlets	0	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P input plug	
Input Cord Length (ft.)	6	
Input Cord Length (m)	1.83	
Input Cord Gauge Type	14 gauge, SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	19500	
Right-Angle Plug	0	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Lighted two position power switch controls power to all outlets	
Diagnostic LED Details	Protection present (green)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1050	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
UL1449 Let Through Rating	400V - UL Verified	
Immunity	Conforms to IEE 587 / ANSI C62.41	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	0	
Cable (Coax) Protection	0	
Network (Ethernet) Protection	0	
PHYSICAL		



[
Shipping Dimensions (hwd / in.)	2.25 x 15 x 6
Shipping Dimensions (hwd / cm)	5.7 x 38.1 x 15.24
Shipping Weight (lbs.)	10
Shipping Weight (kg)	4.5
Unit Dimensions (hwd / in.)	1.25 x 2.5 x 12.25
Unit Dimensions (hwd / cm)	3.175 x 6.35 x 31.12
Unit Weight (lbs.)	2.4
Unit Weight (kg)	1.09
Material of Construction	Metal
Integrated Keyhole Mounting Tabs	Keyhole mounting tabs enable wall mounting
Receptacle Color	Gray
Color (AC Line Cord)	Gray
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: DG206