

Serial ATA (SATA) Latching Signal Cable (7Pin/7Pin), 39-in. (99.06 cm)

MODEL NUMBER: P940-39I



Features

- Connect your high-speed Serial ATA device to a Serial ATA controller/motherboard with SATA connections
- Metal latches ensure secure connections
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design: 1) simplifies cable routing and installation 2) improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- · Cable is shielded to protect against EMI/RFI
- Low profile mold on connector allows for side by side connection with SATA power adapter cable

Specifications

OVERVIEW	
UPC Code	037332118141
Technology	SATA/eSATA
PHYSICAL	
Color	Red
Cable Length (ft.)	3.3
Cable Length (m)	1
Cable Length (in.)	39

Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Cable is shielded to protect against EMI/RFI

System Requirements

- Serial ATA device
- Serial ATA controller

Package Includes

39-in. Serial ATA (SATA)
Latching Signal Cable
7Pin/7Pin, Straight/Straight



99.06	
22.86 x 17.78 x 1.27	
9.00 x 7.00 x 0.50	
0.03	
0.07	
CONNECTIONS	
7 PIN SATA (MALE)	
7 PIN SATA (MALE)	
STANDARDS & COMPLIANCE	
RoHS-Compliant	
WARRANTY	
Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: <u>P940-391</u>