

# Serial ATA (SATA) Power Cable (4Pin Molex to 15pin), 6-in.

MODEL NUMBER: P944-061



## **Highlights**

- Connects SATA drive to internal power source
- Supports most current version of Serial ATA
- Meets the newly released updates and listed in Errata 029

## **System Requirements**

- Serial ATA device
- Serial ATA controller

## **Package Includes**

 6-in. Serial ATA (SATA) Power Adapter Cable 15Pin/4Pin

# Description

Tripp Lite expands its line of hard drive cables with the introduction of our new line of Serial ATA cables. The Serial ATA power cable connects any Serial ATA drive to any standard internal power connector. These new hard drives are perfect for the desktop or server that has multiple drives. This cable offers easy installation and comes with 15 pin/4 pin male connectors.

#### **Features**

- Connects any Serial ATA drive 15pin Power port to a standard internal 4-pin Molex power connector
- Meets serial ATA 1.0 standards

# **Specifications**

INPUT		
Cable Length (ft.)	0.5	
Cable Length (m)	0.2	
Cable Length (in.)	6	
Cable Length (cm)	15.24	
PHYSICAL		
Color	Black; Red; Yellow	
CONNECTIONS		
Side A - Connector 1	15 PIN SATA POWER	
Side B - Connector 1	LP4 (MALE)	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: P944-06I