

3.8kW Single-Phase Monitored Automatic Transfer Switch PDU, 2 200-240V 16A L6-20P Inputs, 1 L6-20R Outlet, 1U

MODEL NUMBER: PDUMNH20HVAT



High-capacity 3.3/3.8kW PDU with ATS provides remote power monitoring and enables redundant power for non-redundant hardware. Digital display and Ethernet interface monitor load levels to prevent overloads that cause downtime.

Description

The PDUMNH20HVAT 3.3/3.8kW Single-Phase 200-240V Monitored Automatic Transfer Switch / ATS PDU provides remote power monitoring and enables redundant power for network devices with non-redundant power supply configurations. Ideal for data centers and server rooms, it mounts in 1U of space in EIA-standard 19-inch racks and features one L6-20R outlet—perfect for connecting a single device or a 0U 208/240V PDU with an L6-20P plug.

Dual 10-ft. (3.05 m) input cords with L6-20P plugs connect to separate primary and secondary single-phase power sources. The PDU constantly evaluates the power quality of both input sources. Dynamic solid-state (TRIAC) automatic transfer switching allows the PDU to switch to the secondary source within 1–5 milliseconds should the primary source fail or become unstable to ensure your connected equipment operates without interruption.

The built-in Java-free HTML5-based LX Platform network interface enables full remote access for PDU status monitoring and email notifications via secure web browser, SNMP, telnet or SSH. It supports 10/100 Mbps auto-sensing for optimum communication with an Ethernet network. Optional EnviroSense2 modules (sold separate) provide a variety of environmental monitoring capabilities, including temperature and humidity conditions. Protocols supported include IPv4, IPv6, HTTP, HTTPS, SMTP, SNMPv1, SNMPv2, SNMPv3, telnet, SSH, FTP, DHCP and NTP. DHCP/Manual configuration lets you assign network settings to the card automatically, reducing the need for manual configuration. Automated alerts help prevent accidental overloads, power loss and downtime.

Features

Primary and Secondary Inputs for Power Redundancy Provides remote power monitoring and enables redundant power for network devices with non-redundant power supply configurations
 Dual 10-ft. (3.05 m) input cords with L6-20P plugs connect to separate primary and secondary single-phase power sources
 Fault-tolerant, hot-swappable UPS protection when used with single UPS; fully redundant UPS protection when each cord is connected to separate UPS systems

Built-In L6-20R Outlet Connects a single device or indirectly powers equipment through a 0U 200-240V PDU with L6-20P input (sold separately)

Automatic Transfer Switching (ATS) Dynamic solid-state (TRIAC) automatic transfer switching
 Switches to secondary power source if primary source fails or becomes unstable
 1-5 ms transfer time ensures uninterrupted operation of connected equipment
 Built-in processor prevents switching if secondary source

Highlights

- Two single-phase L6-20P inputs with 10-ft. (3.05 m) cords
- L6-20R outlet for connecting single device or 0U vertical PDU
- Automatic transfer switching within 1-5 ms
- Built-in LX Platform Interface for remote access
- Digital display for real-time status monitoring

Package Includes

- PDUMNH20HVAT 3.3/3.8kW Single-Phase 200-240V ATS/Monitored PDU
- Mounting brackets
- Owner's manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

is unavailable or of lower quality than primary source

Multifunction Digital Display Reports source A and source B input power status and other information, including power availability, line voltage, frequency, amps, kilowatts and power factor

Advanced Network Monitoring LX Platform interface allows full remote access for power monitoring with email notifications via secure web browser, SNMP, telnet or SSH Real-time load/current data with billing-grade accuracy (+/- 1 percent) Automated alerts help prevent overloads, power loss and downtime Optional EnviroSense2 modules (sold separately) provide a variety of environmental monitoring capabilities

Broad Communications Compatibility 10/100 Mbps auto-sensing allows optimal communication with 10/100 Base-T networks

Mounts Horizontally in 1U of Rack Space Compatible with EIA-standard 19 in. 4-post racks and rack enclosures Optional PDU4PKIT rail kit (sold separately) adds rear mounting support

Specifications

OVERVIEW	
UPC Code	037332187932
PDU Type	Monitored; Auto-Transfer Switch
INPUT	
PDU Input Voltage	200-240V
Recommended Electrical Service	Two single-phase 16/20A 200-240V circuits
Maximum Input Amps	16
Maximum Input Amps Details	Agency de-rated to 16A continuous
PDU Plug Type	(2) NEMA L6-20P
Input Phase	Single-Phase
Input Cord Details	Set of two inputs connect to separate PRIMARY and SECONDARY power sources
Input Cord Length (ft.)	10
Input Cord Length (m)	3.05
OUTPUT	
Output Capacity Details	3.8kW (240V), 3.7kW (230V), 3.5kW (220V), 3.3kW (208V), 3.2kW (200V); 16A total capacity
Frequency Compatibility	50 / 60 Hz
Output Receptacle Details	Output receptacle is on a 61cm / 24 inch cordset
Output Receptacles	(1) L6-20R
Output Nominal Voltage	200-240V
USER INTERFACE, ALERTS & CONTROLS	
Front Panel LCD Display	Digital display reports input current in amps (Source A, Source B), output kilowatts (total), input voltage (Source A, Source B), input frequency (Source A, Source B) and output power factor
Front Panel LEDs	Front panel LEDs confirm amp (A) / kilowatt (kW) / voltage (V) / frequency (Hz) and power factor (PF) reporting information; Additional set of LEDs indicate Source A and Source B inputs for preferred, available and in-use status
Switches	ENTER and MODE switches toggle the digital display to display all reported information



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Current Measurement Accuracy (Amps)	+/-1%
Voltage Measurement Accuracy (Volts)	+/-1%
Power Measurement Accuracy (Watts)	+/-1%
PHYSICAL	
Form Factors Supported	1U rackmount
Material of Construction	Metal
Minimum Required Rack Depth (cm)	44.45
Minimum Required Rack Depth (inches)	17.5
PDU Form Factor	Horizontal (1U)
Shipping Dimensions (hwd / cm)	18.29 x 52.07 x 52.07
Shipping Dimensions (hwd / in.)	7.20 x 20.50 x 20.50
Shipping Weight (kg)	7.21
Shipping Weight (lbs.)	15.90
Unit Dimensions (hwd / cm)	4.4 x 43 x 35.6
Unit Dimensions (hwd / in.)	1.72 x 16.93 x 14
Unit Weight (kg)	6.97
Unit Weight (lbs.)	15.37
ENVIRONMENTAL	
Operating Temperature Range	0C ~ 50C (32F ~ 122F)
Storage Temperature Range	-30°C to +60°C (-22°F to +140°F)
Relative Humidity	5 to 95% (non-condensing)
SPECIAL FEATURES	
High Availability PDU Features	Auto Probe Monitoring (included)
STANDARDS & COMPLIANCE	
Certifications	Tested to UL/CSA 60950-1 (USA, Canada), FCC Class A (Emissions), NOM (Mexico), RoHS Compliant
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

<https://www.tripplite.com/products/product-certification-agencies>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[PDUMNH20HVAT](#)