

Internal SAS Cable, 4-Lane mini-SAS (SFF-8087) to 4xSatA 7pin, 3 ft. (0.91 m)

MODEL NUMBER: \$508-003



Highlights

- Positive and passive latching ensures that the plug remains mated to receptacle
- All internal Mini-SAS assemblies are capable of supporting SAS/SATA generation I, II, and III bandwidths (up to 6Gbps)
- Reduced mechanical size offers up to 4 times the port density of the current x4 solution

Package Includes

• 3 ft. Internal SAS Cable, SFF-8087 to 4 x 7pin SATA

Features

- Positive and passive latching ensures that the plug remains mated to receptacle
- All internal mini SAS assemblies are capable of supporting SAS/SATA generation I, II, and III bandwidths (up to 6Gbps)
- Reduced mechanical size offers up to 4 times the port density of the current x4 solution
- For Controller to hard drive applications

Specifications

OVERVIEW		
UPC Code	037332143341	
Technology	SAS; SATA/eSATA; Ribbon/Internal	
PHYSICAL		
Color	Red	
Cable Length (ft.)	3	
Cable Length (m)	0.9	
Shipping Dimensions (hwd / cm)	1.27 x 2.54 x 20.07	
Shipping Dimensions (hwd / in.)	0.50 x 1.00 x 7.90	
Shipping Weight (kg)	0.09	
Shipping Weight (lbs.)	0.20	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

CONNECTIONS		
Side A - Connector 1	SFF-8087	
Side B - Connector 1	7 PIN SATA (MALE)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: S508-003