



# 1200W 120V Power Conditioner with Automatic Voltage Regulation (AVR) and AC Surge Protection

MODEL NUMBER: LC1200





#### **Description**

Tripp Lite's LC1200 Line Conditioner keeps your equipment working through brownouts and prolonged overvoltage conditions without using emergency power from UPS systems or auxiliary generators. Rated at 1200 watts / 10A, it automatically adjusts for under- and over-voltages to provide safe, computer-grade AC power meeting ANSI C84.1 specifications. It has a 7-ft AC power cord and 4 NEMA 5-15R outlets to provide continuous AC power to your critical IT equipment. With built-in premium surge suppression that exceeds the IEEE-587 standard for surge suppression (both categories A and B), the LC1200 also protects your valuable equipment from surges, spikes and EMI/RFI line noise that can wear down sensitive circuitry and cause premature aging or total failure of your equipment.

#### **Highlights**

- 1200 watt / 10 amp capacity
- Brownout and overvoltage protection in a single, cost-effective unit
- Maintains a regulated 120V nominal output over an input range of 89 to 147V
- Powerful 1200-joule surge suppression rating
- Four NEMA 5-15R outlets; 7 ft.
   AC power cord

#### **Applications**

Maintains regulated output
 voltage during severe brownouts
 and overvoltages for computer
 accessories, printers, home
 theater equipment, a/v
 components, point-of-sale
 equipment, and other
 applications requiring clean,
 regulated AC power.

#### **Package Includes**

- LC1200 Line Conditioner
- Instruction manual

#### Features

- Comprehensive Power Protection: Provides comprehensive power protection for computers, A/V components and all electronics.
- Automatic Voltage Regulation: Built-in automatic voltage regulation (AVR) with three levels of voltage stabilization to provide a targeted response to
  overvoltages, undervoltages and severe brownouts. The LC1200 corrects brownouts as low as 89V and overvoltages up to 147V back to safe, nominal
  120V power.
- EMI/RFI Line Noise Filtering: Electromagnetic and radio sources can cause disruptive interference on the AC line. This EMI/RFI line noise is a common cause of incremental hardware damage, data corruption and audio/video performance problems. The LC1200 incorporates technology that filters out disruptive line noise, preventing it from affecting your equipment or corrupting data.
- Network Grade AC Line Surge Suppression: The LC1200 provides 1200 joules of surge suppression to prevent even the strongest surges from damaging your valuable electronics. Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression.
- Built-In Power Status Display: Seven diagnostic LEDs provide complete power status information: AC power (green = NORM), incoming voltage level (2 x yellow = HIGH/LOW, 2 x red = VERY HIGH/VERY LOW) and AC line status (green = LINE OK, red = LINE FAULT). An On/Off switch located on the rear of the unit provides one-touch power control over all components.
- Compact Design: The LC1200's compact cabinet (less than eight inches in height) and 7-ft. cord make it easy to integrate into a wide range of
  applications.
- Ultimate Peace of Mind: The LC1200 comes with \$25,000 Ultimate Lifetime Insurance—guaranteed lifetime protection for your equipment in case of



surge damage, including direct lightning strikes.

## **Specifications**

ОШТРИТ	
Nominal Output Voltage(s) Supported	120V
Output Receptacles	(4) 5-15R
Output (VA)	1200
Output (Watts)	1200
INPUT	
Plug Type	Right-angle NEMA 5-15P input plug
Input Cord Length (ft.)	7
Input Cord Length (m)	1.83
USER INTERFACE, ALERTS & CONTROLS	
Front Panel LEDs	7 LEDs show incoming voltage status, protection present and line fault conditions
SURGE / NOISE SUPPRESSION	
UPS AC Suppression Joule Rating	1200 joules, conforms to IEEE 587 / ANSI C62.41 specifications
EMI / RFI AC Noise Suppression	75 dB
PHYSICAL	
Shipping Weight (lbs.)	8.7
Shipping Weight (kg)	4
Unit Dimensions (hwd / in.)	7.25 x 6 x 7
Unit Dimensions (hwd / cm)	18.4 x 15.2 x 17.8
Material of Construction	Plastic
Form Factors Supported	Small Tower
CERTIFICATIONS	
Certifications	Tested to UL1012 (USA), cUL1012 (Canada), NOM (Mexico)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Connected Equipment Insurance (U.S., Canada & Puerto Rico)

\$25,000 Ultimate Lifetime Insurance

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

### **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: