


Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

100G Duplex Multimode 50/125 OM5 LSZH Fiber Optic Cable (LC/LC), Lime Green, 7 m

MODEL NUMBER: N820-07M-OM5





Rated OM5, this 50/125 multimode fiber cable with duplex LC connectors carries signals in 40/100 Gb Ethernet networks.

Features

Support Higher Bandwidths in Data Networks with OM5 Multimode 50/125 Fiber Patch CableAs the amount of traffic in data networks grows, so does the need for next generation devices and fiber cables to support higher bandwidths. Tripp Lite's OM5 Duplex Multimode 50/125 Fiber Patch Cable is a wideband multimode fiber (WBMMF) solution that supports at least four wavelengths in the 850-950 nm range. This LC to LC multimode fiber optic patch cable is well-suited for 40/100 Gb Ethernet applications up to 300 meters (at 850 nm).

Use with VCSEL Light Sources for a Cost-Effective, High-Bandwidth SolutionThe N820-07M-OM5 is a laser-optimized multimode fiber (LOMMF) cable designed for use with vertical-cavity surface-emitting lasers (VCSELs) to offer a cost-effective, high-bandwidth solution over extended distances in the 850-950 nm wavelength range. It is commonly used in LANs, SANs and high-speed parallel interconnects for head-ends, central offices and data centers.

Experience Reliable Performance with Premium ConstructionPremium materials ensure this multimode fiber cable reliably carries data and voice signals. The cable has duplex male LC connectors on each end and features a low-smoke zero-halogen (LSZH) jacket that limits the amount of toxic smoke emitted in case of combustion, making it suitable for poorly ventilated areas. The lime green color of the jacket identifies the cable as OM5 rated. It meets current IEEE 802.3ae and TIA LOMMF standards. **Employ OM5 Cable for Backward Compatibility and Future Proofing**Rated OM5, the N820-07M-OM5 cable is backward compatible with existing OM3- and OM4-rated 50/125 fiber solutions. This LC to LC multimode fiber optic cable can also be used with shortwave wavelength division multiplexing (SWDM) technology to provide transmission over longer distances in the 850-950 nm wavelength range than OM3- and OM4-rated cables. Plus, the OM5 cables will be compatible with SWDM solutions in future networks with even higher bandwidths.

Lifetime WarrantyThe N820-07M-OM5 is backed by a lifetime limited warranty, ensuring reliability and performance.

Specifications

OVERVIEW UPC Code 037332224248

Highlights

- Rated OM5 to offer a wideband 50/125 multimode fiber solution
- For 40/100 Gb speeds up to 300 meters (at 850 nm)
- Laser-optimized for use with cost-effective VCSEL light sources
- Lime green jacket for easy OM5 identification; 7 m (23 ft.) cable
- Backward compatible with OM3 and OM4 applications

Applications

- Use to carry signals in LANs, SANs and high-speed parallel interconnects for head-ends, central offices and data centers
- Use with vertical-cavity surfaceemitting laser (VCSEL) or LED laser light sources in a LAN network
- Add backward and forward compatibility to a high-speed data network

Package Includes

N820-07M-OM5 Duplex
 Multimode 50/125 Fiber Patch
 Cable, OM5 Rated, 7 m (23 ft.)



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

[
Technology	Multimode
Optical Mode	OM5
PHYSICAL	
Cable Jacket Color	Lime
Cable Outer Diameter (OD)	1.9 +/- 0.1mm x 3.8 +/- 0.2mm
Clad Diameter	125 micron
Core Diameter	50 micron
Number of Fibers	2
Cable Length (ft.)	23
Cable Length (m)	7
Cable Length (in.)	275.6
ENVIRONMENTAL	
Operating Temperature Range	-20 ~ 60C (-4 ~ 140F)
Storage Temperature Range	-20 ~ 60C (-4 ~ 140F)
Relative Humidity	4% TO 98% RH
COMMUNICATIONS	
Network Speed	10Gbps / 40Gbps / 100Gbps
CONNECTIONS	
Side A - Connector 1	LC DUPLEX (MALE)
Side B - Connector 1	LC DUPLEX (MALE)
SPECIAL FEATURES	
Push/Pull Tabs	No
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: N820-07M-OM5