

1U Logic Control Unit for Robotic Fiber Panel System

MODEL NUMBER: NRFP-LCU-1







Controls the connected Tripp Lite NRFP Robotic Fiber Panel System via the included signaling Y cable.

Features

For Powering and Controlling Your Tripp Lite NRFP Robotic Fiber Panel SystemThe NRFP-LCU-1 comes with a logic control unit, a signaling cable that attaches to your Tripp Lite NRFP-500MM-CP or NRFP-500SM-CP Robotic Fiber Panel System, and a ground cable that connects to the facility ground. It mounts into 1U of space anywhere in your 4-post rack enclosure, including directly above the Robotic Fiber Panel System, which allows adequate space for connecting the LCU control and ground cable. The power cable connections are located on the front panel, as are three LEDs that indicate the system's functional status at a glance.

Highlights

- Required accessory for NRFP Robotic Fiber Panel Systems
- Includes logic control unit, signaling cable and ground cable
- Mounts into 1U of rack space directly above Robotic Fiber Panel System
- Front-panel LEDs provide at-aglance functional status updates

Applications

 Power and control a Tripp Lite NRFP Robotic Fiber Panel
 System in a 4-post rack enclosure

System Requirements

 Required for Tripp Lite NRFP-500MM-CP and NRFP-500SM-CP

Package Includes

- NRFP-LCU-1 Logic Control Unit
- · Signaling cable
- · Grounding cable

Specifications

OVERVIEW	
UPC Code	037332236982
PHYSICAL	
Color	Black
Rack Height	1U
Unit Dimensions (hwd / in.)	1.7 x 17.5 x 27.5
Unit Weight (kg)	10.89



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Unit Weight (lbs.)	24	
FAIVIDONIMENTAL		
ENVIRONMENTAL		
Operating Temperature Range	0 degrees C to 40 degrees C (32 degrees F to 104 degrees F)	
Storage Temperature Range	-40 degrees C to 70 degrees C (-40 degrees F to 158 degrees F)	
Relative Humidity	5% to 95%	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:

NRFP-LCU-1