



# 6-Outlet Surge Protector with 2 USB Ports (3.4A Shared) - Side Load, Direct Plug-In, 1050 Joules

#### MODEL NUMBER: TLP6SLUSBB











6-outlet surge protector with USB charging safeguards your home/office electronics against dangerous surges, spikes and line noise.

#### **Features**

**6-Outlet Surge Protector with USB Charging Safeguards Your Sensitive Electronics**Ideal for your home or office workstation, this Protect It!® 6-outlet side-load surge protector features a surge protection rating of 1050 joules to defend your sensitive electronic components against strong power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP664USBB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

Side-Facing NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices Plug your PC, printer, scanner, router, modem, television, stereo receiver and other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. The TLP6SLUSBB plugs directly into a wall outlet (no cord required), and three outlets are included on either side. This allows you to install the surge protector behind furniture and other tight spaces without equipment power cords getting it the way. It's small enough to take with you for plugging in devices at the office or on the road. 2 USB Ports Share 3.4 Amps of Charging PowerTwo front USB-A ports are available for charging your smartphone, tablet and other USB mobile devices. They share 3.4A for charging two devices at the same time.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety Features An integrated 15A circuit breaker protects all outlets and automatically cuts power if the protection circuit is incapacitated, preventing equipment damage and indicating replacement is required. Diagnostic LEDs confirm your wall outlet is properly grounded and your connected equipment is protected. The TLP664USBB, with a high-impact black plastic housing, conforms to current UL 1449 4th Edition and cUL (Canada) safety standards.

#### **Highlights**

- 6 side-facing NEMA 5-15R outlets allow convenient connection behind furniture
- 1050 joules protect your valuable electronics against dangerous surges and spikes
- 2 USB ports share 3.4A for fast charging of phones, tablets and other mobile devices
- Plugs directly into the wall (no cord required) for easy installation in tight spaces
- LEDs reassure you at a glance that your outlet is grounded and electronics are protected

#### **Applications**

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

#### Package Includes

 TLP6SLUSBB Protect It! 6-Outlet Surge Protector, Side Load, Direct Plug-In, Black



## **Specifications**

OVERVIEW		
UPC Code	037332239549	
Product Type	Surge Protector	
Charging Form Factor	Strip	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Length Details	Direct plug-in	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	60000	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(2) Yes	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Diagnostic LED Details	Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1050	
AC Suppression Response Time	< 1 ns	





UL1449 Let Through Rating  EMI / RFI Filtering  Automatic Shut-Off  CHARGING  Number of Charging Ports  Charging Amps  Charging Method  Charging Port Type  US  Charging Ports / Amps  3.4  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection  No  Network (Ethernet) Protection  No	JSB A (FEMALE)  .4A  JSB A (FEMALE)  .4A
EMI / RFI Filtering 150 Automatic Shut-Off Yes  CHARGING  Number of Charging Ports 2 Total Charging Amps 3.4 Charging Method US Charging Port Type US Charging Ports / Amps 3.4  DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No	50 kHz to 100 mHz  Tes  .4A  JSB JSB A (FEMALE) .4A
Automatic Shut-Off  CHARGING  Number of Charging Ports  Total Charging Amps  Charging Method  Charging Port Type  Charging Ports / Amps  3.4  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection  No  Cable (Coax) Protection  No  Network (Ethernet) Protection	res  .4A  JSB JSB A (FEMALE)  .4A
CHARGING  Number of Charging Ports 2  Total Charging Amps 3.4  Charging Method US  Charging Port Type US  Charging Ports / Amps 3.4  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No	JSB A (FEMALE)  .4A  JSB A (FEMALE)  .4A
Number of Charging Ports 2  Total Charging Amps 3.4  Charging Method US  Charging Port Type US  Charging Ports / Amps 3.4  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No	JSB JSB A (FEMALE)  .4A  lo lo
Total Charging Amps 3.4 Charging Method US Charging Port Type US Charging Ports / Amps 3.4  DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No	JSB JSB A (FEMALE)  .4A  lo lo
Charging Method US Charging Port Type US Charging Ports / Amps 3.4  DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection	JSB A (FEMALE)  .4A  lo
Charging Port Type US Charging Ports / Amps 3.4  DATALINE SURGE SUPPRESSION Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection	JSB A (FEMALE)  .4A  Jo
Charging Ports / Amps 3.4  DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No  Cable (Coax) Protection No  Network (Ethernet) Protection No	.4A lo
DATALINE SURGE SUPPRESSION  Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No	lo
Telephone/DSL Protection No Cable (Coax) Protection No Network (Ethernet) Protection No	lo
Cable (Coax) Protection No Network (Ethernet) Protection No	lo
Network (Ethernet) Protection No	
	10
PHYSICAL	
Antimicrobial Coating No	lo
Housing Color Bla	Black
Integrated Keyhole Mounting Slots No	lo
Material of Construction Pla	Plastic
Receptacle Color Bla	Black
Shipping Dimensions (hwd / cm) 13.	3.46 x 8.64 x 7.11
Shipping Dimensions (hwd / in.) 5.3	.30 x 3.40 x 2.80
Shipping Weight (kg) 0.3	.34
Shipping Weight (lbs.) 0.7	.75
Unit Dimensions (hwd / in.) 5.4	.47 x 3.94 x 2.28
Unit Weight (kg) 0.2	.23
Unit Weight (lbs.) 0.5	.5
SPECIAL FEATURES	
Rotatable Outlets No	lo
STANDARDS & COMPLIANCE	
Canada cU	UL
Approvals Ro	O.LIC



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

UL1449 3rd Edition (AC Suppression)	UL1449 3RD EDITION	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>

### **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite:
TLP6SLUSBB