Magnetics

Power Inductor

Model HA55

- Operating Temperature Range -40°C to +155°C •
- High inductance, high efficieny and excellent • current handling
- Use as DC-DC converter and in high current • applications, suitable for industrial as well as automotive applications
- **RoHS** Compliant •
- AEC-Q200 Certified





All parts are Pb-free and comply with EU Direcv e 2011/65/EU (RoHS2)

Electrical Schematic



Specifications @ 25°C

Part Number	Inductance 100kHz, 100mV (μΗ) TYP	@Rated Current Inductance 100kHz, 100mV (μΗ) TYP	I _{rated} Rated Current (A)	I _{sat} Satura Current (A)	DC Resistance		SPE	
					тΩ Тур	mΩ Max	MHz Type	Figure
HA55-3623200LF	20.00	14.50	33.00	35.0	3.35	3.85	14.0	1
HA55-3023115LF	11.50	8.24	39.00	43.0	2.30	2.76	33.0	2
HA55-2223070LF	7.00	5.33	40.00	48.0	1.70	2.00	33.0	3
HA55-3023130LF	13.00	9.33	37.00	40.0	2.50	3.25	19.0	4
HA55L-3623220LF*	22.00	13.00	34.00	26.0	3.35	3.85	12.0	1
HA55L-3023135LF*	13.50	8.42	39.00	30.0	2.30	2.76	33.0	2
HA55L-2223088LF*	8.83	5.52	41.00	33.0	1.70	2.00	36.0	3
HA55L-3023163LF*	16.30	9.38	37.00	27.0	2.50	3.25	25.0	4
HA55L-3623400LF*	40.00	24.00	26.00	20.0	5.70	6.20	8.25	1
HA55L-4523500LF*	50.00	26.00	32.00	20.0	7.25	8.35	6.85	5

Notes : (1) Inductance is measured at 100kHz, 0.1Vrms, 0Adc. (2) The rated current is the approximate DC current at which ∆T is approximately 60°C. This current is determined by soldering

the unit on a typical application PCB, and then applying the current to the unit for 30 minutes. (3) Isat is the saturation current at which inductance rolls off approximately 30% from its initial unbias inductance value.

* Low cost version

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT Electronics plc

BI Technologies A-1445, Jalan Tanjung Api 25050 Kuantan Pahang Darul Makmur Malaysia Ph: +60 9 565 8888 Fax: +60 9 514 3555 http://www.ttelectronics.com/magnetics/customer-service-enquiry



Electrical Characteristics



We reserve the right to change specifications without prior notice

General Note



Electrical Characteristics



General Note



Electrical Characteristics



General Note



Electrical Characteristics



We reserve the right to change specifications without prior notice.

General Note



Electrical Characteristics



We reserve the right to change specifications without prior notice.

General Note



Electrical Characteristics



We reserve the right to change specifications without prior notice.

General Note



Mechanical Outline (mm)



Packaging

- (Packed in compact PE foam)
- 1) 1 shipping carton 72pcs (FOR CASE 3623 & 4523)
- 2) 1 shipping carton 108pcs (FOR CASE 3023)
- 3) 1 shipping carton 144pcs (FOR CASE 2223)

Ordering Information



General Note

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TT Electronics:

<u>HA55-2223070LF</u> <u>HA55-3023115LF</u> <u>HA55-3023130LF</u> <u>HA55-3623200LF</u> <u>HA55L-3023135LF</u> <u>HA55L-3023163LF</u> HA55L-3623220LF HA55L-3623400LF HA55L-2223088LF HA55L-4523500LF