

ULR Series

Features

- Robust metal strip able to withstand high temperature and high current.
- Power ratings up to 5W
- Low TCR and Inductance
- Resistance Range from 0.15mΩ to 10mΩ
- RoHS compliant
- AEC-Q200
- Higher wattage devices feature PCB clearance gap to maximize thermal performance



 All parts are Pb-free and comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)

Electrical Data

Type	Size	Coating	Power Rating @70°C (W)	Standard Resistance Value mΩ ¹	TCR (ppm/°C)	Tolerance (%)	Dielectric Withstanding Voltage (V)	Ambient Temperature (°C)
ULRG1 / ULR1S	1206	Green Underside	1	0.2, 0.25, 0.3, 0.4, 0.5, 0.6	200	1, 5	N/A	-55 to +170
ULRG15 / ULR15S	2010		1.5	0.75, 1, 1.2, 2, 2.5, 3, 3.5, 4, 5, 5.5, 6, 7, 8, 9, 10	50			
ULRG25 / ULR25S	2512		2.5	0.2, 0.25, 0.3, 0.4, 0.5	150			
ULRG2 / ULR2	2512		2	0.75, 1, 1.5, 2, 2.5, 3, 4, 5, 5.5, 6, 7, 8, 9, 10	50			
ULRG25 / ULR25	2512		2	1	300			
ULRG3 / ULR3	2512		3	1.5, 2, 2.5, 3	170			
ULRG5 / ULR5	2512		5 ²	6.5, 7, 7.5, 8, 9, 10	50			
ULRG3N / ULR3N	1225		3	3.5, 4, 4.5, 5, 5.5, 6	150			
ULRB1 / ULR1	2512	Black	1	0.15, 0.25, 0.3, 0.4, 0.5, 0.75	150	1, 5	200	-55 to +170
ULRB2 / ULR2	2512		2	1, 1.5, 2, 2.5, 3	50			
ULRB3 / ULR3	2512		3	0.5, 0.75	150			
ULRB5 / ULR5	2512		5 ²	1, 1.5, 2, 2.5, 3	50			
ULRB10 / ULR10	2512		10	0.1	500			
ULRB15 / ULR15	2512		15	0.2, 0.25, 0.3, 0.4	350			
ULRB20 / ULR20	2512		20	0.5	300			
ULRB25 / ULR25	2512		25	0.7, 0.75, 0.8, 0.9, 1.0	250			
ULRB30 / ULR30	2512		30	1.5, 2.0, 2.5, 3.0	100			
ULRB40 / ULR40	2512		40	0.5, 0.75, 1, 1.5, 2	50			

Notes: 1. For higher resistance values please refer to LRMA series.

Notes: 2. Terminal temp must not exceed 110°C

Performance Data

AEC-Q200 Table 7		Method		Max. (add R0005)		
ref.	Test ¹			Black	Green Underside	
					1206 & 2010	1020, 2512 & 1225
3	High Temp. Exposure *	MIL-STD-202 Method 108	ΔR%	1		
4	Temperature Cycling	JESD22 Method JA-104	ΔR%	0.5		
6	Moisture Resistance	MIL-STD-202 Method 106	ΔR%	1		
7	Biased Humidity	MIL-STD-202 Method 103	ΔR%	1		
8	Operational Life (Cyclic Load) *	MIL-STD-202 Method 108	ΔR%	1		
14	Vibration	MIL-STD-202 Method 204	ΔR%	0.5		
15	Resistance to Soldering Heat *	MIL-STD-202 Method 210	ΔR%	0.5		
16	Thermal Shock *	MIL-STD-202 Method 107	ΔR%	0.5		
18	Solderability	J-STD-002		>95% coverage		
21	Board Flex	AEC-Q200-005	ΔR%	0.5		
22	Terminal Strength	AEC-Q200-006	ΔR%	0.25		
Short Term Overload *		5 x Pr for 5s	ΔR%	0.5		
Resistance to Sulphur-Bearing Gas ²		EIA-977	ΔR%	N/A	1	

Notes: 1. Full AEC-Q200 qualification applies to 2512 size. The 1206 and 2010 sizes have received the tests marked *.

2. Resistance to sulphur bearing gas has been tested for green underside construction only.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.

All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


BI Technologies IRC Welwyn

www.ttelectronics.com/resistors

ULR Series

Physical Data

Dimensions(mm) and weight (mg)							
Size	Coating	Values	L (±0.25)	W	T (±0.2)	D	Wt (nom)
1206	Green Underside	0.2, 0.25	3.2	1.6 ±0.3	1.0	1.5 ±0.25	25
		0.3, 0.4				1.4 ±0.25	
		0.5, 0.6		1.6 ±0.1	0.6	1.35 ±0.25	20
		0.75				1.23 ±0.25	
		1, 1.2, 3.5, 4, 5, 5.5, 6				1.1 ±0.25	
		2, 2.5, 3, 10				0.6 ±0.25	
		7, 8, 9				0.9 ±0.25	
2010		0.2	5.08	2.54 ±0.3	1.0	2.34 ±0.25	50
		0.25				2.24 ±0.25	
		0.3				2.04 ±0.25	
		0.4				1.84 ±0.25	
		0.5		2.54 ±0.15	0.6	2.17 ±0.25	40
		0.75				2.04 ±0.25	
		1, 1.5, 4, 5, 5.5				1.84 ±0.25	
		2, 2.5, 6, 7, 8				1.54 ±0.25	
		3				1.04 ±0.25	
		9, 10				1.29 ±0.25	
1020		1, 1.5, 2, 2.5, 3	2.54	5.08±0.25	0.6	0.57 ±0.25	45
2512		0.15	6.35	3.0 ±0.3	1.0	2.98 ±0.25	59
		0.2				2.88 ±0.25	
		0.25, 0.3				2.68 ±0.25	
		0.4				2.18 ±0.25	
		0.5		3.0 ±0.2	0.6	2.68 ±0.25	
		0.75				2.48 ±0.25	
		1, 5, 5.5, 6				1.93 ±0.25	
		2, 2.5, 3, 3.5, 8, 9, 10				1.18 ±0.25	
		4, 4.5				2.18 ±0.25	
		1.5, 6.5, 7, 7.5				1.43 ±0.25	
1225		0.1, 0.2,	3.0	6.35±0.25	1	1.0±0.25	65
		0.25, 0.3, 0.4			1	0.5±0.25	
		0.5, 0.7, 0.75, 0.8, 0.9, 1.0			0.6	0.5±0.25	
		1.5			0.6	1.0±0.25	
		2			0.6	0.8±0.25	
		2.5, 3			0.6	0.5±0.25	
2512	Black	0.5	6.35	3.18 ±0.25	1.25	1.85 ±0.38	184
		0.75			0.75	1.55 ±0.38	131
		1			0.65		111
		1.5			0.45		69
		2			0.35		49
		2.5			0.65	1.4 ±0.38	98
		3			0.55		83
		4			0.45		63
		5			0.35		50
		6			0.32		42
		6.5			0.3		36
		7			0.27		34
		10			0.25		26



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

BI Technologies IRC Welwyn

www.ttelectronics.com/resistors

ULR Series

Construction

Black Coat


A low TCR resistance alloy plate, with tin plated connection bands is protectively coated on the upper and lower faces and numerically marked with the resistance value. This part is suitable for wave or reflow soldering.

Green Underside Coat

A low TCR resistance alloy plate is grooved to set the final resistance and the lower face only is protected with an epoxy coating. The lower faces are tin plated for connections. This part is ONLY suitable for reflow soldering.

Marking

Only black coated parts are marked. For values which are integer numbers of milliohms, the marking is 4-character IEC62 code; e.g. "R002" for 2mΩ, "R010" for 10mΩ. For values including fractions of a milliohm the marking is 3 or 4-character code using "M" to indicate the decimal point, e.g. "M75" for 0.75mΩ, "1M50" for 1.5mΩ.



Termination Details:


Material

Matt tin plated finish over copper.

Solderability

95% min coverage (MIL-STD 202F / 208H, 245°C for 3 secs)

Power Derating Curves



Notes


The power derating curve is a guidance based on a conservative design model. The ULR is a solid metal alloy construction that can withstand significantly greater operating temperatures than the conservative model permits. The protective coating will operate up to 260°C and the alloy can withstand in excess of 350°C. Therefore, the system thermal design will be a more significant design parameter due to the heat limitations of the solder joint.

Full power dissipation is achievable with the part mounted on 120x51mm high-Tg FR4 board with 70μm inner and outer planes. Alternative mounting arrangements may be used, provided the heatsinking effect permits a combination of power dissipation and terminal temperature within the derating curve shown.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Recommended Layouts and Measurement Probe Positions




Size	Coating	Values	a	b	c	L	d	e	f								
1206	Green Underside	0.5, 0.6, 1, 4 - 6	1.55	0.5	0.7	0.55	1.9	2.6	1.25								
		2 - 3, 10	1.05			1.55											
		7 - 9	1.35			0.95											
2010		0.5	2.61	0.8	1.05	0.3	2.9	4.32	1.2								
		1, 4 - 5	2.29			0.95											
		2, 6 - 8	1.99			1.55											
		3	1.49			2.55											
		9 - 10	1.74			2.05											
1020			1, 1.5, 2, 2.5, 3	0.925	0.8	2.365	1.04	5.53	2	1.77							
2512	Black	All	2.7	1.0	1.45	2.95	3.6	5.4	1.5								
2512	Green Underside	0.5	3.13		1.2	0.54	0.94			3.45							
		0.75	2.93								2.04						
		1	2.38									3.04					
		1.5	1.88										3.54				
		2 - 3	1.63											1.54			
		4, 4.5	2.63												2.04		
		5 - 6	2.38													3.04	
		6.5, 7	1.88														3.54
		8 - 10	1.63														
1225		0.1 - 0.25	1.4	0.8	3.0	0.6	6.8	2.0	2.25								
		0.3 - 1.0	0.9							1.6							
		1.5	1.4								0.6						
		2.0	1.2									1.0					
		2.5, 3.0	0.9										1.6				

Note: These resistors are designed to have the correct ohmic value when mounted on a PCB. Probed measurements may read higher values and mounting offsets may need to be established to account for this, especially with sub-milliohm values.

Symmetrical Kelvin Connected (4-Wire) Alternatives

Package	Resistance (mΩ)	a	b	c	d	e	f
1206	0.2 - 0.4	0.75	1.9	0.4	0.6	2.15	0.6
2010	0.2 - 0.4	1.35	2.89	1.4	0.6	3.08	0.6
2512 - Green Underside	0.15 - 0.3	2	3.4	1.0	0.6	2.8	0.6
	0.4	1.5	3.4	2.0	0.6	3.8	0.6

The diagram shows a symmetrical Kelvin connected (4-wire) alternative layout for a resistor. It includes dimensions a, b, c, d, e, and f, and labels for the current sense pads (I+, I-) and voltage sense pads (V+, V-).




General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

ULR Series

Packaging



Type	Resistance (mΩ)	A	B	W	E	F	P0	P1	P2	ØD0	ØD1	T	Quantity (EA)
1206	<0.5	1.90 ± 0.1	3.60 ± 0.1	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.0min	1.25 ± 0.1	2000 on 7" reel
	≥0.5											0.87 ± 0.1	
2010	<0.5	2.85 ± 0.1	5.55 ± 0.1	12.0 ± 0.2	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.5min	1.35 ± 0.1	
	≥0.5											0.85 ± 0.1	
1020	1 - 3												
2512 Black	0.50 - 0.75	3.40 ± 0.1	6.75 ± 0.1	12.0 ± 0.1	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.4min	1.45 ± 0.2	
	>0.75											0.81 ± 0.1	
2512 Green Underside	<0.5	3.40 ± 0.1	6.75 ± 0.1	12.0 ± 0.3	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.5min	1.4 ± 0.1	
	≥0.5											0.8 ± 0.1	
1225	0.1 - 0.4	3.40 ± 0.1	6.75 ± 0.1	12.0 ± 0.3	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.5min	1.2 ± 0.1	
	0.5-3.0											0.80 ± 0.1	

Note:

1. The cumulative tolerance of 10 sprocket hole pitch is ± 0.2 mm.
2. Carrier camber shall not be more than 1 mm per 100 mm through a length of 250 mm.
3. A & B measured 0.3 mm from the bottom of the packet.
4. T measured at a point on the inside bottom of the packet to the top surface of the carrier.
5. Pocket position relative to sprocket hole is measured as the true position of the pocket and not the pocket hole.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

BI Technologies IRC Welwyn

www.ttelectronics.com/resistors

ULR Series

Ordering Procedure

This product has two valid part numbers:

European (Welwyn) Part Number: ULR2-R0015FT2 (2512, 1.5 milliohms $\pm 1\%$, Pb-free)

U	L	R	2	-	R	0	0	1	5	F	T	2
1				2				3	4			

1 Type	2 Value	3 Tolerance	4 Packing	
ULR1S, ULR1, ULR15S, ULR2N, ULR2, ULR25, ULR3, ULR3N, ULR5	3 to 6 characters R = ohms	F = $\pm 1\%$	T2 = Plastic tape	
		J = $\pm 5\%$	All sizes	2000/reel

USA (IRC) Part Number: ULRB22512R0015FLFSLT (2512, 1.5 milliohms $\pm 1\%$, Pb-free)

U	L	R	B	2	2	5	1	2	R	0	0	1	5	F	L	F	S	L	T
1				2				3				4	5	6					

1 Type	2 Size	3 Value	4 Tolerance	5 Termination	6 Packing	
ULRG1, ULRG15, ULRG2, ULRG25, ULRG3, ULRB1, ULRB2	1206	4 - 6 characters R = ohms	F = $\pm 1\%$	LF = Pb-free	SLT = Plastic tape	
	2010		J = $\pm 5\%$		All sizes	
	2512				2000/reel	

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

BI Technologies IRC Welwyn

www.ttelectronics.com/resistors

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TT Electronics:](#)

[ULRB12512R003FLFSLT](#) [ULRB12512R004FLFSLT](#) [ULRB12512R005FLFSLT](#) [ULRB12512R007FLFSLT](#)
[ULRB12512R006FLFSLT](#) [ULR1R002JLF](#) [ULR1R0015JLF](#) [ULR1R004FLFTR](#) [ULR1R005FLFTR](#) [ULR1R0075FLFTR](#)
[ULR1R006FLFTR](#) [ULR1R007LFTR](#) [ULRB1-2512-R0065-F-LF-SLT](#) [ULRB1-2512-R003-F-LF-SLT](#) [ULRB1-2512-](#)
[R0075-J-LF-SLT](#) [ULRB1-2512-R010-J-LF-SLT](#) [ULRB1-2512-R004-F-LF-SLT](#) [ULRB1-2512-R0065-J-LF-SLT](#) [ULRB1-](#)
[2512-R0035-F-LF-SLT](#) [ULRB1-2512-R0035-J-LF-SLT](#) [ULRB1-2512-R006-J-LF-SLT](#) [ULRB1-2512-R007-F-LF-SLT](#)
[ULRB1-2512-R007-J-LF-SLT](#) [ULRB1-2512-R0045-F-LF-SLT](#) [ULRB1-2512-R0045-J-LF-SLT](#) [ULRB1-2512-R0055-F-](#)
[LF-SLT](#) [ULRB1-2512-R0055-J-LF-SLT](#) [ULRB1-2512-R003-J-LF-SLT](#) [ULRB1-2512-R004-J-LF-SLT](#) [ULRB1-2512-](#)
[R0025-F-LF-SLT](#) [ULRB1-2512-R0025-J-LF-SLT](#) [ULRB1-2512-R001-J-LF-SLT](#) [ULRB1-2512-R0015-J-LF-SLT](#) [ULRB1-](#)
[2512-R002-J-LF-SLT](#) [ULRB1-2512-R0005-J-LF-SLT](#) [ULRB1-2512-R00075-F-LF-SLT](#) [ULRB1-2512-R00075-J-LF-SLT](#)