


Vitreous Enamelled Wirewound Resistors

W20 Series

Features

- IECQ-CECC approved
- Suitable for harsh environments
- Impervious lead free vitreous enamel coating
- Overload characteristics ideal for protection circuits
- High stability and reliability
- High power dissipation for size



All parts are Pb-free and comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)

Electrical Data

Commercial		W21	W22	W23	W24
Power rating at 25°C	watts	3.0	7.0	10.5	14.0
Resistance range at	1% tolerance	1R to 10K	1R to 22K	1R to 60K	1R to 100K
	2% tolerance	0R5 to 10K	0R5 to 22K	1R to 60K	1R to 100K
	5% tolerance	0R1 to 10K	0R1 to 22K	0R15 to 60K	0R2 to 100K
TCR (-55° to 200° C)	ppm/°C	Typically: <+75		Maximum: +200	



BS IECQ-CECC 40-201-002 Requirements		JB	KB	LB	MB
Power rating at 25°C	watts	2.9	7.0	10.5	14.0
Power rating at 70°C	watts	2.5	6.0	9.0	12.0
Resistance range at	1% tolerance	1R to 10K	1R to 20K	1R to 56K	1R to 100K
	2% tolerance	0R5 to 10K	0R5 to 20K	1R to 56K	1R to 100K
	5% tolerance	0R1 to 10K	0R1 to 20K	0R15 to 56K	0R2 to 100K
TCR (-55° to 200° C)	ppm/°C	≥5 ohms < 10 ohms: ±400		≥10 ohms: ±200	

This table indicates the CECC specification requirements, and these are met or exceeded by the corresponding W20 series products

Applicable to commercial and approved ranges					
Limiting element voltage	volts	100	200	500	750
Standard values		E24 preferred. Other values to special order			
Thermal impedance	°C/watt	88	44	29	22
Ambient temperature range	°C	-55 to 200			

Physical Data

Dimensions (mm) and Weight (g)					
Type	L max	D max	f min	d nom	Wt.nom
W21	12.7	5.6	22.75	0.8	1
W22	22.0	8.0	23.1	0.8	2
W23	38.0	8.0	-	0.8	3.5
W24	53.5	8.0	-	0.8	5



Construction

A high purity ceramic substrate is assembled with interference fit end caps to which are welded the termination wires. The resistive element is wound on the substrate and welded to the caps; the vitreous enamel protective coating is then applied.

Terminations

- Material** Copper clad steel wire, nickel plated and solder-coated.
- Strength** The terminations meet the requirements of IEC 68.2.21.
- Solderability** The terminations meet the requirements of IEC 115-1, Clause 4.17.3.2.
- Length** W23's and W24's are not supplied on tape. Minimum lead length is 30 mm.

Marking

The resistors are legend marked with type reference, resistance value and tolerance. Values are marked in accordance with IEC 62.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Vitreous Enamelled Wirewound Resistors

W20 Series

Solvent Resistance

The body protection and marking are resistant to all normal industrial cleaning solvents suitable for printed circuits


Flammability

All materials used in the construction of W20 series resistors are inorganic and inherently non-burning.

Performance Data


		IECQ-CECC 40201-002	Actual Performance	
		Requirements	Maximum	Typical
Load at commercial rating: 1000 hrs at 25°C	ΔR%		5	3.5
Load at CECC rating: 1000 hours at 25°C	ΔR%	5	5	3.5
Dry heat: 1000 hours at 200°C	ΔR%	5	2	1
Shelf life: 12 months at room temperature	ΔR%	not specified	0.03	0.02
Derating		see derating curve		
Short term overload	ΔR%	1	1.0	0.2
Climatic	ΔR%	5	0.5	0.2
Climatic category	ΔR%	55/200/56		
Long term damp heat	ΔR%	5	0.05	0.02
Temperature rapid change	ΔR%	1	0.5	0.2
Resistance to solder heat	ΔR%	1	0.25	0.03
Vibration and bump	ΔR%	1	0.25	0.05
Noise (in decade of frequency)	μv/v	not specified	zero	zero
Robustness	ΔR%	1	0.4	0.05
Insulation resistance	ohms	not specified	> 1G ohm	> 1G ohm
Voltage Proof	volts	not specified	500 min	500 min
Pulse handling				

Data available at: <https://www.ttelectronics.com/TTElectronics/media/ProductFiles/Resistors/ApplicationNotes/Wirewound-Pulse-Overload-Resistors.pdf>



Packaging

For W21 the standard method of packaging is taped in Ammo Packs. For W22 the standard method of packaging is taped and reeled. W23's and W24's are available only as loose packed in boxes.



Type	b
W21	63±2
W22	73±2

Application Notes

The termination should not be bent closer than 1.6mm from the body, and the recommended minimum bend radius is 1.2mm. The terminations are solderable to within 4mm from the body. When cold, vitreous enamel has excellent insulation resistance. In common with all insulants the specific resistance of the enamel decreases with increase in temperature. Therefore, resistors operated at near maximum temperature cannot be classed as insulated and should not be used in contact with any conducting material. Care must be taken when determining clearance distance between the resistor body and the printed circuit board or other components to ensure these are not over heated. Resistance is measured 6mm from body.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Vitreous Enamelled Wirewound Resistors

W20 Series

Ordering Procedure

Example: **W22-3K3JI** (W22, 3.3 kilohms $\pm 5\%$, Pb-free)

W	2	2	-	3	K	3	J	I
1		2			3		4	

1	2	3	4	
Type	Value	Tolerance	Packing & Termination Finish	
W21	E24 = 3/4 characters	F = $\pm 1\%$	I = Standard packing & Pb-free	
W22	R = ohms	G = $\pm 2\%$	W21	1000/box
W23	K = kilohms	J = $\pm 5\%$	W22	700/reel
W24			W23, W24	50/box

For CECC released product follow the MPN with text indicating the relevant release and style.
(Note that this additional text does not form part of our MPN.) Example: **W22-3K3JI IECQ-CECC40201-002 KB**

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TT Electronics:

[W22 82 5%A](#) [W2151002JA](#) [W21150R0FTR](#) [W22150R0FTR](#) [W2275R0FTR](#) [W21 10 5%LFTR](#) [W22-27R0JLF](#) [W24 24K 5%B](#) [W2110R0JLFTR](#) [W21 22 5%TR](#) [W22 7.5 5%TR](#) [W215-R500-JALF](#) [W21 10 5%](#) [W21R100JLFTR](#) [W21 .18 5%LF](#) [W24-5K-JI](#) [W21 .1 5%LFR](#) [W21 .5 5%LF](#) [W21 .1 5%LFTR](#) [W225R60JR](#) [W236R80JB](#) [W2120R0JA](#) [W212700JA](#) [W2155010JA](#) [W221500JR](#) [W2152700JA](#) [W211501JA](#) [W233302JB](#) [W231R00JB](#) [W241R50JB](#) [W221R20JR](#) [W22R390JR](#) [W242R20JB](#) [W21R220JA](#) [W2151R00JA](#) [W225601JR](#) [W218201JA](#) [W2154700JA](#) [W232200JB](#) [W21582R0JA](#) [W214R70JA](#) [W23R470JB](#) [W2152701JA](#) [W232202JB](#) [W231500JB](#) [W2156801JA](#) [W22R330JR](#) [W232201JB](#) [W246R80JB](#) [W215R60JA](#) [W216R80JA](#) [W234701JB](#) [W234700JB](#) [W2155601JA](#) [W2115R0JA](#) [W243301JB](#) [W2310R0JB](#) [W221801JR](#) [W243300JB](#) [W23R680JB](#) [W2155001JA](#) [W221R80JR](#) [W226801JR](#) [W21R270JA](#) [W211200JA](#) [W216800JA](#) [W2222R0JR](#) [W21539R0JA](#) [W2155600JA](#) [W212701JA](#) [W2154R70JA](#) [W21R100JA](#) [W2153301JA](#) [W21R150JA](#) [W2155R60JA](#) [W228R20JR](#) [W22R560JR](#) [W22R680JR](#) [W246802JB](#) [W215R120JA](#) [W231000JB](#) [W21R180JA](#) [W211500JA](#) [W215R390JA](#) [W244701JB](#) [W244R70JB](#) [W242201JB](#) [W215R100JA](#) [W223301JR](#) [W2215R0JR](#) [W2182R0JA](#) [W221R50JR](#) [W2151R80JA](#) [W2227R0JR](#) [W2151202JA](#) [W21100RJA](#) [W215R680JA](#) [W2139R0JA](#) [W215R220JA](#) [W2158200JA](#)