



**PART AFTER  
UNRESTRICTED RECOVERY**

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
A	"U" TOL. WAS $\pm 10\%$	8-7-84	JLJ

TABLE OF DIMENSIONS:

PART NUMBER	H		J			P	R	S	T	JO	HW	JW	U
	Min	Max	POLY Min	VITON Min	Max								
	a	b	a	a	b								
202D211-X-32	.88 (22,3)	.45 (11,5)	.88 (22,3)	.55 (13,9)	.25 (6,4)	3.00 (76,2)	.46 (11,7)	.12 (3,05)	.040 (1,02)	2.23 (56,6)	.06 (1,52)	.045 (1,14)	.55 (14,0)
202D221-X-32	1.01 (25,6)	.59 (15,0)	1.01 (25,6)	.63 (16,0)	.29 (7,4)	3.25 (82,6)	.48 (12,2)	.12 (3,05)	.040 (1,02)	2.36 (59,9)	.06 (1,52)	.045 (1,14)	.59 (15,0)
202D232-X-32	1.16 (29,4)	.74 (18,8)	1.16 (29,4)	.72 (18,2)	.33 (8,4)	3.50 (88,9)	.48 (12,2)	.12 (3,05)	.040 (1,02)	2.48 (63,0)	.07 (1,78)	.045 (1,14)	.60 (15,2)
202D242-X-32	1.34 (34,0)	.90 (22,9)	1.34 (34,0)	.84 (21,3)	.38 (9,7)	4.00 (101,6)	.48 (12,2)	.12 (3,05)	.040 (1,02)	2.87 (72,9)	.07 (1,78)	.045 (1,14)	.62 (15,7)
202D253-X-32	1.47 (37,3)	1.16 (29,5)	1.47 (37,3)	.91 (23,1)	.41 (10,5)	4.25 (108,0)	.55 (14,0)	.12 (3,05)	.065 (1,65)	2.85 (72,4)	.08 (2,03)	.045 (1,14)	.70 (17,8)
202D263-X-32	1.72 (43,6)	1.34 (34,1)	1.72 (43,6)	1.07 (27,1)	.48 (12,2)	4.50 (114,3)	.60 (15,2)	.12 (3,05)	.065 (1,65)	2.92 (74,2)	.08 (2,03)	.045 (1,14)	.78 (19,8)
202D274-X-32	1.97 (50,0)	1.62 (41,2)	1.97 (50,0)	1.24 (31,4)	.56 (14,3)	4.65 (118,1)	.60 (15,2)	.12 (3,05)	.065 (1,65)	2.86 (72,6)	.09 (2,29)	.055 (1,40)	.78 (19,8)
202D285-X-32	2.47 (62,7)	1.85 (47,0)	2.47 (62,7)	1.54 (39,1)	.69 (17,6)	4.75 (120,7)	.63 (16,0)	.12 (3,05)	.08 (2,03)	2.78 (70,6)	.10 (2,54)	.055 (1,40)	.81 (21,0)
202D296-X-32	2.73 (69,3)	2.35 (59,7)	2.73 (69,3)	1.70 (43,1)	.77 (19,6)	5.00 (127,0)	.63 (16,0)	.12 (3,05)	.08 (2,03)	2.64 (67,1)	.10 (2,54)	.055 (1,40)	.81 (21,0)
202D299-X-32	3.22 (81,7)	2.64 (67,1)	3.22 (81,7)	2.01 (51,0)	.90 (22,9)	5.25 (133,4)	.63 (16,0)	.12 (3,05)	.08 (2,03)	2.70 (68,6)	.10 (2,54)	.055 (1,40)	.81 (21,0)

NOTES:

1. All dimensions are in inches (millimeters)
2. Dimensions appearing in Table are as follows:  
a - As supplied  
b - After unrestricted recovery
3. Part shall have injection and vent ports, located as shown.

ORDERING INFORMATION:

Base part number 202D221 -4 -32  
 Material dash number \_\_\_\_\_  
 -3 Polyolefin, semi-rigid (RT-301/7)  
 -4 Polyolefin, flexible (RT-1304)  
 -12 Viton (RT-1312)  
 -25 Elastomer, fluid-resistant (RT-1325)  
 Modification number \_\_\_\_\_

SPECIFICATION CONTROL DRAWING (LIMITED DISTRIBUTION)

If this document is printed it becomes uncontrolled.  
Check for the latest revision.

THIS DRAWING AND THE INFORMATION SET FORTH HEREON ARE THE PROPERTY OF RAYCHEM CORPORATION, AND ARE TO BE HELD IN TRUST AND CONFIDENCE. PUBLICATION, DUPLICATION, DISCLOSURE, OR USE FOR ANY PURPOSE NOT EXPRESSLY AUTHORIZED IN WRITING BY RAYCHEM CORPORATION IS PROHIBITED.	DRAWN	<i>R. Watson 10-8-80</i>	<b>Raychem</b> RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025
	CHECKED	<i>Phyllis 10/14/80</i>	
	DESN APPD	<i>Phyllis 10/14/80</i>	TITLE
	MFG APPD	<i>Paul 10/14/80</i>	BOOT, STRAIGHT, WITH LIP
	QC APPD	<i>Long 10/19/80</i>	CODE IDENT.
MKTG APPD	<i>V. Rotman 10/19/80</i>	DWG. NO.	202D2XX-X-32
Trace Service	<i>R. Watson 10/19/80</i>	NO. 00080	
DO NOT SCALE THIS DRAWING	PROJECT	SIZE 8	SHEET 1 OF 1

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[202D211-4-32-0](#)