Molded Parts Customer Drawing


IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED. CHECK FOR THE LATEST REVISION.

Part Number : 234A011thru071

ECO No.: ECO-11-005139

NOTES

- inches 1. All dimensions are in ; [millimeters]
- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- 3. Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
- 4. Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.
- 5. Weight shown in table of dimensions is based on polyolefin part.
- **6. /180 coating is only available on 234A011, 234A021 and 234A032. Contact factory for additional sizes.






	TABLE OF DIMENSIONS													
	PART	Н		J		K		Р	R	S	W	X	Weight	This Boot Fits
	NÜMBER	±5%	±5%	±5%	±5%	Min	Max	±10%	±10%	±10%	±20%	±20%	Nom	Cannon—Cinch
		а	b	а	b	а	b	Ь	b	b	b	Ь	b	
**	234A011	.80 [20,3]	.80 [20,3]	.42 [10,7]	.42 [10,7]	.31 [7,9]	.16 [4,1]	1.02 [25,9]	.85 [21,6]	<u>.60</u> [15,2]	<u>.04</u> [1,02]	<u>.12</u> [3,05]	. <u>0048</u> [2,18]	DE-9
**	234A021	1.11 [28,2]	1.11 [28,2]	.42 [10,7]	<u>.42</u> [10,7]	.40 [10,2]	.21 [5,3]	1.21 [30,7]	<u>.97</u> [24,6]	<u>.73</u> [18,5]	<u>.04</u> [1,02]	<u>.12</u> [3,05]	.0059 [2,68]	DA-15
**	234A032	1.66 [42,2]	1.66 [42,2]	.42 [10,7]	.42 [10,7]	.55 [14,0]	.29 [7,4]	1.69 [42,9]	1.10 [27,9]	<u>.87</u> [22,1]	<u>.04</u> [1,02]	<u>.12</u> [3,05]	.0102 [4,63]	DB-25
	234A042	2.31 [58,7]	2.31 [58,7]	.42 [10,7]	.42 [10,7]	.68 [17,3]	<u>.34</u> [8,6]	2.10 [53,3]	1.20 [30,5]	1.00 [25,4]	<u>.04</u> [1,02]	.12 [3,05]	.0 <u>132</u> [5,99]	DC-37
	234A052	2.28 [57,9]	2.28 [57,9]	.54 [13,7]	.54 [13,7]	.75 [19,1]	.42 [10,7]	2.20 [55,9]	1.27 [32,3]	1.00 [25,4]	<u>.04</u> [1,02]	.12 [3,05]	.0152 [6,90]	DD-50
	234A061	.80 [20,3]	.80 [20,3]	.42 [10,7]	<u>.42</u> [10,7]	.31 [7,9]	<u>.15</u> [3,8]	1.02 [25,9]	.73 [18,5]	.48 [12,2]	.04 [1,02]	.12 [3,05]	.0045 [2,04]	DE-9
	234A071	1.11 [28,2]	1.11 [28,2]	.42 [10,7]	<u>.42</u> [10,7]	.40 [10,2]	.20 [5,1]	1.21 [30,7]	.78 [19,8]	.53 [13,5]	.04 [1,02]	<u>.12</u> [3,05]	.0056 [2,54]	DA-15



Raychem Molded Parts 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 Revision: R1

Date: 20APR11

Page 1 of 2

Description : Boot, Rectangular

Subminiature, 90 DEGREE

End Entry


Molded Parts Customer Drawing

Part Number: 234A011thru071

ECO No.: ECO-11-005139

COMPATABILITY	/ CHART				
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION
-3	Polyolefin, Semi-rigid	RT-301	/42; /86,**/180,/184	S-1017; S-1048	Adhesive
-4	Polyolefin, Flexible	RT-1304	/42; /86,**/180,/184	S-1017; S-1048	Adhesive
-8	Polyolefin, Space	RT-1308	N/A		
-12	*VITON, Flexible	RT-1312	N/A		
-25	Elastomer, Fluid Resistant	RT-1325	/86; /225	S-1048: S-1206	Adhesive
-100	Polyolefin, Semi-flexible ZEROHAL™	RT-1323	/86 :**/180;/184	S-1048: S-1030	Adhesive

^{*}VITON is a Registered Trademark of Dupont



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION



Raychem Molded Parts 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision: R1

Date: 20APR11

Page 2 of 2

© 2007,2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All Rights Reserved.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>TE Connectivity</u>: 234A011-4/42-0