



NOTES:

- ALL DIMENSIONS ARE IN $\frac{\text{INCHES}}{\text{[MILLIMETERS]}}$
- DIMENSIONS APPEARING IN TABLE ARE AS FOLLOWS:
 - AS SUPPLIED
 - AFTER UNRESTRICTED RECOVERY
- COATING IS OPTIONAL. AS SUPPLIED DIMENSIONS APPEARING IN TABLE ARE FOR UNCOATED PARTS. WHEN COATING IS ADDED, ENTRY DIAMETERS WILL BE REDUCED BY .06 MAX.
- MOLDING PORTS ARE OPTIONAL. WHEN -00 MODIFICATION NUMBER IS SPECIFIED MOLDING PORTS WILL BE LOCATED AS SHOWN.
- WEIGHT SHOWN IN TABLE OF DIMENSIONS IS BASED ON POLYOLEFIN PART.



| REVISIONS | | |
|-----------|---------------------------|----------|
| LTR | DESCRIPTION | DATE |
| U | REVISED PER ECO-13-013640 | 09/20/13 |

ORDERING INFORMATION

BASE PART NUMBER 382A0XX -XX -XX /XXX -0

MATERIAL DASH NUMBER _____
(SEE COMPATABILITY CHART)

MODIFICATION NUMBER _____
(IF NECESSARY, SEE FRONT OF SCD BINDER FOR A COMPLETE LIST)

ADHESIVE SLASH NUMBER _____
(IF NECESSARY, SEE COMPATABILITY CHART)

COLOR DESIGNATOR _____

TABLE OF DIMENSIONS

| PART NUMBER | H | | J | | K | | P | R | S | T | HW | JW & KW | C | Weight |
|-------------|----------------|----------------|----------------|---------------|----------------|---------------|----------------|----------------|-----------------|----------------|---------------|---------------|---------|------------------|
| | Min a | Max b | Min a | Max b | Min a | Max b | ±10% b | ±10% b | ±10% b | ±10% b | ±20% b | ±20% b | ±5% b | Norm b |
| 382A012 | .52 [13,2] | .24 [6,1] | .26 [6,6] | .13 [3,3] | .26 [6,6] | .13 [3,3] | .88 [22,4] | .76 [19,3] | .94 [23,9] | .61 [15,5] | .06 [1,52] | .04 [1,02] | 22 1/2" | .004 [1,81] |
| 382A023 | 1.06 [26,9] | .49 [12,4] | .52 [13,2] | .24 [6,1] | .52 [13,2] | .24 [6,1] | 1.50 [38,1] | 1.70 [43,2] | 2.10 [53,3] | 1.30 [33,0] | .10 [2,54] | .06 [1,52] | 22 1/2" | .026 [11,79] |
| 382A034 | 1.52 [38,6] | .71 [18,0] | 1.06 [26,9] | .49 [12,4] | 1.06 [26,9] | .49 [12,4] | 2.58 [65,5] | 3.10 [78,7] | 3.10 [78,7] | 2.20 [55,9] | .12 [3,05] | .10 [2,54] | 22 1/2" | .141 [63,96] |
| 382A046 | 2.19 [55,6] | 1.02 [25,9] | 1.06 [26,9] | .50 [12,7] | 1.06 [26,9] | .50 [12,7] | 3.35 [85,1] | 3.70 [94,0] | 4.40 [111,8] | 2.80 [71,1] | .18 [4,57] | .10 [2,54] | 22 1/2" | .249 [112,95] |

COMPATIBILITY CHART

| MATERIAL DASH NO. | MATERIAL DESCRIPTION | COATING SLASH NUMBER | COATING S NUMBER |
|-------------------|---|----------------------|-----------------------------|
| -3 | Polyolefin, Semi-rigid | /42;/86;/87 | S-1017;S-1048;S-1052 |
| -4 | Polyolefin, Flexible | /42;/86;/87;/180 | S-1017;S-1048;S-1052;S-1030 |
| -5 | Elastomer, Flexible | /42 | S-1017 |
| -6 | Silicone | N/A | |
| -12 | *VITON, Flexible *VITON is a Registered Trademark of Dupont | N/A | |
| -25 | Elastomer, Fluid Resistant | /42;/86;/180;/225 | S-1017;S-1048;S-1030;S-1206 |
| -100 | Polyolefin, Semi-flexible ZEROHAL™ | /86;/180 | S-1048;S-1030 |

IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED.
CHECK FOR THE LATEST REVISION.

Raychem Molded Parts
CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE INCHES. METRIC
DIMENSIONS ARE IN BRACKETS.
DECIMAL TOLERANCES
.XXX ± 0.005 [0.13 mm]
.XX ± 0.01 [0.25 mm]
.X ± 0.1 [0.50 mm]
ANGLE TOLERANCE
.X ± 1 DEG.

TE CONNECTIVITY RESERVES THE RIGHT TO
AMEND THIS DRAWING AT ANY TIME. USERS
SHOULD EVALUATE THE SUITABILITY OF THE
PRODUCT FOR THEIR APPLICATION.

© 2013 Tyco Electronics Corporation, a TE connectivity Ltd. company. All rights reserved.

DRAWN
MMazariegas

APPROVED
SGravano

THIRD ANGLE
PROJECTION



TE Connectivity

TITLE
TRANSITION, Y

SIZE B CODE IDENT. NO. 06090 DWG. NO. 382A012thru046

DO NOT SCALE THIS DRAWING

SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[382A012-100/180-0](#)