



- 1 SHELL MATERIAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER MIL-M-24519 OR PER ASTM D1538
- 2 JACKSCREW MATERIAL: 303 STAINLESS STEEL, PASSIVATED PER SAE-AMS-2700 AND DRY LUBED PER DOD-L-85645.
RETAINING RING MATERIAL: 17-4 STAINLESS STEEL, PASSIVATED PER SAE-AMS-2700. JACKSCREWS HAVE A .9mm
HEX SOCKET HEAD.
- 3 THIS CONFIGURATION TO BE TERMINATED WITH 30 AWG, 7 STRAND, TEFLON COLOR CODED WIRE. WIRING IS 1 TO 1.
- 4 THIS CONFIGURATION HAS THE SAME CONNECTOR TYPE TERMINATED TO EACH END OF THE JUMPER ASSEMBLY.
NOTE THAT CONNECTOR LOBES ARE FACIING IN OPPOSITE DIRECTIONS.
- 5 DIMENSIONS TYPICAL FOR BOTH CONNECTORS.
- 6 NANONICS PART NUMBER: JTM06512753PP2DC003N

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C SCHOLL	3 OCT 08	 Tyco Electronics Corporation Harrisburg, PA 17105-3608			
		CHK M STORRY	3 OCT 08				
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD —	—	NAME JUMPER ASSEMBLY, PLUG TO PLUG, TWO ROW DUALOBE, 65 POSITION, METAL, SPECIAL N12753			
	0 PLC ± — 1 PLC ± — 2 PLC ± .010 3 PLC ± .005 4 PLC ± —	PRODUCT SPEC —	—				
	ANGLES ± .1°	APPLICATION SPEC —	—				
MATERIAL	FINISH	WEIGHT —	A2	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
SEE NOTES	SEE NOTES			OPJN9	C=5-1925009-8		—
CUSTOMER DRAWING				SCALE	4:1	SHEET	1 of 1
						REV	A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-1925009-8](#)