


## Aluminium Housed Power Resistors

### Type CFH Series

#### Type CFH Series



The CFH is a high quality range of aluminium housed power resistors offering environmental protection to IP55, 6kV dielectric strength, 1.8kW power dissipation, and the ability to absorb electrical pulses of up to 24kJ.

The use of advanced materials in the construction of this device enables operating temperatures of up to 450°C giving very high power density.

#### Key Features

- **2200W in a 72cm<sup>2</sup> footprint**
  - Unparalleled power density of 31W/cm<sup>2</sup>
- **Impressive Pulse Capability**
  - Large active element can absorb up to 24kJ
- **No Heatsink Required**
  - Dissipates up to 950W in free air
- **Slimline Casing**
  - 30mm casing height for design flexibility
- **Environmental Protection to IP55**
  - Reliable in the harshest conditions


#### Applications

- Braking
- Balancing
- Capacitor Charging & Discharging
- Crowbar
- Filter
- Power Supplies
- Electrical Machinery
- Inrush Limiting

#### Characteristics - Electrical

|                                            | CFH350                                                                                                                                                                                                           | CFH500             | CFH750               | CFH1100              |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------------------|----------------------|
| Dissipation @ 25°C with Heatsink (Watts):  | 650                                                                                                                                                                                                              | 850                | 1300                 | 1800                 |
| Without Heatsink:                          | 350                                                                                                                                                                                                              | 500                | 750                  | 1100                 |
| With Water Cooled Heatsink (40°C):         | 750                                                                                                                                                                                                              | 1000               | 1500                 | 2200                 |
| Overload Rating (5s):                      | 4000                                                                                                                                                                                                             | 5600               | 8000                 | 12000                |
| Ohmic Value Min (Ohms):                    | 0R5                                                                                                                                                                                                              | 0R5                | 0R5                  | 0R5                  |
| Max:                                       | 10K                                                                                                                                                                                                              | 18K                | 27K                  | 27K                  |
| Tolerance:                                 | ±5% Standard                                                                                                                                                                                                     |                    |                      |                      |
| Maximum Working Voltage (DC/ACrms) Volts:  | 1500                                                                                                                                                                                                             | 2500               | 3500                 | 4000                 |
| Insulation Resistance (Volts):             | ≥10000 MΩ                                                                                                                                                                                                        |                    |                      |                      |
| Dielectric Strength (AC peak) Volts:       | 4500 standard and 6000 special                                                                                                                                                                                   |                    |                      |                      |
| Inductance (Henries):                      | 5-50 μH at 1000 Hz                                                                                                                                                                                               | 7-70 μH at 1000 Hz | 10-100 μH at 1000 Hz | 20-200 μH at 1000 Hz |
| Standard Heatsink area (mm <sup>2</sup> ): | 1600                                                                                                                                                                                                             | 1600               | 1600                 | 1600                 |
| Thickness (mm):                            | 135                                                                                                                                                                                                              | 135                | 135                  | 135                  |
| Protection Grade (IP):                     | IP55                                                                                                                                                                                                             |                    |                      |                      |
| Mounting:                                  | Vertically                                                                                                                                                                                                       |                    |                      |                      |
| Cable Length:                              | 300mm                                                                                                                                                                                                            |                    |                      |                      |
| Weight (g):                                | 460                                                                                                                                                                                                              | 670                | 920                  | 1250                 |
| Heat Dissipation:                          | Although the use of proprietary heat sinks with lower thermal resistance is acceptable, up rating is not recommended.<br>The use of proprietary heat sink compound to improve thermal conductivity is essential. |                    |                      |                      |

#### Dimensions



| Type | CFH350 | CFH500 | CFH750 | CFH1100 |
|------|--------|--------|--------|---------|
| L    | 110 mm | 160 mm | 220 mm | 320 mm  |
| P    | 60 mm  | 110 mm | 140 mm | 240 mm  |

### Application Notes

**Power rating.** The dissipation power of a resistor depends also from the mounting position. If the resistor is mounted onto a surface, the latter takes part positively (if it is large and conductive) or negatively (if it is small and insulating) to the thermal dissipation.

Data of power rating are referred to a resistor mounted vertically, with terminals in the lower side and away from the nearest surface at least 10cm, in order to avoid thermal influence from the wall.

**Surface temperature rise @ Pn.** During the load application, the surface temperature is not homogeneous, and it is higher on the flat surface of the resistor (surface that in the practical application shall be fixed to a heat sink or to a metallic surface to help the thermal dissipation).

**Max.power rating of a resistor mounted onto a heat sink.** Standard heat sink is a common heat sink (as shown) used for the cooling of semiconductors, with two grooves for components mounting.

The distance between the axes of these two grooves is 80 mm. In this case both heat sink and resistor will be mounted upright. The length of the heat sink shall be at least 40 mm longer than the resistor's body (20 mm for each side).

**Power rating of a resistor mounted on a water-cooled heat sink.** If the heat sink is water-cooled, power dissipation increases considerably, and the limiting power rating is due to temperature of the resistor body. In the case illustrated in the specifications board, the temperature of the heat sink is 40°C and the resistor's surface reaches 300°C. In this case too, the length of the heat sink shall be at least 20 mm longer than the resistor's body.

**Absorbed energy @ 250°C ΔT.** It represents the quantity of energy stored into the resistor when it has reached 250°C of temperature rise. The above indication is an index of the thermal capacity of the resistor.

**Absorbed energy in 5".** It gives an index of behaviour of the resistor to short overloads.

**Absorbed energy in time ≥0.2".** During a short impulse (from 0 to 2 sec.), the resistor may stand only the energy that the thermal capacity of the resistance wire is able to absorb. In fact the phenomenon is too short to let significant heat conduction from wire to filling material. The energy absorbed from the resistor in this case results from this simple equation:

$$Q_J = C_s P \Delta T \text{ where:}$$

- QJ is the quantity of energy expressed in Joule, - Cs is the specific heat of the employed resistance alloy expressed in  $J g^{-1} \cdot ^\circ K^{-1}$ , - P is the weight of the wire in grams and - ΔT is the rise of temperature, expressed in °K, reached by the wire during the impulse.

As type and quantity of wire are characteristics of every resistance value and resistor model, the acceptable temperature limit of wire is relevant.


This limit (@ 25°C) is:

- 500°C for the standard operations (steady state load);
- 800°C for not repeatable overload.


The following graphs show these two conditions for each resistance value and resistor type.

### Pulse Energy

Absorbed energy for wire temperature of 500°C  
(Impulse time ≤ 0,2")



Absorbed energy for wire temperature of 800°C  
(Impulse time ≤ 0,2")



These graphs are irregular owing to the necessity to adapt the commercial dimension of wire to the resistance range, however they are enough to show the trend of this characteristic.

Should the energy value of an impulse be too close to the limits given from these graphs, it is suitable to consult the factory for further information concerning the precise value of absorbed energy for the used resistor.

## Aluminium Housed Power Resistors

### Type CFH Series

#### Application Notes (continued)

**Resistance Range.** The resistance range fulfils almost all the use of power resistors, but in cases of special requirements, lower or higher resistance values are available on request as well as closer tolerances.

**Inductance.** The inductance changes with the resistance value and is not very influenced from frequency. On request the CFH resistors are available with non inductive windings (Airtion-Perry's system) and are identified by adding the letter N after the CFH identification (e.g.CFHN500). The inductance of the CFHN resistors is less than 1  $\mu$ H.

**Parasitic Capacity.** Parasitic capacity does not depend on the resistance value, but it changes with frequency. The supplied value are just referred to 1 kHz (the higher) and 100 kHz. During normal load conditions the effects of parasitic capacity are negligible. However in the presence of transients of high voltage <10 $\mu$ sec, the housing may be a source of interference for most sensitive electronic circuits. For a correct grounding of the housing, CFH resistors are available, on request, with a threaded hole M5.

**Limiting Element Voltage.** This is the maximum voltage, which should not be exceeded during the application conditions. The rated values are rather elevated, but special designs with higher limiting element voltage are available for particular requirements.


The limiting element voltage of non inductive resistors is lower than the standard resistors (Please contact us for advice).

**Insulation resistance and dielectric strength.** After a long load time, the insulation resistance of CFH resistors keeps elevated as the employed insulating material does not get damaged despite the high thermal conditions.

**Thermal time constant.** The dimension of the resistor models is proportional to power rating and weight, therefore their behaviour during the rise of temperature, when the rated power is applied, is analogous.

Of course the application of a heat sinks or the mounting of the resistor on a surface, will modify the thermal time constant which is peculiar for each application.


#### Thermal Time Constant Kt




## Aluminium Housed Power Resistors

### Type CFH Series

#### Derating Curve



#### Surface Temperature Rise



#### How to Order

| CFH                                   | 750                               | A                                                 | 680R                                                       | J         |
|---------------------------------------|-----------------------------------|---------------------------------------------------|------------------------------------------------------------|-----------|
| Common Part                           | Power Rating                      | Termination                                       | Resistance Value                                           | Tolerance |
| CFH - Aluminium Housed Power Resistor | 350 W<br>500 W<br>750 W<br>1100 W | A - 300mm Flying Leads<br>B - 1000mm Flying Leads | 0.1ohm (100mΩ) R10<br>1 ohm (1000mΩ) 1R0<br>1K (1000Ω) 1K0 | J - 5%    |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[CFH350A10RJ](#)