

REV. A DCO 144519

COIL: @ 25°C	1007	CUSTOMER DATA SHEET
RESISTANCE 44 OHMS ±1	<u>0%</u>	BLUE BEAD-
NOMINAL VOLTAGE5.0 VDC	ak og ga parter, menga sigligang primaga minimum kanan dan dan disaksi kanaliki dag dag dag dag dag dag dag sa	
MUST OPERATE		B1 Q A2 O X1 Q A3
MUST RELEASE	.26 VDC MIN.	B3 O X2 O B2 O A1
ENVIRONMENT:	20	TERMINAL VIEW
VIBRATION 10 Hz TO 3000	<i>J</i>	CONTACT RATING:
SHOCK	MS. DURATION	LOW LEVEL TO 2A 28VDC RES
TEMPERATURE <u>-65</u> °C	ro <u>+125</u> °c	100,000 OPS
NOTES: OPERATE & RELEASE 4 MS MAX. STABILIZATION 2.5 MS MAX.		DR. B.D. 11SEP2008 CK (NB 9/1)/ S
		Tyco Electronics Tyco Electronics Tyco Electronics Tyco Electronics corporation ALL INTERNATIONAL RIGHTS RESERVED
CUSTQPL	TE NUMBER	CII PART NUMBER
CUST. NO. M39016/13-073P REV.	2-1617073-1	3SBC 2018A2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 3SBC2018A2