

TOLERANCE OF LEAD LENGTH: UP TO 24 INCHES  $[609.6] = \pm .12 [\pm 3.0]$ 24 INCHES [609.6] & UP =  $\pm 1\%$ 

2. MARKED PER MIL-STD-130.

3. TO MATE WITH AMP LGH-1/2RECEPTACLE WITH .53 [13.4] BARREL DEPTH.

WHERE APPLICABLE "B" STRIP LENGTH IS SOLDER DIPPED.

5. OPERATING VOLTAGE: 10 KVDC AT 0 TO 70,000 FEET, -55°C TO 125°C.

THIS DRAWING IS A CONTROLLED DOCUMENT. **ETE** TE Connectivity 1-16-90 TOLERANCES UNLESS OTHERWISE SPECIFIED: INCHES[MM] LEAD ASS'Y, SGL. END, LGH-1/2 ± -± .02 [0.5] ± -APPLICATION SPEC SIZE CAGE CODE DRAWING NO RESTRICTED T 1 |00779 **C-**830611 SEE CALLOUTS SCALE 4:1 SHEET 1 OF 1 REV JSTOMER DRAWING

DATE DWN APVE

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 830611-8