


REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D1	ECR-20-006499	06MAY2020	RK	HL

PD-Caps Semirigid Polyolefin Heat-shrinkable End Caps

As Supplied



After Unrestricted Recovery


Outer Jacket
Heat shrinkable sem-irigid, irradiated,
modified polyolefinInner Wall
Adhesive

Table 1: Dimensions mm (inches)

Size	A	B Minimum	C Minimum	D Maximum	W Nominal
1/8	25.40 (1.000) ± 3.00 (0.125)	13.97 (0.550)	3.18 (0.125)	0.58 (0.023)	1.22 (0.048)
3/16	30.15 (1.187) ± 3.81 (0.150)	16.51 (0.650)	4.75 (0.187)	1.52 (0.060)	1.57 (0.062)
1/4	25.00 (0.984) ± 3.00 (0.125)	16.51 (0.650)	6.35 (0.250)	2.03 (0.080)	1.98 (0.078)
1/4	28.58 (1.125) ± 3.00 (0.125)	16.51 (0.650)	6.35 (0.250)	2.03 (0.080)	1.98 (0.078)
1/4	35.00 (1.378) ± 3.81 (0.150)	16.51 (0.650)	6.35 (0.250)	2.03 (0.080)	1.98 (0.078)
3/8	31.12 (1.225) ± 3.81 (0.150)	19.69 (0.775)	9.53 (0.375)	2.28 (0.090)	2.08 (0.082)
1/2	32.26 (1.270) ± 3.30 (0.130)	21.59 (0.850)	12.70 (0.500)	2.28 (0.090)	2.54 (0.100)
1/2	50.00 (1.968) ± 3.81 (0.150)	21.59 (0.850)	12.70 (0.500)	2.28 (0.090)	2.54 (0.100)

Color: Black**Specification:** Formed from semirigid, encapsulant-lined polyolefin tubing per TEC-108-120027

© 2019 TE Connectivity. All Rights Reserved.



DIMENSIONS: INCHES	DWN J. Bitter	10AUG2017	MATERIAL —	FINISH —
	CHK T. Licko	—		
TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD T. Licko	—		
	PRODUCT SPEC 108-120027	—	NAME PD-Caps Semirigid Polyolefin Heat-Shrinkable End Caps	
0 PLC ± —	APPLICATION SPEC —	—	SIZE A4	CAGE CODE 06090
1 PLC ± —	WEIGHT —	—	DRAWING NO C-PD-CAPS	RESTRICTED TO —
2 PLC ± —	CUSTOMER DRAWING			
3 PLC ± —	SCALE None			
4 PLC ± —	SHEET 1 of 1			
ANGLES ± —	REV D1			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[PD-CAP-1/2-0](#)