SAFETY ORGANIZATION(S):

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS

UL RECOGNIZED CSA CERTIFIED VDE APPROVED UL 1283 CSA 22.2, NO.0,0.4,8 VDE 565-3

OPERATING SPECIFICATIONS:

LINE VOLTAGE/CURRENT: 6 AMP, 120/250 VAC 6 AMP./40°C, 250 VAC LINE FREQUENCY, 50-60Hz

MAX. LEAKAGE CURRENT, EACH: LINE TO GROUND:

2.0 mA AT 120V 60Hz 3.0 mA at 250V 50Hz

OPERATING AMBIENT TEMP. RANGE: -10°C TO +40°C @ RATED CURRENT, I.

IN AN AMBIENT, To, HIGHER THAN 40°C, THE MAXIMUM OPERATING CURRENT, Io, IS AS FOLLOWS,

6AY01

RELIABILITY SPECIFICATIONS:

STORAGE TEMPERATURE. -40°C TO +85°C
HUMIDITY. 21 DAYS & 40°C 95% RH
CURRENT OVERLOAD TEST, 6 TIMES RATED CURRENT FOR 8 SECONDS

TEST SPECIFICATIONS:

INDUCTANCE: .45 mH NOMINAL CAPACITANCE: (MEASURED # 1 KHz, 0.25VAC MAX., 25°C±1°C) LINE TO GROUND: 15000pF ±20% LINE TO LINE: 10 µF ±20% DISCHARGE RESISTOR:1500Kp

LINE/GROUND AND LINE/LINE, 6000Mm (MIN) AT 100VDC INSULATION RESISTANCE, 20°C AND 50% RH


RECOMMENDED RECEIVING INSPECTION HIPOT:

LINES TO GROUND: LINE TO LINE:

1500 VAC FOR 1 MINUTE 1450 VDC FOR 1 MINUTE

FILTER APPROVAL:

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.



50a - 50a (MINIMUM) INSERTION LOSS												
FREQUENCY MHz	. 15	.5	1.0	5.0	10	30						
COMMON dB	7	23	30	40	50	30						
DIFF.	10	18	24	31	28	28						

3.370 MAX.-

UNLESS OTHERWISE SPECIFIED, TOLERANCE TO BE ±.025

MATERIAL & FINISH: AS SUPPLIED

This document is proprietary to CORCOM INC. and is not to be reproduced nor used for manufacturing purposes except on CORCOM'S prior written consent.



POWER LINE FILTER

DATE: 4-14-94 CATALOS NO. **6AY01** BAY01.00

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: