



- 1 PBT.
- 2 LCP.
- 3 TOLERANCE IS $+.007/- .003$ FOR 6 POSITION AND SMALLER SIZES.
- 4 VOID CORING IN THIS AREA OPTIONAL FOR MOLDING IMPROVEMENT.





DETAIL X
SCALE 6:1
(18 POSN SHOWN FOR CLARITY)



DETAIL FOR -2 ONLY
(3 POSITION)

$\frac{2}{2}$	2.595	2.520	2.400	24	25	2-103653-4
$\frac{2}{2}$	2.495	2.420	2.300	23	24	2-103653-3
$\frac{2}{2}$	2.395	2.320	2.200	22	23	2-103653-2
$\frac{2}{2}$	2.295	2.220	2.100	21	22	2-103653-1
$\frac{2}{2}$	2.195	2.120	2.000	20	21	2-103653-0
$\frac{2}{2}$	2.095	2.020	1.900	19	20	1-103653-9
$\frac{2}{2}$	1.995	1.920	1.800	18	19	1-103653-8
$\frac{2}{2}$	1.895	1.820	1.700	17	18	1-103653-7
$\frac{2}{2}$	1.795	1.720	1.600	16	17	1-103653-6
$\frac{2}{2}$	1.695	1.620	1.500	15	16	1-103653-5
$\frac{2}{2}$	1.595	1.520	1.400	14	15	1-103653-4
$\frac{2}{2}$	1.495	1.420	1.300	13	14	1-103653-3
$\frac{2}{2}$	1.395	1.320	1.200	12	13	1-103653-2
$\frac{2}{2}$	1.295	1.220	1.100	11	12	1-103653-1
$\frac{2}{2}$	1.195	1.120	1.000	10	11	1-103653-0
$\frac{2}{2}$	1.095	1.020	.900	9	10	103653-9
$\frac{2}{2}$.995	.920	.800	8	9	103653-8
$\frac{2}{2}$.895	.820	.700	7	8	103653-7
$\frac{2}{2}$.795	.720	.600	6	7	103653-6
$\frac{1}{1}$.695	.620	.500	5	6	103653-5
$\frac{1}{1}$.595	.520	.400	4	5	103653-4
$\frac{1}{1}$.495	.420	.300	3	4	103653-3
$\frac{1}{1}$.395	.320	.200	2	3	103653-2
$\frac{1}{1}$.295	.220	.100	1	2	103653-1
MATERIAL COLOR-BLACK	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R BROWN	28JUL00		 TE Connectivity	
		CHK K WRIGHT	28JUL00			
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD K WRIGHT	NAME	
		1 PLC ± -		PIN HOUSING, AMPMODU MTE, SINGLE ROW, .100 CL POLARIZED WITH LATCH		
		2 PLC ± -				
		3 PLC ± -.005				
4 PLC ± -		4.000		SIZE		
ANGLES		FINISH		CAGE CODE		
MATERIAL		WEIGHT		DRAWING NO		
SEE TABLE		—		A2 00779		
		CUSTOMER DRAWING		RESTRICTED TO		
				—		
				SCALE 4:1		
				SHEET 1 of 1		
				REV R		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-103653-9](#)