



- 1 INSERT A 1.57[.062] THICK DUMMY PC BOARD INTO CARD SLOT DURING SOLDERING PROCESS.
- 2 DATUMS AND DIMENSIONS ARE ESTABLISHED BY CUSTOMER.
- 3 PART NUMBER AND DATE CODE(OPTIONAL), LOCATED APPROXIMATELY AS SHOWN.
- 4 .400 DIMENSION REFERENCES CARD SLOT DEPTH.
- 5 HOUSING-GLASS FILLED POLYSTER, WHITE.
CONTACTS-ALLOY CDA-194.
- 6 CONTACTS-3.81µm[.000150] MIN TIN-LEAD
OVER 0.76µm[.000030] MIN NICKEL.
- 7 PIN LENGTH RECOMMENDED FOR USE WITH 3.18±0.51[.125±.020] THICK PRINTED CIRCUIT BOARD.
- 8 CONTACTS-3.81µm[.000150] MIN MATTE TIN
OVER 0.76µm[.000030] MIN NICKEL.

5-145339-1
SUPERSEDED 145339-1
PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M. MORRIS 25SEP198	TE Connectivity	
		OK C. REIFSNYDER 25SEP198		
DIMENSIONS: mm [INCHES]		APVD C. REIFSNYDER 25SEP198	NAME CONNECTOR ASSY, 5 POSITION, SELECTIVELY LOADED, HIGH CURRENT	
		TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC 108-9045	
		0 PLC ± - 1 PLC ± - 2 PLC ± 0.13[.005] 3 PLC ± - 4 PLC ± - ANGLES ± -	APPLICATION SPEC 114-9005	
MATERIAL 5	FINISH 6	WEIGHT -	SIZE A1	CAGE CODE 00779
CUSTOMER DRAWING		SCALE 4:1	SHEET 1	OF 1
		REV C		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-145339-1](#)