










REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
D1		REV PER ECO 08-006962	07JAN2008	DLD	WTW
E		REVISED PER ECR 07-030366	08JAN2008	DLD	WTW
F		REVISED PER ECO 08-006962	19MAR2008	DLD	WTW
F1		REVISED PER ECO-20-012415	10SEP2020	AP	WW



- NOTE(S):
1. APPLICABLE TERMINAL PART NUMBERS (SOLD SEPARATELY):
FOR TIN APPLICATIONS: 1393367 AND 1393366.
FOR GOLD APPLICATIONS: 1393365 AND 1393364.
FOR TERMINATION AND REELING OPTIONS
SEE DRAWINGS 1393367, 1393366, 1393365, AND 1393364.
 2. COMPATIBLE WIRE SIZES FOR MAT SEAL DESIGN 1.19 TO 2.06 O.D.
(22-18 AWG, 0.35-0.75 mm2)
 3. TPA AND CAM LEVER ARE SHIPPED IN THEIR PRE-LOADED POSITION.
ALL ASSEMBLIES ARE TO BE TRAY PACKAGED.
 - ④ CUSTOMER PART NUMBER AND TRACEABILITY CODE (YY = TWO DIGIT YEAR,
JJJ = JULIAN DAY, HH = TWO DIGIT MILITARY HOUR, A=ASSEMBLY PROCESS
USED) ARE PRINTED IN THIS LOCATION.
 5. PART ASSEMBLY WEIGHT WITHOUT TERMINALS AND WITH STANDARD PIN-OUT
CONFIGURATION IS 26.09 GRAMS.
 - ⑥ OPTIONAL WIRESHIELD P/N 8-1419157-8 (SOLD SEPARATELY). PLEASE CONTACT
YOUR TYCO ELECTRONICS SALES REPRESENTATIVE FOR AVAILABILITY AND PRICING.
 - ⑦ OBSOLETE PART

KEYING OPTION "G" SHOWN
SEE SHEET 2 FOR BILL OF MATERIALS
AND SHEET 3, 4 AND 5 FOR PIN-OUT CHARTS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. HOLT	14NOV2006	TE Connectivity	
DIMENSIONS:		CHK W. WELLINSKY	14NOV2006		
mm		APVD W. WELLINSKY	14NOV2006	NAME 40 WAY SHORTING BAR ARM PLUG ASSEMBLY WITHOUT SHORTING BARS LOADED	
		TOLERANCES UNLESS OTHERWISE SPECIFIED:		SIZE 00779	
		0 PLC ±.3 1 PLC ±0.3 2 PLC ±0.10 3 PLC ±. 4 PLC ±. ANGLES ±.3° FINISH		RESTRICTED TO	
MATERIAL SEE CHART ON SHEET 2		WEIGHT SEE NOTE 5		DRAWING NO C=1924170	
		CUSTOMER DRAWING		SCALE 3:1	
				SHEET 1 OF 5	
				REV F1	

[illegible]

8

7

6

5

4

3

2

I

© 2020 TE Connectivity. All Rights Reserved.

REVISIONS

P	LYR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

PIN OUT CHART

BLANK CAVITIES INDICATE OPEN TERMINAL HOLE POSITIONS

CAVITIES WITH A NUMERIC SYMBOL INDICATE CLOSED TERMINAL HOLE POSITIONS

TERMINAL HOLE POSITION																																				ASSEMBLY PART NUMBER	KEYING OPTION					
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40			
											11	12																												0-1924172-1	G	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18			21	22						27	28	29	30					35	36	37	38	39	40	0-1924172-2	G
			3	4	5	6	7	8	9	10	11	12	13	14	15	16																		35	36	37	38	39	40	0-1924172-3	G	
							7	8	9	10	11	12	13	14	15	16																		35	36	37	38	39	40	0-1924172-4	G	
							7	8	9	10	11	12																						35	36	37	38	39	40	0-1924172-5	G	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21	22						27	28	29	30					35	36	37	38	39	40	0-1924172-6	G
							7	8	9	10	11	12					17	18																35	36	37	38	39	40	0-1924172-7	G	
							7	8	9	10	11	12	13	14	15	16	17	18																35	36	37	38	39	40	0-1924172-8	G	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21	22						27	28	29	30					35	36	37	38	39	40	0-1924172-9	G
							7	8	9	10	11	12																						35	36	37	38	39	40	1-1924172-0	G	
							7	8	9	10	11	12	13	14	15	16																		35	36	37	38	39	40	1-1924172-1	G	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				19	20	21	22	23	24		26	27	28	29	30				35	36	37	38	39	40	1-1924172-2	G	
1	2					7	8	9	10	11	12						17	18			21	22											35	36	37	38	39	40	1-1924172-3	G		
			3	4	5	6					11	12																					35	36	37	38	39	40	1-1924172-4	G		
			3	4	5	6																										35	36	37	38	39				1-1924172-5	G	
			3	4	5	6					11	12																					35	36	37	38	39				1-1924172-6	G

PIN OUT CHART

BLANK CAVITIES INDICATE OPEN TERMINAL HOLE POSITIONS

CAVITIES WITH A NUMERIC SYMBOL INDICATE CLOSED TERMINAL HOLE POSITIONS

TERMINAL HOLE POSITION																																				ASSEMBLY PART NUMBER	KEYING OPTION						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40				
											11	12																														0-1924173-1	H
						7	8	9	10	11	12							19	20				24														37	38	39	40	0-1924173-2	H	
				5	6	7	8	9	10	11	12	13	14	15	16			19	20				24				27	28	29	30							37	38	39	40	0-1924173-3	H	
1	2	3	4					9	10	11	12	13	14	15	16					21	22						27	28	29	30									39	40	0-1924173-4	H	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21	22	23	24	25	26	27	28	29	30	31	32	33	34				37	38	39	40	0-1924173-5	H	
								9	10	11	12																											39	40	0-1924173-6	H		
						7	8	9	10	11	12													24										35	36	37	38	39	40	0-1924173-7	H		
						7	8	9	10	11	12												24																	0-1924173-8	H		
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				20	21	22					27	28	29	30	31	32						37	38	39	40	0-1924173-9	H	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21	22					27	28	29	30	31	32					37	38	39	40	1-1924173-0	H		
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21	22		24				27	28	29	30				35	36	37	38	39	40	1-1924173-1	H		
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21	22		24				27	28	29	30					37	38	39	40	1-1924173-2	H			
								9	10	11	12						17	18	19	20	21	22		24		26						33	34	35	36	37	38	39	40	1-1924173-3	H		
1	2					7	8	9	10	11	12	13	14	15	16					21	22					27	28	29	30	31	32					37	38	39	40	1-1924173-4	H		
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16		17	18			21	22				27	28	29	30				35	36	37	38	39	40	1-1924173-5	H			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21	22		24				27	28	29	30				35	36	37	38			1-1924173-6	H		
1	2					7	8	9	10	11	12	13	14	15	16					21	22		24				27	28	29	30				35	36	37	38	39	40	1-1924173-7	H		
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					21		23		25	26	27	28	29	30	31	32	33	34			37	38	39	40	1-1924173-8	H		
			3	4	5	6					11	12							19	20																	39	40	1-1924173-9	H			
			3	4	5	6					11	12							19	20																	39			2-1924173-0	H		
			3	4	5	6					11	12							19	20																	39	40	2-1924173-1	H			

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±
1 PLC ±0.3
2 PLC ±0.10
3 PLC ±
4 PLC ±
ANGLES ±3°
FINISH

MATERIAL
SEE CHART
ON SHEET 2

DWN
A. HOLT
CHK
W. WELLINSKY
APVD
W. WELLINSKY

14NOV2006
14NOV2006
14NOV2006

PRODUCT SPEC
APPLICATION SPEC

WEIGHT
SEE NOTE 5

CUSTOMER DRAWING

NAME
40 WAY SHORTING BAR ARM
PLUG ASSEMBLY
WITHOUT SHORTING BARS LOADED

SIZE
CAGE CODE
DRAWING NO
00779

RESTRICTED TO

SCALE
3:1

SHEET
5

OF
5

REV
F1

4805 (3/13)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-1924170-4](#)