



## MEAS RTD PROBE

- Variety of Configurations
- Single and Dual Elements
- Stainless Steel Case
- Custom Designs Available with:
  - » Degree Specific Case Bends
  - » Fast Response Time
  - » Cut-to-Length Cases
  - » Connector Options
  - » Special Cable or Leadwires

The RTD Probe is constructed with a Stainless Steel case. The sensing element is embedded into the tip of the sheath. With the element located in the tip of the case this is the area that needs to be in contact with the process to obtain correct temperature measurement. Fittings associated with the probe designs are related to the mounting technique required by your application. These sensors can be utilized in many different industries and applications. Probe sensors are ideal for immersion in processes.

### Features

- Sheath Styles:
  - » Stainless Steel
- Elements, Single and Dual:
  - » Platinum, Cooper, Nickel
- Sheath Diameters:
  - » 0.125", 0.188", 0.250"
- Leadwire/Cable Options

### Applications

- Process
- Aerospace
- Defense
- Hot Melt

## Dimensions



'D' = Sheath Diameter  
'L' = Sheath Length  
'Y' = Leadwire/Cable Length

## Performance Specifications

### Repeatability:

Less than  $\pm .06\%$  change in ice point resistance after 10 consecutive cycles between ice point and 250°C

### Long Term Stability:

Less than  $\pm .2\%$  ice point resistance shift after 1,000 hours at 250°C

### Self-Heating:

10 mW/C in water moving 3 feet/sec

### Pressure Rating:

1,500 psi

### Insulation Resistance:

1,000 megohms @ 500 V, leads to case

### Vibration:

Withstands 5 to 500 Hz at 3 g-level peak for 3 hours. Per ASTM E 644, Sec. 10.

### Shock:

Withstands 50 g-level peak sine wave shock of 11 milliseconds duration. Per ASTM E 644, Sec. 11

### RTD TEMPERATURE ACCURACY SPECIFICATIONS:

Element Material	TCR	Standard Tolerances at 0°C			
		$\pm .06\%$	$\pm .12\%$	$\pm .2\%$	$\pm .5\%$
Platinum	0.00385	0.15°C, 0.06Ω	0.30°C, 0.12Ω	0.50°C, 0.19Ω	1.20°C, 0.46Ω
Platinum	0.00392	N/A	N/A	N/A	1.20°C, 0.46Ω
Copper	0.00427	N/A	N/A	0.71°C, 0.028Ω	1.49°C, 0.058Ω
Nickel	0.00672	N/A	N/A	N/A	0.85°C, 0.68Ω

## Ordering Information

RTD PROBE			
Model	Temperature Range		
100M	Moderate: -50 to 250°C (-58 to 482°F)		
100H	High: -50 to 500°C (-58 to 932°F)		
100F	Full: -200 to 500°C (-328 to 932°F)		
Model	Element	Accuracy	Temperature Coefficient
P2A	Platinum	100 Ohm $\pm$ .06% at 0°C	.00385
P2B	Platinum	100 Ohm $\pm$ .12% at 0°C	.00385
P2C	Platinum	100 Ohm $\pm$ .5% at 0°C	.00385
P6B	Platinum	1,000 Ohm $\pm$ .12% at 0°C	.00385
G2C	Platinum	100 Ohm $\pm$ .5% at 0°C	.00392
C1D	Copper	10 Ohm $\pm$ .2% at 25°C	.00427 (Model 100 M Only)
N3C	Nickel	120 Ohm $\pm$ .5% at 0°C	.00672 (Model 100 M Only)
Model	Leadwires, Element Configuration		Typical Color Code
3S	Three Wire, Single		Red/Red/White
3D	Three Wire, Dual		Red/Red/White // Black/Green/Green
4S	Four Wire, Single		Red/Red/White/White
4D	Four Wire, Dual		Red/Red/White/White // Black/Black/Green/Green
Model	'L' Sheath Length		
---	Define 'L' Length in Inches Note: Minimum 1.5" / Maximum 96.0" Example: (12.0 = 12.0"; 28.5 = 28.5")		
Model	'D' Sheath Diameter		
A	.125" Diameter (Single Element Only)		
B	.188" Diameter		
C	.250" Diameter		
Model	'Y' Leadwire/Cable Options		
N	No Options, Stranded TFE Leadwires (36.0" Standard)		
W	Leadwire Options		

### NORTH AMERICA

Measurement Specialties, Inc.,  
a TE Connectivity Company  
Tel: 800-522-6752  
[customercare.ando@te.com](mailto:customercare.ando@te.com)

### EUROPE

Measurement Specialties (Europe), Ltd.,  
a TE Connectivity Company  
Tel: 800-440-5100  
[customercare.tlse@te.com](mailto:customercare.tlse@te.com)

### ASIA

Measurement Specialties (China), Ltd.,  
a TE Connectivity Company  
Tel: 0400-820-6015  
[customercare.chdu@te.com](mailto:customercare.chdu@te.com)

### te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[20009209-00](#)