



## Stability

Typical Thermometric Drift

| Operating<br>Temperature | 10 months | 100 months |
|--------------------------|-----------|------------|
| 25°C                     | < 0.01°C  | < 0.01°C   |
| 70°C                     | < 0.01°C  | < 0.01°C   |
| 100°C                    | 0.02°C    | 0.03°C     |
| 150°C                    | 0.05°C    | 0.08°C     |
| 200°C                    | 0.22°C    | 0.60°C     |

## **46000 SERIES**

## **Thermistor Components**

Hermetically Sealed Glass Encapsulated Precision Interchangeable NTC Thermistor utilizing high stability pressed-disk ceramic sensor for high temperature and high stability applications

## Features

- Glass Hermetic Seal
- $\bullet$  2252 Ohm to 30K Ohm Resistance @ 25°C
- 0.095" (2.4 mm) Maximum Diameter
- Interchangeability up to ±0.1°C from 0°C to 70°C
- Excellent High Temperature Performance
- Drift Certified Unmatched Long Term Stability
- High Sensitivity
- RoHS Compliance

## **Applications**

- High Moisture Applications
- Low to Mid Range Temperature Applications
- Tight Tolerance Instrumentation
- Exposure up to 200°C
- Applications Requiring Outstanding Stability and/or Requiring Sensing Small Changes in Temperature
- Allows use in Applications World-wide

## **Performance Specifications**

|   | Model<br>Number | Ordering Part<br>Number | Zero Power<br>Resistance<br>ohm at 25°C | Beta<br>0- 50°C (K) | Ratio Ohm<br>25/125°C | Maximum<br>Working<br>Temperature |
|---|-----------------|-------------------------|---|---------------------|-----------------------|-----------------------------------|
| ±0.2°C<br>Interchange                                       | 46004           | 069154                  | 2252                                    | 3891                | 29.26                 | 200°C                             |
|   | 46005           | 065437                  | 3000                                    | 3891                | 29.26                 | 200°C                             |
|   | 46007           | 065439                  | 5000                                    | 3891                | 29.26                 | 200°C                             |
| - ability<br>Tolerance                                      | 46017           | 091688                  | 6000                                    | 3891                | 29.26                 | 200°C                             |
| 0 – 70°C  | 46016           | 091687                  | 10K                                     | 3891                | 29.26                 | 200°C                             |
|   | 46006           | 065438                  | 10K                                     | 3574                | 23.51                 | 200°C                             |
|   | 46008           | 091162                  | 30K                                     | 3810                | 29.15                 | 200°C                             |
| ±0.1°C<br>Interchange<br>- ability<br>Tolerance<br>0 – 70°C | 46033           | 069158                  | 2252                                    | 3891                | 29.26                 | 200°C                             |
|   | 46030           | 065440                  | 3000                                    | 3891                | 29.26                 | 200°C                             |
|   | 46034           | 065442                  | 5000                                    | 3891                | 29.26                 | 200°C                             |
|   | 46037           | 091690                  | 6000                                    | 3891                | 29.26                 | 200°C                             |
|   | 46036           | 091689                  | 10K                                     | 3891                | 29.26                 | 200°C                             |
|   | 46031           | 065441                  | 10K                                     | 3574                | 23.51                 | 200°C                             |
|   | 46032           | 091163                  | 30K                                     | 3810                | 29.15                 | 200°C                             |

#### **NORTH AMERICA**

Measurement Specialties, Inc.,

a TE Connectivity Company

Tel: 800-522-6752

### customercare.ando@te.com

#### EUROPE

Measurement Specialties (Europe), Ltd., a TE Connectivity Company Tel: 800-440-5100

customercare.tlse@te.com

#### ASIA

Measurement Specialties (China), Ltd., a TE Connectivity Company Tel: 0400-820-6015 customercare.chdu@te.com

#### te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties (MEAS), American Sensor Technologies (AST), TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.



# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

11028337-00