

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC  
J

DIST  
/

REVISIONS  
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L2	REVISED(ECR-14-018055)	17MAR2015	W.C	V.P

14

2.1

2.9

3.7

4.9

0.8 ±0.1

2.5 TYP

ピッチ PITCH

A

B

C

2

回路番号  
CIRCUIT NO.

5.8

4

3~12極  
POS

2.9

2.1

3.7

4.9

0.8 ±0.1

2.5 PITCH

5.6

0.8 ±0.1

5.3

6.9

1.5

回路番号  
CIRCUIT NO.

4

6.7

2極  
POS

1 使用するコンタクトは 170262 又は 170263.  
2 ロッキング凸部位置は長手方向の中央.

1 CONTACTS, 170262 & 170263 ARE USED.  
2 LOCKING PROTRUSION IS PLACED ON THE CENTER OF HOUSING.

OBSOLETE	39.4	37.8	38.1	15	9-171822-5	7-171822-5
	36.9	35.3	35.6	14	9-4	7-4
	34.4	32.8	33.1	13	9-3	7-3
	29.4	27.8	28.1	11	9-1	7-1
	31.9	30.3	30.6	12	9-2	7-2
	26.9	25.3	25.6	10	9-0	7-0
	24.4	22.8	23.1	9	8-9	6-9
	21.9	20.3	20.6	8	8-8	6-8
	19.4	17.8	18.1	7	8-7	6-7
	16.9	15.3	15.6	6	8-6	6-6
	14.4	12.8	13.1	5	8-5	6-5
	11.9	10.3	10.6	4	8-4	6-4
	9.4	7.8	8.1	3	8-3	6-3
-図示-	SHOWN			2	8-171822-2	6-171822-2
C	B	A	極数 (POS)	赤色 (RED) 緑色 (GREEN)		
OBSOLETE	39.4	37.8	38.1	15	5-171822-5	3-171822-5
	36.9	35.3	35.6	14	5-4	3-4
	34.4	32.8	33.1	13	5-3	3-3
	29.4	27.8	28.1	11	5-1	3-1
	31.9	30.3	30.6	12	5-2	3-2
	26.9	25.3	25.6	10	5-0	3-0
	24.4	22.8	23.1	9	4-9	2-9
	21.9	20.3	20.6	8	4-8	2-8
	19.4	17.8	18.1	7	4-7	2-7
	16.9	15.3	15.6	6	4-6	2-6
	14.4	12.8	13.1	5	4-5	2-5
	11.9	10.3	10.6	4	4-4	2-4
	9.4	7.8	8.1	3	4-3	2-3
-図示-	SHOWN			2	4-171822-2	2-171822-2
C	B	A	極数 (POS)	青色 (BLUE) 黒色 (BLACK) 自然色 (NATURAL)		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:  
一般公差

0 PLC ± -  
1 PLC ± -  
2 PLC ± -  
3 PLC ± -  
4 PLC ± -  
ANGLES ± -  
FINISH  
仕上

MATERIAL  
材料  
66 NYLON  
(UL94-0)

GENERAL TOLERANCE  
一般公差

10 ≥ : ±0.2  
30 ≥ > 10: ±0.25  
100 ≥ > 30: ±0.3  
ANGLES: ±3°

THIS DRAWING IS UNPUBLISHED.  
RELEASED FOR PUBLICATION  
ALL RIGHTS RESERVED.

LOC  
J

DIST  
/

REVISIONS  
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L2	REVISED(ECR-14-018055)	17MAR2015	W.C	V.P

回路番号  
CIRCUIT NO.

5.8

4

3~12極  
POS

回路番号  
CIRCUIT NO.

4

6.7

2極  
POS

1 使用するコンタクトは 170262 又は 170263.  
2 ロッキング凸部位置は長手方向の中央.

1 CONTACTS, 170262 & 170263 ARE USED.  
2 LOCKING PROTRUSION IS PLACED ON THE CENTER OF HOUSING.

OBSOLETE	39.4	37.8	38.1	15	9-171822-5	7-171822-5
	36.9	35.3	35.6	14	9-4	7-4
	34.4	32.8	33.1	13	9-3	7-3
	29.4	27.8	28.1	11	9-1	7-1
	31.9	30.3	30.6	12	9-2	7-2
	26.9	25.3	25.6	10	9-0	7-0
	24.4	22.8	23.1	9	8-9	6-9
	21.9	20.3	20.6	8	8-8	6-8
	19.4	17.8	18.1	7	8-7	6-7
	16.9	15.3	15.6	6	8-6	6-6
	14.4	12.8	13.1	5	8-5	6-5
	11.9	10.3	10.6	4	8-4	6-4
	9.4	7.8	8.1	3	8-3	6-3
-図示-	SHOWN			2	8-171822-2	6-171822-2
C	B	A	極数 (POS)	赤色 (RED) 緑色 (GREEN)		
OBSOLETE	39.4	37.8	38.1	15	5-171822-5	3-171822-5
	36.9	35.3	35.6	14	5-4	3-4
	34.4	32.8	33.1	13	5-3	3-3
	29.4	27.8	28.1	11	5-1	3-1
	31.9	30.3	30.6	12	5-2	3-2
	26.9	25.3	25.6	10	5-0	3-0
	24.4	22.8	23.1	9	4-9	2-9
	21.9	20.3	20.6	8	4-8	2-8
	19.4	17.8	18.1	7	4-7	2-7
	16.9	15.3	15.6	6	4-6	2-6
	14.4	12.8	13.1	5	4-5	2-5
	11.9	10.3	10.6	4	4-4	2-4
	9.4	7.8	8.1	3	4-3	2-3
-図示-	SHOWN			2	4-171822-2	2-171822-2
C	B	A	極数 (POS)	青色 (BLUE) 黒色 (BLACK) 自然色 (NATURAL)		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:  
一般公差

0 PLC ± -  
1 PLC ± -  
2 PLC ± -  
3 PLC ± -  
4 PLC ± -  
ANGLES ± -  
FINISH  
仕上

MATERIAL  
材料  
66 NYLON  
(UL94-0)

GENERAL TOLERANCE  
一般公差

10 ≥ : ±0.2  
30 ≥ > 10: ±0.25  
100 ≥ > 30: ±0.3  
ANGLES: ±3°

THIS DRAWING IS UNPUBLISHED.  
RELEASED FOR PUBLICATION  
ALL RIGHTS RESERVED.

LOC  
J

DIST  
/

REVISIONS  
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L2	REVISED(ECR-14-018055)	17MAR2015	W.C	V.P

回路番号  
CIRCUIT NO.

5.8

4

3~12極  
POS

回路番号  
CIRCUIT NO.

4

6.7

2極  
POS

1 使用するコンタクトは 170262 又は 170263.  
2 ロッキング凸部位置は長手方向の中央.

1 CONTACTS, 170262 & 170263 ARE USED.  
2 LOCKING PROTRUSION IS PLACED ON THE CENTER OF HOUSING.

OBSOLETE	39.4	37.8	38.1	15	9-171822-5	7-171822-5
	36.9	35.3	35.6	14	9-4	7-4
	34.4	32.8	33.1	13	9-3	7-3
	29.4	27.8	28.1	11	9-1	7-1
	31.9	30.3	30.6	12	9-2	7-2
	26.9	25.3	25.6	10	9-0	7-0
	24.4	22.8	23.1	9	8-9	6-9
	21.9	20.3	20.6	8	8-8	6-8
	19.4	17.8	18.1	7	8-7	6-7
	16.9	15.3	15.6	6	8-6	6-6
	14.4	12.8	13.1	5	8-5	6-5
	11.9	10.3	10.6	4	8-4	6-4
	9.4	7.8	8.1	3	8-3	6-3
-図示-	SHOWN			2	8-171822-2	6-171822-2
C	B	A	極数 (POS)	赤色 (RED) 緑色 (GREEN)		
OBSOLETE	39.4	37.8	38.1	15	5-171822-5	3-171822-5
	36.9	35.3	35.6	14	5-4	3-4
	34.4	32.8	33.1	13	5-3	3-3
	29.4	27.8	28.1	11	5-1	3-1
	31.9	30.3	30.6	12	5-2	3-2
	26.9	25.3	25.6	10	5-0	3-0
	24.4	22.8	23.1	9	4-9	2-9
	21.9	20.3	20.6	8	4-8	2-8
	19.4	17.8	18.1	7	4-7	2-7
	16.9	15.3	15.6	6	4-6	2-6
	14.4	12.8	13.1	5	4-5	2-5
	11.9	10.3	10.6	4	4-4	2-4
	9.4	7.8	8.1	3	4-3	2-3
-図示-	SHOWN			2	4-171822-2	2-171822-2
C	B	A	極数 (POS)	青色 (BLUE) 黒色 (BLACK) 自然色 (NATURAL)		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:  
一般公差

0 PLC ± -  
1 PLC ± -  
2 PLC ± -  
3 PLC ± -  
4 PLC ± -  
ANGLES ± -  
FINISH  
仕上

MATERIAL  
材料  
66 NYLON  
(UL94-0)

GENERAL TOLERANCE  
一般公差

10 ≥ : ±0.2  
30 ≥ > 10: ±0.25  
100 ≥ > 30: ±0.3  
ANGLES: ±3°

THIS DRAWING IS UNPUBLISHED.  
RELEASED FOR PUBLICATION  
ALL RIGHTS RESERVED.

LOC  
J

DIST  
/

REVISIONS  
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L2	REVISED(ECR-14-018055)	17MAR2015	W.C	V.P

回路番号  
CIRCUIT NO.

5.8

4

3~12極  
POS

回路番号  
CIRCUIT NO.

4

6.7

2極  
POS

1 使用するコンタクトは 170262 又は 170263.  
2 ロッキング凸部位置は長手方向の中央.

1 CONTACTS, 170262 & 170263 ARE USED.  
2 LOCKING PROTRUSION IS PLACED ON THE CENTER OF HOUSING.

OBSOLETE	39.4	37.8	38.1	15	9-171822-5	7-171822-5
	36.9	35.3	35.6	14	9-4	7-4
	34.4	32.8	33.1	13	9-3	7-3
	29.4	27.8	28.1	11	9-1	7-1
	31.9	30.3	30.6	12	9-2	7-2
	26.9	25.3	25.6	10	9-0	7-0
	24.4	22.8	23.1	9	8-9	6-9
	21.9	20.3	20.6	8	8-8	6-8
	19.4	17.8	18.1	7	8-7	6-7
	16.9	15.3	15.6	6	8-6	6-6
	14.4	12.8	13.1	5	8-5	6-5
	11.9	10.3	10.6	4	8-4	6-4
	9.4	7.8	8.1	3	8-3	6-3
-図示-	SHOWN			2	8-171822-2	6-171822-2
C	B	A	極数 (POS)	赤色 (RED) 緑色 (GREEN)		
OBSOLETE	39.4	37.8	38.1	15	5-171822-5	3-171822-5
	36.9	35.3	35.6	14	5-4	3-4
	34.4	32.8	33.1	13	5-3	3-3
	29.4	27.8	28.1	11	5-1	3-1
	31.9	30.3	30.6	12	5-2	3-2
	26.9	25.3	25.6	10	5-0	3-0
	24.4	22.8	23.1	9	4-9	2-9
	21.9	20.3	20.6	8	4-8	2-8
	19.4	17.8	18.1	7	4-7	2-7
	16.9	15.3	15.6	6	4-6	2-6
	14.4	12.8	13.1	5	4-5	2-5
	11.9	10.3	10.6	4	4-4	2-4
	9.4	7.8	8.1	3	4-3	2-3
-図示-	SHOWN			2	4-171822-2	2-171822-2
C	B	A	極数 (POS)	青色 (BLUE) 黒色 (BLACK) 自然色 (NATURAL)		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:  
一般公差

0 PLC ± -  
1 PLC ± -  
2 PLC ± -  
3 PLC ± -  
4 PLC ± -  
ANGLES ± -  
FINISH  
仕上

MATERIAL  
材料  
66 NYLON  
(UL94-0)

GENERAL TOLERANCE  
一般公差

10 ≥ : ±0.2  
30 ≥ > 10: ±0.25  
100 ≥ > 30: ±0.3  
ANGLES: ±3°

THIS DRAWING IS UNPUBLISHED.  
RELEASED FOR PUBLICATION  
ALL RIGHTS RESERVED.

LOC  
J

DIST  
/

REVISIONS  
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L2	REVISED(ECR-14-018055)	17MAR2015	W.C	V.P

回路番号  
CIRCUIT NO.

5.8

4

3~12極  
POS

回路番号  
CIRCUIT NO.

4

6.7

2極  
POS

1 使用するコンタクトは 170262 又は 170263.  
2 ロッキング凸部位置は長手方向の中央.

1 CONTACTS, 170262 & 170263 ARE USED.  
2 LOCKING PROTRUSION IS PLACED ON THE CENTER OF HOUSING.

OBSOLETE	39.4	37.8	38.1	15	9-171822-5	7-171822-5
	36.9	35.3	35.6	14	9-4	7-4
	34.4	32.8	33.1	13	9-3	7-3
	29.4	27.8	28.1	11	9-1	7-1
	31.9	30.3	30.6	12	9-2	7-2
	26.9	25.3	25.6	10	9-0	7-0
	24.4	22.8	23.1	9	8-9	6-9
	21.9	20.3	20.6	8	8-8	6-8
	19.4	17.8	18.1	7	8-7	6-7
	16.9	15.3	15.6	6	8-6	6-6
	14.4	12.8	13.1	5	8-5	6-5
	11.9	10.3	10.6	4	8-4	6-4
	9.4	7.8	8.1	3	8-3	6-3
-図示-	SHOWN			2	8-171822-2	6-171822-2
C	B	A	極数 (POS)	赤色 (RED) 緑色 (GREEN)		
OBSOLETE	39.4	37.8	38.1	15	5-171822-5	3-171822-5
	36.9	35.3	35.6	14	5-4	3-4
	34.4	32.8	33.1	13	5-3	3-3
	29.4	27.8	28.1	11	5-1	3-1
	31.9	30.3	30.6	12	5-2	3-2
	26.9	25.3	25.6	10	5-0	3-0
	24.4	22.8	23.1	9	4-9	2-9
	21.9	20.3	20.6	8	4-8	2-8
	19.4	17.8	18.1	7	4-7	2-7
	16.9	15.3	15.6	6	4-6	2-6
	14.4	12.8	13.1	5	4-5	2-5
	11.9	10.3	10.6	4	4-4	2-4
	9.4	7.8	8.1	3	4-3	2-3
-図示-	SHOWN			2	4-171822-2	2-171822-2
C	B	A	極数 (POS)	青色 (BLUE) 黒色 (BLACK) 自然色 (NATURAL)		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:  
一般公差

0 PLC ± -  
1 PLC ± -  
2 PLC ± -  
3 PLC ± -  
4 PLC ± -  
ANGLES ± -  
FINISH  
仕上

MATERIAL  
材料  
66 NYLON  
(UL94-0)

GENERAL TOLERANCE  
一般公差

10 ≥ : ±0.2  
30 ≥ > 10: ±0.25  
100 ≥ > 30: ±0.3  
ANGLES: ±3°

THIS DRAWING IS UNPUBLISHED.  
RELEASED FOR PUBLICATION  
ALL RIGHTS RESERVED.

LOC  
J

DIST  
/

REVISIONS  
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L2	REVISED(ECR-14-018055			

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[171822-8](#)