

	PH BRZ	TIN	NYLON,	UL	V-0 G	W, NATURAL	190	69811-	— 1
	CONTA	СТ	DUSING			PART NO			
THIS DRAWING IS A CO	DWN 07JAN2016 BASVESH WARAD CHK 07JAN2016		-	-	<b>TE</b>	TE Conr	ectivity		
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ±	WICKES EVAN APVD 07jan2016 WICKES EVAN PRODUCT SPEC		NAME			JNIVERSAL MATE-N-LOK (TM) D SOCKET HEADER ASSEMBLY		
	2 PLC ± 3 PLC ± 0.13 [.005] 4 PLC ± ANGLES ± FINISH	APPLICATION SPEC		SIZE	CAGE CODE	DRAWING NO		F	RESTRICTED TO
SEE TABLE	SEE TABLE	WEIGHT 0.0	AL	00779	<b>C-</b> 1969811				
		CUSTOMER DRAWING				SCALE 5	:1 SHEET	0F 1 1	REV A 1

В

				2				1				
					REVISIONS							
				-	P LT	R [	DESCRIPTION	DATE	DWN	APVD		
				Ī	A	REVISED PER ECR-1	7-012945	21SEP2017	JB	SD		
					A	REVISED PER ECR-1	7-012945	21SEP2017	JB			
1	PARTS	MUST	COMPLY	WITH	AMP	SOLDERABLITY	SPFC 109-11-	3.				

2 circuit identification characters are adjacent to the indicated cavities, but location and orientation may differ from print.

3 FLAMMABILITY UL V-0 FOR THICKNESS 0.4, 0.45, 0.8, 1.6, AND 3.0 PER IEC 60695-11-10.

4 GLOW WIRE FLAMMABILITY (GWFI): 960°C FOR THICKNESS 0.45, 0.8, 1.6, AND 3.0 PER IEC 60695-2-12.

5 GLOW WIRE IGNITION (GWIT): 825°C FOR THICKNESS 0.45, 800°C FOR THICKNESS 0.8, 775°C FOR THICKNESS 1.6 AND 3.0 PER IEC 60695–2–13.

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1969811-1</u>