


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00		A	RELEASE	02NOV2016	JY	SH
			B	REVISED PER ECO-20-012918	1AUG2020	JW	SH

D


D





1. COMPONENTS
CAGE ASSEMBLY: NICKEL-SILVER ALLOY
HEAT SINK: ALUMINUM/BLACK ANODIZE
HEAT SINK CLIP: STAINLESS STEEL
EMI SPRING: COPPER ALLOY/NICKEL PLATE
LIGHT PIPE: CLEAR POLYCARBONATE WITH UL 94 V-0
ORGANIZER: POLYESTER WITH UL 94 V-0
2. REFERENCE APPLICATION SPECIFICATION 114-32023
FOR RECOMMENDED DRILL HOLE DIAMETER AND
PLATING THICKNESS
3. DATUM AND BASIC DIMENSION ESTABLISHED BY CUSTOMER
4. DIMENSION APPLIES WITH MODULE INSERTED IN CAGE
5. HEAT SINKS, HEAT SINK CLIPS AND LIGHT PIPES
ARE SHIPPED ASSEMBLED ON CAGE
6. MINIMUM PC BOARD THICKNESS: SINGLE SIDED: 1.57 MIN
DOUBLE SIDED: 2.20 MIN
7. DATUM -A- IS TOP SURFACE OF THE HOST BOARD.
8. THESE HOLES ARE OPTIONAL WHEN THE REAR PINS ARE REMOVED.
9. MATES WITH QSFP28 MSA COMPATIBLE TRANSCEIVER.
10. DATE CODE (YYWWD) MARKED APPROXIMATELY AS SHOWN.


C

C



SCALE 2:1




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN JASON YANG 24OCT2013		 TE Connectivity				
		CHK SEAN HAN 02NOV2016						
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD -	-	NAME CAGE ASSEMBLY, 1X6, QSFP28 WITH HEAT SINKS AND LIGHT PIPES, THRU BEZEL, EMI SPRING				
		PRODUCT SPEC 108-19428						
	0 PLC ±.	APPLICATION SPEC 114-32023		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO -	
	1 PLC ±0.25	WEIGHT -		A200779	C-2170708			
MATERIAL	FINISH	CUSTOMER DRAWING			SCALE	SHEET	OF	REV
SEE NOTES	SEE NOTES				1:1	1	9	B

A


A

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
			-	SEE SHEET 1	-	-	-


HEAT SINK OPTION



PCI HEAT SINK
SCALE 1:1




SAN HEAT SINK
SCALE 1:1




NETWORKING
SCALE 1:1


LIGHT PIPE OPTION



SINGLE LIGHT PIPE
SCALE 1:1




DUAL LIGHT PIPE
SCALE 1:1




QUAD LIGHT PIPE
SCALE 1:1

OF REAR LEGS OPTIONS



1 REAR LEGS
SCALE 2:1



0 REAR LEGS
SCALE 2:1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±0.25
2 PLC ±0.2
3 PLC ±
4 PLC ±
ANGLES ±
FINISH

MATERIAL
SEE NOTES
material_2

SEE NOTES
finish_spec_2

DWN
JASON YANG
24OCT2013

CHK
SEAN HAN
02NOV2016

APVD

PRODUCT SPEC
108-19428

APPLICATION SPEC
114-32023

WEIGHT

CUSTOMER DRAWING

SCALE 3:1

SHEET 2 OF 9

REV B


TE Connectivity

CAGE ASSEMBLY, 1X6, QSFP28 WITH HEAT SINKS AND LIGHT PIPES, THRU BEZEL, EMI SPRING



SIZE A2
CAGE CODE 00779
DRAWING NO. C-2170708

RESTRICTED TO


5-2170708-5 UNMARKED DIMENIONS SAME AS 2170708-1



SCALE 3:2



5-2170708-5
SCALE 1:1



0	16	FIN TYPE , SAN	SINGLE	5-2170708-5
1	14.9	CUSTOMER SPECIFIC	QUAD	4-2170708-7
0	23.0	NETWORKING	QUAD	4-2170708-6
0	16.0	SAN	QUAD	4-2170708-5
0	13.7	PCI	QUAD	4-2170708-4
1	23.0	NETWORKING	QUAD	4-2170708-3
1	16.0	SAN	QUAD	4-2170708-2
1	13.7	PCI	QUAD	4-2170708-1
0	16.5	CUSTOMIZED	DUAL	2-2170708-7
0	23.0	NETWORKING	DUAL	2-2170708-6
0	16.0	SAN	DUAL	2-2170708-5
0	13.7	PCI	DUAL	2-2170708-4
1	23.0	NETWORKING	DUAL	2-2170708-3
1	16.0	SAN	DUAL	2-2170708-2
1	13.7	PCI	DUAL	2-2170708-1
1	14.9	CUSTOMER SPECIFIC	SINGLE	1-2170708-1
0	23.0	NETWORKING	SINGLE	2170708-6
0	16.0	SAN	SINGLE	2170708-5
0	13.7	PCI	SINGLE	2170708-4
1	23.0	NETWORKING	SINGLE	2170708-3
1	16.0	SAN	SINGLE	2170708-2
1	13.7	PCI	SINGLE	2170708-1
# OF REAR PIN	DIM A	APPLICATION	LIGHT PIPE OPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

MATERIAL

SEE NOTES material_2

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±-

1 PLC ±0.25

2 PLC ±0.2

3 PLC ±-

4 PLC ±-

ANGLES ±-

FINISH

SEE NOTES finish_spec_2

DWN 24OCT2013 JASON YANG

CHK 02NOV2016 SEAN HAN

APVD -

PRODUCT SPEC 108-19428

APPLICATION SPEC 114-32023

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME

CAGE ASSEMBLY, 1X6, QSFP28 WITH HEAT SINKS AND LIGHT PIPES, THRU BEZEL, EMI SPRING

SIZE

A200779

CAGE CODE

C-2170708

DRAWING NO

C-2170708

RESTRICTED TO

-

SCALE


3:1


SHEET


3 OF 9

REV


B







THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		20		LOC		DIST		REVISIONS					
© COPYRIGHT 20		BY -		ALL RIGHTS RESERVED.						P	LTR	DESCRIPTION	DATE	DWN	APVD
										-	-	SEE SHEET 1	-	-	-



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
			-	SEE SHEET 1	-	-	-

D

D

C


C

B


B

A


A



P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-



DETAIL D
SCALE 3:1



DETAIL E
SCALE 6:1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 24OCT2013 JASON YANG CHK 02NOV2016 SEAN HAN		 TE Connectivity	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC $\pm$ 1 PLC ± 0.25 2 PLC ± 0.2 3 PLC $\pm$ 4 PLC $\pm$ ANGLES $\pm$		NAME CAGE ASSEMBLY, 1X6, QSFP28 WITH HEAT SINKS AND LIGHT PIPES, THRU BEZEL, EMI SPRING	
		PRODUCT SPEC 108-19428 APPLICATION SPEC 114-32023		SIZE A2	
MATERIAL SEE NOTES material-2		FINISH SEE NOTES finish_spec-2		DRAWING NO C-2170708	
		WEIGHT -		RESTRICTED TO -	
CUSTOMER DRAWING				SCALE 3:1	SHEET 9 of 9
				REV B	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[4-2170708-4](#)