

I				
REVISIONS				
DESCRIPTION	DATE	DWN	APVD	
0-11-004820	11MAR11	RK	HMR	
0-17-007400	21NOV2017	RS	DR	D
AMP 16-14*, APPROX AS SHOWN.				
OM EDGE OF METAL WIRE CENTER OF STUD HOLE.				
RIAL THK IS 0.787±0.051[.031±.002]				
PHOS BRONZE PER ASTM B-103 - COPPER PER ASTM B-152 ON - NYLON				
TIN PLATE PER ASTM B545 – TIN PLATE PER ASTM B545 ION – COLOR – BLUE				С
Listed FILE E13288	LR7189 Certified			
16–14 AWG SOLID OR STRANDED S	16–14 AWG SOLID OR STRANDED			<u> </u>
) LOOSE PIECE, BOX	7 50	075	1	
	7-52935-1			
) -2 ON TAPE 52935-3			3	В
) LOOSE PIECE 52935-2		2		
0 –1 ON TAPE	52935-1			
LOOSE PIECE 52935				
PACKAGE TYPE PART NO			C	
ETE TE Connectivity				
TERMINAL, SHORT SPRING SPADE, PIDG, WIRE SIZE: 16-14 AWG				А
AGE CODE DRAWING NO RESTRICTED TO 0779 C=52935 -				
SCALE 6:1	ет 1 оғ 1	RE	′L3	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 52935-3