

4

THIS DRAWING IS UNPUBLISHED.

3

RELEASED FOR PUBLICATION

2

1

© COPYRIGHT — TE Connectivity Ltd.

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	28OCT2019	RV	MB

General Specifications

Temperature Rating —  
-70°C TO + 125°C

Altitude — 300,000 Feet

Shock\* —  
Z & Y Enclosures —  
200 g for 6 mS  
W, X & M Enclosures —  
100 g for 6 mS  
T Enclosure (In Track) —  
50 g for 11 mS

Vibration, Sinusoidal\* —  
Z & Y Enclosures —  
30 g 70-3000Hz  
W, X & M Enclosures —  
20 g 70-3000Hz  
T Enclosure (Socket Mounted in Track) —  
20 g 500-3000 Hz

Vibration, Random\* —  
Z & Y Enclosures —  
0.4 g²/Hz 50-2000Hz  
T, W, X & M Enclosures —  
0.2 g²/Hz 50-2000Hz

Dielectric Strength —  
At Sea Level —  
All circuits to ground and circuit to  
circuit — 1000 V rms  
Coil to ground — 1000 V rms  
At 80,000 Feet — 250 V rms

Insulation Resistance —  
Initial (500 VDC) — 100 MΩ Min.  
After Life or Environmental Tests —  
50 MΩ Min.

Operate Time at Nominal  
Voltage — 6 ms or less

Release Time at Nominal  
Voltage — 6 ms or less

\* Max. contact opening under vibration  
or shock 10 microseconds

Coil Data

Coil Code	Nominal Voltages	Freq. Hz	DC Res. (B)	Over Temperature Range		
				Pickup or Below Volts	Dropout or Above Volts	Must Hold Voltage (C)
1	6	DC	25 Ω	4.5	0.3	2.5
2	12	DC	78 Ω	9.0	0.75	4.5
3	28	DC	400 Ω	18.0	1.5	7.0
4 (A)	28	DC	400 Ω	18.0	1.5	7.0
5	48	DC	1275 Ω	36.0	2.5	14.0

A. CODE 4 COILS HAVE BACK EMF SUPPRESSION TO 42 VOLTS MAX.  
B. DC COIL RESISTANCE ± 10% AT 25°C  
C. RELAY WILL STAY IN PICKED-UP STATE DOWN TO MUST HOLD VOLTAGES SHOWN.  
D. MAX. OVERVOLTAGE: 6 & 12 VDC COILS 120% OF NOMINAL; ALL OTHERS 110% OF NOMINAL.

Contact Rating — Amperes  
Ratings Are Continuous Duty

Type of Load	Life (Min.) Cycles x 10³	28 VDC	115VAC 400Hz	115/200VAC 400Hz-3Ø
Resistive	100	5	5	5
Inductive	20	3	5	5
Motor	100	2	3	3
Lamp	100	1	1	1

Low Level Switching Capability: With contacts operating a load of 10 to 50 microamperes at 10 to 50 millivolts, the contact resistance miss detection level shall be 100 ohms max. Cycling rate is 1 to 12 per second, for 100,000 operations.

Overload Current — 20 AMPS DC, 30 AMPS 400Hz

Rupture Current — 25 AMPS DC, 40 AMPS 400Hz

Contact Make Bounce —1.0 MILLISECOND AT NOMINAL VOLTAGE

Max. Contact Drop at 5 Amps — INITIAL 0.100 VOLTS

End of Life — 0.125 VOLTS

Image of FCB-405 relay

Product Facts

■ Hermetically Sealed

■ All Welded Construction

■ Balanced Force

■ Permanent Magnet Drive

■ Contacts rated low level to 5 Amps 28 VDC and 115/200 VAC 400 Hz, 3 Phase

■ Weight .93 ounces max. (26.4 grams)

■ Qualified to M83536/5 & /6

increased contact pressure in both states over that of a spring return nonpolar design. We also manufacture other versions of this relay:

FCB-205 — 5 Amp DPDT Relay

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
INCHES

0 PLC ± —

1 PLC ± —

2 PLC ± —

3 PLC ± —

4 PLC ± —

ANGLES ± —

MATERIAL —

FINISH —

DWN RV 28OCT2019

CHK RV 28OCT2019

APVD MB 28OCT2019

PRODUCT SPEC —

APPLICATION SPEC —

WEIGHT —

CUSTOMER DRAWING

TE Connectivity

NAME C-FCB-405-SERIES

—

—

SIZE A3

CAGE CODE —

DRAWING NO C-FCB-405-SERIES

RESTRICTED TO —

SCALE NTS

SHEET 1 OF 2

REV A

1470-19 (1/15)





# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1617787-6](#)