

© 2021 TE Connectivity. All Rights Reserved.										8	7	6	5	4
--	--	--	--	--	--	--	--	--	--	---	---	---	---	---

										A-A		B-B		WIRE CRIMP Drahtcrimp											
-	-	-	-	-	-	1862029-5	A	CuFe2	PRESILVERED vorversilbert	A	0.35 - 0.5 FLR	E = 2.37 G = 2.45 D _{cr} = 0.8	H = 2.8 K = 3.1	0.5mm ² = 1.14 0.35mm ² = 1.09 0.5mm ² = 1.14 0.35mm ² = 1.09	MQC - Applicator 2837770-2	-	2.5	3.8	6.6	19.5	0.3				
-	-	-	-	-	-	-	-	-	-		0.2 - 0.5 FLK	E = 2.2 G = 2.2 D _{cr} = 0.8	H = 3.7 K = 3.8 D _{cr} = 2.0	0.20mm ² = 1.13 0.25mm ² = 1.15 0.35mm ² = 1.19 0.50mm ² = 1.26	MQC - Applicator 878426-2	539635-1 WITH DIE: mit Matrize 539744-2	2.5	3.8	6.6	19.5	0.3				
-	-	-	-	-	-	-	-	-	-	VERSION A	0.5 - 1.0 FLK	E = 2.8 G = 3.0 D _{cr} = 1.1	H = 4.5 K = 4.7 D _{cr} = 2.4	0.5mm ² = 1.38 0.75mm ² = 1.56 1.0mm ² = 1.57	MQC - Applicator 2-541689-2	539733-2 WITH DIE: mit Matrize 734249-0	3	4.2	5.8	19.5	0.4				
-	-	927839-2	C	-	-	-	-	CuSn4	PRETINNED vorverzinkt		>1.0 - 2.5 FLK	E = 3.8 G = 4.1 D _{cr} = 1.6	H = 5.7 K = 5.8 D _{cr} = 3.6	1.5mm ² = 1.76 2.0mm ² = 1.90 2.5mm ² = 2.04	MQC - Applicator 878367-2	539635-1 WITH DIE: mit Matrize 539733-2	3.5	4.7	6.3	19.5	0.4				
-	-	927839-1	C	-	-	-	-	CuFe2	PRETINNED vorverzinkt		>2.5 - 4.0 FLK	E = 4.6 G = 4.8 D _{cr} = 2.4	H = 6.3 K = 6.6 D _{cr} = 4.0	3.0mm ² = 2.13 3.5mm ² = 2.24 4.0mm ² = 2.35	MQC - Applicator 2-878314-2	539635-1 WITH DIE: mit Matrize 539734-2	4	5.2	6.8	19.5	0.6				
-	-	-	-	-	-	-	-	-	-		4.0 - 6.0 FLK	E = 5.2 G = 5.5 D _{cr} = 2.9	H = 7.3 K = 7.6 D _{cr} = 4.5	4.0mm ² = 2.17 5.0mm ² = 2.36 6.0mm ² = 2.55	MQC - Applicator 2-878738-2	-	4.2	5.6	7.7	20 20.4	0.6				
-	-	-	-	-	-	-	-	-	-		0.2 - 0.5 FLR	E = 2.2 G = 2.2 D _{cr} = 0.8	H = 2.8 K = 2.8 D _{cr} = 1.4	0.2mm ² = 1.13 0.35mm ² = 1.19 0.5mm ² = 1.26	MQC - Applicator 878427-2	-	2.5	3.8	6.6	19.5	0.3				
-	-	-	-	-	-	-	-	-	-		0.5 - 1.0 FLR	E = 2.8 G = 3.0 D _{cr} = 1.1	H = 3.9 K = 4.1 D _{cr} = 1.8	0.5mm ² = 1.43 0.75mm ² = 1.52 1.0mm ² = 1.61	MQC - Applicator 878328-2	169400-0 WITH DIE: mit Matrize 734781-1	3	4.2	5.8	19.5	0.4				
-	-	-	-	-	-	-	-	-	-		>1.0 - 2.5 FLR	E = 3.8 G = 4.1 D _{cr} = 1.6	H = 4.8 K = 4.9 D _{cr} = 2.6	1.25mm ² = 1.69 1.5mm ² = 1.76 2.0mm ² = 1.90 2.5mm ² = 2.04	MQC - Applicator 878356-2	169400-0 WITH DIE: mit Matrize 734251-0	3.5	4.7	6.3	19.5	0.4				
-	-	-	-	-	-	-	-	-	-		>2.5 - 4.0 FLR	E = 4.6 G = 4.8 D _{cr} = 2.4	H = 5.5 K = 5.7 D _{cr} = 3.3	3.0mm ² = 2.13 3.5mm ² = 2.24 4.0mm ² = 2.35	MQC - Applicator 2-878384-2	169400-0 WITH DIE: mit Matrize 734251-0	4	5.2	6.8	19.5	0.6				
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-	-	-	-	-	-	-	-	-	-																
-																									

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[927831-2 \(Cut Strip\)](#)