








POS.	DIM. A
2*6	39.70
2*5	33.70
2*4	27.70
2*3	21.70



1 MATERIAL:
LEVEL 1: PBT,STANDARD TEMPERATURE 105°C
KEY A:NATURAL; KEY B:PURPLE; KEY C:BLUE; KEY D:YELLOW

LEVEL 2: PA66,HIGH TEMPERATURE 150°C
KEY A:LIGHT GREY; KEY B:RED; KEY C:BLACK; KEY D:NATURAL

2 MATERIAL MARK:
LEVEL 1:PBT,LEVEL 2:HDT

3. APPLICABLE CONTACT P/N
RECEPTACLE CONTACT:1971237/1971779/81/83/85/87-*, 2238066-*


4. MATING CONN, P/N
CAP HSG: *-1971774/5-
TPA (LOCKING PLATE): *-1971778-*

5 GLOW WIRE COMPLIANT IN ACCORDANCE WITH IEC 60335-1. THIS IS BASED
ON THE PRODUCT MEETING A GWEPT 850° C TEST AND RESIN GWIT GREATER
THAN OR EQUAL TO 775° C.


LOC		DIST		REVISIONS				
-	-	P	LTR	DESCRIPTION	DATE	DWN	APVD	
			E	REVISED PER ECR-21-100678	08APR2021	SS	VS	
			F	REVISED PER ECR-20-100915	28APR2021	JP	VS	

THIS DRAWING IS A CONTROLLED DOCUMENT.					DWN		TOMMY WU		09JUL2012		TE Connectivity PLUG HOUSING, DOUBLE ROW POWER TRIPLE LOCK -													
DIMENSIONS:					CHK		HAPYE WU		09JUL2012															
mm					APVD		YUHONG MAO		09JUL2012						NAME									
					PRODUCT SPEC		108-106118		APPLICATION SPEC						114-106118		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO	
																	A1		00779		C=1971776		-	
																	Customer Drawing		SCALE		4:1		SHEET	


LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
-	-	SEE SHEET 1		-	-	-	




2*5 POSITIONS




KEYING FOR 2*5 POS.




2*4 POSITIONS



KEYING FOR 2*4 POS.




2*3 POSITIONS




KEYING FOR 2*3 POS.

2*6	LEVEL 1	KEY A	1-1971776-6
		KEY B	2-1971776-6
		KEY C	3-1971776-6
		KEY D	4-1971776-6
	LEVEL 2	KEY A	5-1971776-6
		KEY B	6-1971776-6
		KEY C	7-1971776-6
		KEY D	8-1971776-6
2*5	LEVEL 1	KEY A	1-1971776-5
		KEY B	2-1971776-5
		KEY C	3-1971776-5
		KEY D	4-1971776-5
	LEVEL 2	KEY A	5-1971776-5
		KEY B	6-1971776-5
		KEY C	7-1971776-5
		KEY D	8-1971776-5
POS.	MATERIAL	KEY	P/N

2*4	LEVEL 1	KEY A	1-1971776-4
		KEY B	2-1971776-4
		KEY C	3-1971776-4
		KEY D	4-1971776-4
	LEVEL 2	KEY A	5-1971776-4
		KEY B	6-1971776-4
		KEY C	7-1971776-4
		KEY D	8-1971776-4
2*3	LEVEL 1	KEY A	1-1971776-3
		KEY B	2-1971776-3
		KEY C	3-1971776-3
		KEY D	4-1971776-3
	LEVEL 2	KEY A	5-1971776-3
		KEY B	6-1971776-3
		KEY C	7-1971776-3
		KEY D	8-1971776-3
POS.	MATERIAL	KEY	P/N



2*6 POSITIONS



KEYING FOR 2*6 POS.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN TOMMY WU	09JUL2012	TE Connectivity PLUG HOUSING, DOUBLE ROW POWER TRIPLE LOCK					
		CHK HAPYE WU	09JUL2012						
		APVD YUZHONG MAO	09JUL2012						
		NAME							
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME					
mm				PRODUCT SPEC					
		0 PLC ±°		108-106118					
		1 PLC ±0.35		APPLICATION SPEC					
		2 PLC ±0.25		114-106118					
		3 PLC ±°		WEIGHT					
		4 PLC ±°		Customer Drawing					
ANGLES ±°		FINISH		SIZE		CAGE CODE	DRAWING NO	RESTRICTED TO	
MATERIAL		-		A1		00779	©=1971776	-	
		-							
							SCALE 4:1	SHEET 2 OF 2	REV F

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1971776-5](#)