

## COMPATIBILITY CHART

Material Dash Number	Material Description	RT Spec	Coating Slash No.	Coating S No.	
-3	POLYOLEFIN, SEMI-RIGID	RT-301	/42,/86,/180	S1017; S1048; S1030	
-4	POLYOLEFIN, FLEXIBLE	RT-1304	/42,/86,/180	S1017; S1048; S1030	
-12	FLUOROELASTOMER, FLEXIBLE	RT-1312	N/A	N/A	
-25	ELASTOMER, FLUID RESISTANT	RW-2070	/42,/86,/225	S1017; S1048; S1206	
-100	POLYOLEFIN, SEMI-FLEXIBLE ZEROHAL	RW-2082	/86; /180	S1048; S1030	

## Ordering Information



## NOTES

- 1) As supplied dimensions are for uncoated parts, when coating is added entry diameters will reduce by 1.5mm[.06] Max.
- 2) Potting Ports are optional, when specified by suffix "-00" they will be located as shown.

mm [INCHES]  PRAVEEN N T  CHK 0		01FEB2019	MATERIAL SEE SHEET 2			FINISH	FINISH _			
		1	01FEB2019							
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M TAYLOR	01FEB2019	TE Connectivity Ltd.					Ltd.	
0 PLC	± -	PRODUCT SPEC		NAME						
1 PLC	± -	_		TRANSITION, Y						
2 PLC	± -									
3 PLC	± -	APPLICATION SPEC		_						
4 PLC ANGLES	± - ± -	_		SIZE	CAGE CODE	DRAWING NO				RESTRICTED TO
4		WEIGHT		A4	00779	<b>C</b> - 382	2W042->	$\langle X-0 \rangle$		_
	<b>9</b>	CUSTOMER DRA	AWING				scale DNS	SHEET	2 of 2	2 REV 4

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 382W042-25-0