







RECOMMENDED PC BOARD HOLE PATTERN

PC BOARD THIKNESS 1.57 [.062]

HOUSING: GLASS FILLED FLAME RETARDANT POLYSTER, COLOR BLACK, CONTACTS: PHOSPHOR BRONZE.

- CONTACTS: DUPLEX PLATED 0.76 MICROMETERS [.000030] GOLD IN CONTACT AREA 3.81-7.62 MICROMETERS [.000150-.000300] BRIGHT TIN-LEAD ON SOLDER LEADS. ALL OVER 1.27[.000050] MIN NICKEL.
- $\boxed{3}$ TE CONNECTIVITY, CSA LOGO MOLDED INTO HOUSING.
- $\stackrel{\frown}{4}$ point of measurement for plating thikness, measured inside contact beams
- 5 POINT OF CONTACT DIMENSION.

CONTACTS: DUPLEX PLATED 0.76 MICROMETERS (.000030) GOLD IN CONTACT AREA 3.81-7.62 MICROMETERS (.000150-.000300) MATTE TIN ON SOLDER LEADS. ALL OVER 1.27 (.000050) MIN NICKEL.

- $\overline{2}$ ROHS 2002 /95/EC COMPLIANT.
- \mathbb{Z}_8 part number and date code marked in approximate location shown.
- 9 NO PART NUMBER MARKING REQUIRED FOR THIS PART.
- 10 FOR 2 POS, DATE CODES MARKED OPPOSITE SIDE OF TE CONNECTIVITY LOGO.
- 11 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

С

В

А

	\wedge	5.08[.200]	2.54[.100]	2	3-87879-9		
	$\overline{2}$	12.70[.500]	10.16[.400]	5	3-87879-8		
	$\overline{2}$	7.62[.300]	5.08[.200]	3	3-87879-7		
	$\overline{2}$	10.16[.400]	7.62[.300]	4	3-87879-6		
		101.60[4.000]	99.06[3.900]	40	3-87879-5		
I <u>ZIIN</u> I OBSOLETE	$\overline{2}$	99.06[3.900]	96.52[3.800]	39	3-87879-4	-	
		96.52[3.800]	93.98[3.700]	38	3-87879-3		
		93.98[3.700]	91.44[3.600]	37	3-87879-2	С	
		91.44[3.600]	88.90[3.500]	36	3-87879-1		
		88.90[3.500]	86.36[3.400]	35	3-87879-0		
		86.36[3.400]	83.82[3.300]	34	2-87879-9		
11		83.82[3.300]	81.28[3.200]	33	2-87879-8		
OBSOLETE		81.28[3.200]	78.74[3.100]	32	2-87879-7		
		78.74[3.100]	76.20[3.000]	31	2-87879-6	-	
		76.20[3.000]	73.66[2.900]	30	2-87879-5		
		73.66[2.900]	71.12[2.800]	29	2-87879-4		
		71.12[2.800]	68.58[2.700]	28	2-87879-3		
		68.58[2.700]	66.04[2.600]	27	2-87879-2		
		66.04[2.600]	63.50[2.500]	26	2-87879-1		
		63.50[2.500]	60.96[2.400]	25	2-87879-0		
		60.96[2.400]	58.42[2.300]	24	1-87879-9		
		58.42[2.300]	55.88[2.200]	23	1-87879-8		
		55.88[2.200]	53.34[2.100]	22	1-87879-7		
		53.34[2.100]	50.80[2.000]	21	1-87879-6	879	
		50.80[2.000]	48.26[1.900]	20	1-87879-5	87879	
OBSOLETE		48.26[1.900]	45.72[1.800]	19	1-87879-4	B	
	2	45.72[1.800]	43.18[1.700]	18	1-87879-3		
	/2	43.18[1.700]	40.64[1.600]	17	1-87879-2		
		40.64[1.600]	38.10[1.500]	16	1-87879-1		
	/2\	38.10[1.500]	35.56[1.400]	15	1-87879-0	-	
<u> </u>		35.56[1.400]	33.02[1.300]	14	87879-9	-	
	/2	33.02[1.300]	30.48[1.200]	13	87879-8	-	
	/2\	30.48[1.200]	27.94[1.100]	12	87879-7		
	/2\	27.94[1.100]	25.40[1.000]		87879-6	-	
	/2	22.86[.900]	20.32[.800]	9	87879-5	-	
	/2	17.78[.700]	15.24[.600]	7	87879-4		
	/2	15.24[.600]	12.70[.500]	6	87879-3		
	/2	25.40[1.00]	22.86[.900]				
	/2		17.78[.700]	10	87879-2		
	/2	20.32[.800]	17.78[.700]	8	87879-1	-	
FINISH		A	B	NO OF POSN	PART NUMBER		
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 12-20-93 - J KNAUB СНК 6-28-94			TE Connectivity	, .	
DIMENSIONS: TO	DIMENSIONS: TOLERANCES UNLESS OTHERWISE SPECIFIED:		+ D _ _		, 	A	
mm [INCHES]				SEMBLY,	MOD IV, SINGLE ROW		
0 PLC 1 PLC	± - ± -	PRODUCT SPEC 108-25022			AL ENTRY		
	± – ± .127[.005]	APPLICATION SPEC			· · · · · · · · · · · · · · · · · · ·	_	
4 PLC ANGLES	± - ± -	114-25018	SIZE CAGE CODE DRAWING NO		RESTRICTED TO		
		WEIGHT	A2 00779 C- 87				
	/2\/6\	CUSTOMER DRAWING		scale 4	:1 SHEET 1 OF 2 AA3]	

 LOC
 DIST
 REVISIONS

 AD
 OO
 P
 LTR
 DESCRIPTION
 DATE
 DWN
 APVD

 AA3
 REVISED PER ECO-11-004917
 11MAR11
 RK
 HMR

2

D

	THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION			
		ALL RIGHTS RESERVED.	-,	_	
	C COPYRIGHT - By -	ALL NOTIS NESLIVED.			
D					
	-				
С					
\cup					
	-				
В					
А					

3

۷											-
		DIST REVISIONS									
	AD	00 -	P LTR		DESCRIPTION			DATE	DWN	APVD	
			-	SEE S⊢	HEET 1			_	-	—	_
											D
$\land \land [$	\land	5 0 8	3[.20		2.54[.100]	2		8_8	7879	_9	
/10V9V	/6\		0[.5		10.16[.400]	5			<u>7879</u>		·
			_	_ 1	5.08[.200]	3			7879 7879		
/9\ \\OBSOLETE	/6\		2 <u>[.3</u> (7.62[.300]	4			<u>7879</u> 7879		
			$\frac{6}{0}$			40			7879 7879		
		101.6	_		<u>99.06[3.900]</u> 96.52[3.800]	39			<u>7879</u> 7879		1
	/6\	99.0				38			7879 7879		
-	<u>6</u> \	96.5			93.98 3.700	37			7879 7879		
-	<u>6</u> \	93.9			91.44 3.600	36			7879 7879		С
	/6\	91.4			88.90 3.500	35			<u>7879</u>		
	/6\	88.9			86.36[3.400]				7879 7879		
					83.82 3.300				<u>7879</u> 7879		
OBSOLETE			_	_	81.28 3.200	32			7879 7879		
	<u>/6\</u>				78.74 3.100				7879 7879		
	/6\	78.7			76.20[3.000]						
	<u>6</u> \	76.2	_	_	73.66 2.900				7879		
		73.6			71.12[2.800]	29			7879		
	<u>6</u> \	71.1		_	68.58[2.700]				7879		·
	<u>/6\</u>	68.5	1		66.04[2.600]				7879 7879		
	/6\	66.0·	_	_	63.50[2.500]						
	<u>6</u> \	63.5	_	_	60.96 2.400				7879		
	<u>6\</u>	60.9	_		58.42[2.300]		$\left \begin{array}{c} 7 \\ 7 \\ 7 \\ 7 \\ 7 \\ 7 \\ 7 \\ 7 \\ 7 \\ 7 $		7879		
	/6\	58.4			55.88 2.200				7879 7879		
-	/6\	55.8			53.34[2.100]				7879 7879		879
		53.3	_		50.80[2.000]				7879 7879		878
		50.8	_	_	48.26[1.900]	19			7879 7879		B
OBSOLETE		48.2			45.72 1.800	18			7879 7879		
		45.7			43.18[1.700]				7879 7879		
			_						7879 7879		1
		40.6	_	_	38.10[1.500]				7879		1
		38.1			<u>35.56</u> 1.400 33.02[1.300]				7879 7879		1
		33.0			30.48[1.200]				7879 7879		
	/6\	30.4			27.94[1.100]	12			7879 7879		
		27.9	_		25.40[1.000]	11			7879 7879		
OBSOLETE		22.8			20.32[.800]	9			7879		
-			8[.7		15.24[.600]	7			7879		
			<u>8</u> 4[.6		12.70[.500]	6			7879		
-			-0[1.		22.86[.900]	10			7879		
OBSOLETE	<u> </u>	20.3			17.78[.700]	8			7879 7879		
	/ 6 \	∠∪.∟		,001	1 / . / 0 . / 00	NO OF			, U / C	. 1	1
	FINISH		A		В	POSN		PART	NUMBE	2	
THIS DRAWING IS A CONTROLL	ED DOCUMFNT	DWN		12-20-93							1
		J KNAI CHK							A		
DIMENSIONS: TOLERANCES UNLESS OTHERWISE SPECIFIED:		A GAB	AIN Y		NAME						
mm [INCHES] 0 PLC	± -	- PRODUCT SF	PEC		CONNECTOR ASS				EROW		
1 PLC 2 PLC	± - ± -		08-25022 .100CL, DUAL ENTRY								
3 PLC 4 PLC	± .127[.005] ± -	APPLICATION SPEC						1			
ANGLES MATERIAL FINISH	$\frac{\pm -}{\wedge \wedge}$	WEIGHT - A200779 G=87879					-	_			
	2 6	CUSTON	/FR DR	AWING		SCALE 1:	1 SHEE	T 2 OF	2 REV	/	
									∠	AA3	1

2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 87879-8