


# CUSTOMER DRAWING



Product Name	NAS Equiv.	Product Dimensions			Cable Dimensions	
		L±1.52 (L±0.06)	B min	C min	D max	E min
D-142-50	1745-14	15.75 (0.620)	2.80 (0.110)	3.175 (0.125)	3.175 (0.125)	1.40 (0.055)
D-142-51	1745-15	15.75 (0.620)	4.45 (0.175)	5.08 (0.200)	5.08 (0.200)	2.54 (0.100)
D-142-52	1745-16	19.05 (0.750)	7.11 (0.280)	7.62 (0.300)	7.62 (0.300)	4.06 (0.160)


## MATERIALS

- INSULATION SLEEVE: Heat shrinkable, radiation cross-linked polyvinylidene fluoride.  
Color: natural.
- SOLDER PREFORM WITH FLUX:  
SOLDER: TYPE Cd18 per ANSI J-STD-006.  
FLUX: TYPE ROL0 per ANSI J-STD-004.
- MELTABLE RINGS: Thermally stabilized thermoplastic, one grey, and one blue.

## APPLICATION

- These parts are designed for shield terminations on cables having tin or silver plated shields and insulations rated for at least 105°C and falling within size range listed.
- These parts are designed to meet the requirements of Raychem Specification RT-1404. They also comply with National Aerospace Standard Part Drawing NAS-1745.  
See table above for equivalent size.
- For installation techniques, see Raychem Assembly Procedure RCPS 100-70.
- For other sizes available in this configuration, see Raychem Devices Specification Control Drawings D-142-56, -65 & -66.

For best results, prepare the cable as shown:



TE Connectivity, TE connectivity (logo), Raychem, and SolderSleeve are trademarks

		<b>Raychem</b> Devices	TITLE: <b>(105°C) SOLDERSLEEVE LOW TEMPERATURE</b>			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.			DOCUMENT NO.: <b>D-142-50/-51/-52</b>			
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A  ROUGHNESS IN MICRON	TE Connectivity reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.	Revision: <b>B2</b>		Issue Date: March 2020	
DRAWN BY: M. FORONDA	Drawn Date: 17-Jul-2000	ECO: ECO-20-003573	SCALE: None	SIZE: A	SHEET: 1 of 1	

If this document is printed it becomes uncontrolled. Check for the latest revision.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## TE Connectivity:

[D-142-50CS1787](#) [D-142-51CS918](#) [D-142-51CS2828](#) [D-142-51CS728](#) [8-1196660-7](#) [D-142-50CS2828](#) [2-1194907-2](#)  
[7-1191285-3](#) [2-1194194-9](#)