

		DESIGNED FOR USE WITH OSS SR CABLE ENTRY DIAMETER MINIMUM		REVISIONS																																																														
		HOUSING	.0875	REV	DESCRIPTION	DATE	APPROVED																																																											
		CONTACT	.0234	01	REVISED	01/10/88	BA																																																											
<table><tr><td>ELECTRICAL</td><td>MECHANICAL</td><td>ENVIRONMENTAL</td></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348 FIG. 319-1</td><td>Temperature Rating -65°C to 165°C</td></tr><tr><td>Frequency Range (GHz) D.C. TO 26.0</td><td>Recommended Mounting</td><td>Vibration - MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX) 250</td><td>Torque 7-8 IN-POUNDS</td><td>Shock - MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR 1.15 ± 0.015 (GHz)</td><td>Mating Characteristics:</td><td>Thermal shock MIL-STD-202, Method 107 Test Condition B</td></tr><tr><td>Insertion Loss .04 V/GHz</td><td>Insertion (MAX Lbs) N/A</td><td>Except High Temp 115°C</td></tr><tr><td>RF Leakage -60 dB MIN @ 6.0 TO 8.0 GHz</td><td>Withdrawal (MIN Oz) N/A</td><td>Moisture Resistance - MIL-STD-202, Method 106</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 190</td><td>Connector Engagement and Disengagement (In/Lbs MAX) 20</td><td>Corrosion - MIL-STD-202, Method 101, Condition B</td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) 750</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Axial 6.0 LBS MIN</td><td></td></tr><tr><td>Center Contact 4.0</td><td>Radial 4.0 IN-OUNCES</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Cable Retention</td><td></td></tr><tr><td>Cable To Housing (Milliohms MAX) 0.5</td><td>Axial Force 30 LBS</td><td></td></tr><tr><td>RF High Potential (VRMS MIN @ 5 MHz) 500</td><td>Torque 16 IN-OUNCES MIN</td><td></td></tr><tr><td>IR (Megohms) 5000</td><td>Weight (Grams) 2.0</td><td></td></tr></table>		ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348 FIG. 319-1	Temperature Rating -65°C to 165°C	Frequency Range (GHz) D.C. TO 26.0	Recommended Mounting	Vibration - MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX) 250	Torque 7-8 IN-POUNDS	Shock - MIL-STD-202, Method 213, Condition I	VSWR 1.15 ± 0.015 (GHz)	Mating Characteristics:	Thermal shock MIL-STD-202, Method 107 Test Condition B	Insertion Loss .04 V/GHz	Insertion (MAX Lbs) N/A	Except High Temp 115°C	RF Leakage -60 dB MIN @ 6.0 TO 8.0 GHz	Withdrawal (MIN Oz) N/A	Moisture Resistance - MIL-STD-202, Method 106	Corona, 70,000 Ft (VRMS MIN) 190	Connector Engagement and Disengagement (In/Lbs MAX) 20	Corrosion - MIL-STD-202, Method 101, Condition B	Dielectric Withstanding Voltage (VRMS MIN) 750	Center Contact Captivation		Contact Resistance (Milliohms MAX)	Axial 6.0 LBS MIN		Center Contact 4.0	Radial 4.0 IN-OUNCES		Outer Contact 2.0	Cable Retention		Cable To Housing (Milliohms MAX) 0.5	Axial Force 30 LBS		RF High Potential (VRMS MIN @ 5 MHz) 500	Torque 16 IN-OUNCES MIN		IR (Megohms) 5000	Weight (Grams) 2.0		<table><tr><td>HOUSING CAP</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>COUPLING NUT</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>RETAINING RING</td><td>BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H</td><td>N/A</td></tr><tr><td>GASKET</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr></table>		HOUSING CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204	COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A	GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348 FIG. 319-1	Temperature Rating -65°C to 165°C																																																																
Frequency Range (GHz) D.C. TO 26.0	Recommended Mounting	Vibration - MIL-STD-202, Method 204, Condition D																																																																
Volt Rating (VRMS MAX) 250	Torque 7-8 IN-POUNDS	Shock - MIL-STD-202, Method 213, Condition I																																																																
VSWR 1.15 ± 0.015 (GHz)	Mating Characteristics:	Thermal shock MIL-STD-202, Method 107 Test Condition B																																																																
Insertion Loss .04 V/GHz	Insertion (MAX Lbs) N/A	Except High Temp 115°C																																																																
RF Leakage -60 dB MIN @ 6.0 TO 8.0 GHz	Withdrawal (MIN Oz) N/A	Moisture Resistance - MIL-STD-202, Method 106																																																																
Corona, 70,000 Ft (VRMS MIN) 190	Connector Engagement and Disengagement (In/Lbs MAX) 20	Corrosion - MIL-STD-202, Method 101, Condition B																																																																
Dielectric Withstanding Voltage (VRMS MIN) 750	Center Contact Captivation																																																																	
Contact Resistance (Milliohms MAX)	Axial 6.0 LBS MIN																																																																	
Center Contact 4.0	Radial 4.0 IN-OUNCES																																																																	
Outer Contact 2.0	Cable Retention																																																																	
Cable To Housing (Milliohms MAX) 0.5	Axial Force 30 LBS																																																																	
RF High Potential (VRMS MIN @ 5 MHz) 500	Torque 16 IN-OUNCES MIN																																																																	
IR (Megohms) 5000	Weight (Grams) 2.0																																																																	
HOUSING CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204																																																																
COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																																
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A																																																																
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																																																
<table><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCE ON FRACTION DECIMAL ANGLES ± 1/64 ± .005 ± .1°</td></tr><tr><td colspan="3">These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.</td></tr><tr><td colspan="3">USE ASSY PROCEDURE</td></tr><tr><td colspan="3">NO AP 10-054</td></tr></table>		COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCE ON FRACTION DECIMAL ANGLES ± 1/64 ± .005 ± .1°			These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.			USE ASSY PROCEDURE			NO AP 10-054			<table><tr><td colspan="2">M/A-COM an AMP company</td><td colspan="2">M/A-COM, Inc. Waltham, MA 02254</td></tr><tr><td colspan="4">TITLE OSSM RIGHT ANGLE CABLE PLUG DIRECT SOLDER ATTACHMENT</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO 26805</td><td>1007-5015-92</td><td>REV 01</td></tr><tr><td colspan="2">SCALE 5:1</td><td colspan="2">SHEET 1 OF 1</td></tr></table>		M/A-COM an AMP company		M/A-COM, Inc. Waltham, MA 02254		TITLE OSSM RIGHT ANGLE CABLE PLUG DIRECT SOLDER ATTACHMENT				SIZE B	CODE IDENT NO 26805	1007-5015-92	REV 01	SCALE 5:1		SHEET 1 OF 1																																	
COMPONENT	MATERIAL	FINISH																																																																
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCE ON FRACTION DECIMAL ANGLES ± 1/64 ± .005 ± .1°																																																																		
These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.																																																																		
USE ASSY PROCEDURE																																																																		
NO AP 10-054																																																																		
M/A-COM an AMP company		M/A-COM, Inc. Waltham, MA 02254																																																																
TITLE OSSM RIGHT ANGLE CABLE PLUG DIRECT SOLDER ATTACHMENT																																																																		
SIZE B	CODE IDENT NO 26805	1007-5015-92	REV 01																																																															
SCALE 5:1		SHEET 1 OF 1																																																																

COPY IN PUERTO RICO

CUSTOMER

Tyco PART #1045418
SHEET 1 of 1 REV 0

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1007-5015-92](#)